

product type designation



W774-1 RJ45

IWLAN Access Point, SCALANCE W774-1 RJ45, 1 radio, 2 R-SMA antenna port, iFeatures support via KEY-PLUG, IEEE 802.11a/b/g/h/n, 2.4/5GHz, gross data rate 300 Mbit/s, 2x RJ45 max. 100 Mbit/s, PoE integrated 2-port switch, redundant 24 V DC, joint block, IP30, -20... 60 °C, plug slot WPA2/802.11i/e, observe national approvals! CERT ID: MSN-W1-RJ-E2, scope of delivery: Manuals on CD-ROM, German/English, 1x joint block; for operation outside of USA/Israel .

transfer rate

| | |
|---|----------------|
| transfer rate | |
| • with WLAN / maximum | 300 Mbit/s |
| • for Industrial Ethernet | 10, 100 Mbit/s |
| transfer rate / for Industrial Ethernet | |
| • minimum | 10 Mbit/s |
| • maximum | 100 Mbit/s |

interfaces

| | |
|--|----------------------------|
| number of electrical connections | |
| • for network components or terminal equipment | 2 |
| • for power supply | 1 |
| • for redundant voltage supply | 1 |
| type of electrical connection | |
| • for network components or terminal equipment | RJ45 socket |
| • for power supply | 4-pole screw terminal, PoE |
| design of the removable storage | |
| • C-PLUG | Yes |
| • KEY-PLUG | Yes |

memory

| | |
|---------------------------------|-----|
| design of the removable storage | |
| • C-PLUG | Yes |
| • KEY-PLUG | Yes |

interfaces / wireless

| | |
|--|----------------|
| number of radio cards / permanently installed | 1 |
| transmission mode / for multiple input multiple output (MIMO) | 2x2 |
| number of spatial streams | 2 |
| number of electrical connections / for external antenna(s) | 2 |
| type of electrical connection / for external antenna(s) | R-SMA (socket) |
| product feature / external antenna can be mounted directly on device | Yes |

supply voltage, current consumption, power loss

| | |
|--|---------|
| type of voltage / of the supply voltage | DC |
| supply voltage | |
| • from Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af | 48 V |
| consumed current | |
| • at DC / at 24 V / typical | 0.25 A |
| • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical | 0.125 A |
| power loss [W] | |

| | |
|--|---|
| <ul style="list-style-type: none"> • at DC / at 24 V / typical • with Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af / typical | 6 W |
| | 6 W |
| supply voltage / 1 | |
| <ul style="list-style-type: none"> • from terminal block | 19.2 V |
| supply voltage / 2 | |
| <ul style="list-style-type: none"> • from terminal block | 28.8 V |
| ambient conditions | |
| ambient temperature | |
| <ul style="list-style-type: none"> • during operation • during storage • during transport | -20 ... +60 °C |
| | -40 ... +85 °C |
| | -40 ... +85 °C |
| relative humidity / at 25 °C / without condensation / during operation / maximum | 97 % |
| ambient condition / for operation | When used under hazardous conditions (Zone 2), the SCALANCE W774-1 RJ45 or W734-1 RJ45 product must be installed in an enclosure. To comply with EN 50021, this enclosure must meet the requirements of at least IP 54 in compliance with EN 60529. |
| protection class IP | IP30 |
| design, dimensions and weights | |
| width | 26 mm |
| height | 156 mm |
| depth | 127 mm |
| width / of the enclosure / without antenna | 26 mm |
| height / of the enclosure / without antenna | 147 mm |
| depth / of the enclosure / without antenna | 127 mm |
| net weight | 0.52 kg |
| fastening method | wall mounting only if flat mounted |
| <ul style="list-style-type: none"> • S7-300 rail mounting • S7-1500 rail mounting • 35 mm top hat DIN rail mounting • wall mounting | Yes |
| | Yes |
| | Yes |
| | Yes |
| radio frequencies | |
| operating frequency | |
| <ul style="list-style-type: none"> • for WLAN in 2.4 GHz frequency band • for WLAN in 5 GHz frequency band | 2.41 ... 2.48 GHz; depending on the country approvals |
| | 4.9 ... 5.8 GHz; depending on the country approvals |
| product features, product functions, product components / general | |
| product function / Access Point Mode | Yes |
| product function / client Mode | Yes |
| number of SSIDs | 4 |
| product function | |
| <ul style="list-style-type: none"> • iPCF Access Point • iPCF client • iPCF-MC Access Point • iPCF-MC client | Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' |
| | Yes; Only in combination with the 'KEY-PLUG W740 iFeatures' |
| | No |
| | Yes; Only in combination with the 'KEY-PLUG W740 iFeatures' |
| number of iPCF-capable radio modules | 1 |
| product function / iREF | Yes; Only in combination with the 'KEY-PLUG W780 iFeatures' or 'KEY-PLUG W740 iFeatures' |
| number of iREF-capable radio modules | 1 |
| product function / iPRP | Yes; In combination with the 'KEY-PLUG W780 iFeatures' only |
| product functions / management, configuration, engineering | |
| number of manageable IP addresses / in client | 8 |
| product function | |
| <ul style="list-style-type: none"> • CLI • web-based management • MIB support • TRAPs via email • configuration with STEP 7 • configuration with STEP 7 in the TIA Portal • operation with IWLAN controller • operation with Enterasys WLAN controller • forced roaming on IP down with IWLAN | Yes |
| | Yes |
| | Yes |
| | Yes |
| | Yes |
| | Yes |
| | No |
| | No |
| | Yes |

| | |
|--|--|
| <ul style="list-style-type: none"> • forced roaming on link down with IWLAN | Yes |
| <ul style="list-style-type: none"> • WDS | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • Address Resolution Protocol (ARP) | Yes |
| <ul style="list-style-type: none"> • ICMP | Yes |
| <ul style="list-style-type: none"> • Telnet | Yes |
| <ul style="list-style-type: none"> • HTTP | Yes |
| <ul style="list-style-type: none"> • HTTPS | Yes |
| <ul style="list-style-type: none"> • TFTP | Yes |
| <ul style="list-style-type: none"> • DCP | Yes |
| <ul style="list-style-type: none"> • LLDP | Yes |
| identification & maintenance function | |
| <ul style="list-style-type: none"> • I&M0 - device-specific information | Yes |
| <ul style="list-style-type: none"> • I&M1 - higher level designation/location designation | Yes |
| product functions / diagnostics | |
| product function | |
| <ul style="list-style-type: none"> • PROFINET IO diagnosis | Yes |
| <ul style="list-style-type: none"> • link check | No |
| <ul style="list-style-type: none"> • connection monitoring IP-Alive | No |
| <ul style="list-style-type: none"> • localization via Aeroscout | Yes |
| <ul style="list-style-type: none"> • SysLog | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • SNMP v1 | Yes |
| <ul style="list-style-type: none"> • SNMP v2 | Yes |
| <ul style="list-style-type: none"> • SNMP v3 | Yes |
| product functions / VLAN | |
| product function | |
| <ul style="list-style-type: none"> • function VLAN with IWLAN | Yes |
| product functions / DHCP | |
| product function | |
| <ul style="list-style-type: none"> • DHCP client | Yes |
| <ul style="list-style-type: none"> • DHCP server | Yes |
| <ul style="list-style-type: none"> • DHCP Option 82 | Yes |
| product functions / redundancy | |
| protocol / is supported | |
| <ul style="list-style-type: none"> • STP/RSTP | Yes |
| <ul style="list-style-type: none"> • MSTP | Yes |
| <ul style="list-style-type: none"> • RSTP | Yes |
| product functions / security | |
| product function | |
| <ul style="list-style-type: none"> • ACL - MAC-based | Yes |
| <ul style="list-style-type: none"> • management security, ACL-IP based | Yes |
| <ul style="list-style-type: none"> • IEEE 802.1x (radius) | Yes |
| <ul style="list-style-type: none"> • NAT/NAPT | Yes |
| <ul style="list-style-type: none"> • access protection according to IEEE802.11i | Yes |
| <ul style="list-style-type: none"> • WPA/WPA2 | Yes |
| <ul style="list-style-type: none"> • TKIP/AES | Yes |
| protocol / is supported | |
| <ul style="list-style-type: none"> • SSH | Yes |
| <ul style="list-style-type: none"> • RADIUS | Yes |
| product functions / time | |
| protocol / is supported | |
| <ul style="list-style-type: none"> • NTP | Yes |
| <ul style="list-style-type: none"> • SNTP | Yes |
| <ul style="list-style-type: none"> • SIMATIC time synchronization (SIMATIC Time) | Yes |
| standards, specifications, approvals | |
| standard | |
| <ul style="list-style-type: none"> • for FM | FM 3611: Class I, Division 2, Groups A,B,C,D, T4 / Class 1, Zone 2, Group IIC, T4, FM16US0205X |
| certificate of suitability | |
| <ul style="list-style-type: none"> • EC Declaration of Conformity | Yes |

| | |
|---|---|
| <ul style="list-style-type: none"> • CE marking • C-Tick • E1 approval • railway application in accordance with EN 50155 • railway application in accordance with EN 50121-4 • NEMA TS2 • IEC 61375 • IEC 61850-3 • NEMA4X • Power-over-Ethernet according to IEEE802.3at for type 1 and IEEE802.3af • Power-over-Ethernet according to IEEE802.3at for type 2 | Yes Yes No No No No No No No Yes Yes |
| standard for wireless communication <ul style="list-style-type: none"> • IEEE 802.11a • IEEE 802.11b • IEEE 802.11e • IEEE 802.11g • IEEE 802.11h • IEEE 802.11i • IEEE 802.11n | Yes Yes Yes Yes Yes Yes Yes |
| wireless approval | You will find the current list of countries at: www.siemens.de/funkzulassungen |
| standards, specifications, approvals / marine classification | |
| Marine classification association <ul style="list-style-type: none"> • American Bureau of Shipping Europe Ltd. (ABS) • French marine classification society (BV) • DNV GL • Korean Register of Shipping (KRS) • Lloyds Register of Shipping (LRS) • Nippon Kaiji Kyokai (NK) • Polski Rejestr Statkow (PRS) • Royal Institution of Naval Architects (RINA) | Yes Yes Yes Yes Yes Yes Yes Yes |
| standards, specifications, approvals / hazardous environments | |
| standard / for hazardous zone <ul style="list-style-type: none"> • from CSA and UL | EN 60079-15:2005, EN 60079-0:2006, II 3 G Ex nA II T4 KEMA 07 ATEX 0145X ANSI/ISA 12.12.01-2013, CAN/CSA C22.2 No.213-M1987, Cl. 1, div. 2, GP. A, B, C, D, T4 / Cl. 1, Zone 2, GP IIC E240480 |
| certificate of suitability / CCC / for hazardous zone according to GB standard <ul style="list-style-type: none"> • as marking | Yes Ex nA IIC T4 Gc |
| accessories | |
| accessories | 24 V DC screw terminal included in scope of delivery |
| further information / internet links | |
| internet link <ul style="list-style-type: none"> • to website: TIA Selection Tool • to web page: selection aid TIA Selection Tool • to the website: IWLAN • to website: Industry Mall • to website: Information and Download Center • to website: Image database • to website: CAX-Download-Manager • to website: Industry Online Support | http://www.siemens.com/tia-selection-tool http://www.siemens.com/tia-selection-tool http://www.siemens.com/iwlan https://mall.industry.siemens.com http://www.siemens.com/industry/infocenter http://automation.siemens.com/bilddb http://www.siemens.com/cax https://support.industry.siemens.com |
| security information | |
| security information | Siemens provides products and solutions with industrial security functions that support the secure operation of plants, solutions, machines, equipment and/or networks. They are important components in a holistic industrial security concept. With this in mind, Siemens' products and solutions undergo continuous development. Siemens recommends strongly that you regularly check for product updates. For the secure operation of Siemens products and solutions, it is necessary to take suitable preventive action(e.g. cell protection concept) and integrate each component into a holistic, state-of-the-art industrial security concept. Third-party products that may be in use should also be considered. For more information about industrial security, visit http://www.siemens.com/industrialsecurity . To stay informed about product updates as they occur, sign up for a product-specific newsletter. For more information, visit http://support.automation.siemens.com . (V3.4) |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

6GK57741FX000AA0