


product type designation



Antenna ANT793-8DP

ANT793-8DP IWLAN antenna with strong directional effect incl. N-female plug: 13/13.5 dBi; IP66/67; (-40-+80 °C); 4.9-5.35 GHz; Wi-Fi compliance and observe national approvals! Mounting on wall or mast; Compact instructions as hard copy German/English; scope of delivery: 1x ANT793-8DP, 1x mounting aid for alignment

radio frequencies	
type of wireless network / is supported	WLAN
operating frequency	
• for WLAN in 5 GHz frequency band 1	4.9 ... 5.35 GHz
antenna gain compared to spherical radiator	
• of the WLAN antenna / in the 5 GHz frequency band	13.5 dB
electrical data	
impedance	50 Ω
polarization	linear vertical
radiation characteristic	directional
antenna gain compared to spherical radiator	
• of the WLAN antenna / in the 5 GHz frequency band	13.5 dB
standing wave ratio (VSWR) / maximum	1.5
radiating angle of the antenna	
• in the 5 GHz frequency band / horizontal	40°
• in the 5 GHz frequency band / vertical	35°
number of electrical connections / of the antenna	1
type of electrical connection / of the antenna	N-Connector
design of plug-in connection	female
angle of inclination / downward / maximum	0°
front-to-back ratio	20 dB
mechanical data	
material	
• of outer shell	Lexan EXL 9330
ambient conditions	
ambient temperature	
• during operation	-40 ... +80 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
protection class IP	IP66/67
wind load / maximum	15 N; frontal at 160 km/h
design, dimensions and weights	
width	80 mm
height	101 mm
depth	35 mm
net weight	110 g
fastening method	
• mast mounting	Yes
• wall mounting	Yes

<ul style="list-style-type: none"> • roof mounting 	No
<ul style="list-style-type: none"> • directly on the device 	No
product features, product functions, product components / general	
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	
<ul style="list-style-type: none"> • RoHS conformity 	Yes
<ul style="list-style-type: none"> • railway application in accordance with EN 50155 	Yes
<ul style="list-style-type: none"> • fire protection in accordance with EN 45545-2 	Yes
product conformity	UL 94-V0
wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
reference code / according to IEC 81346-2:2019	TFB
further information / internet links	
internet link	
<ul style="list-style-type: none"> • to web page: selection aid TIA Selection Tool 	http://www.siemens.com/snst
<ul style="list-style-type: none"> • to website: Industrial communication 	http://www.siemens.com/simatic-net
<ul style="list-style-type: none"> • to website: Industry Mall 	https://mall.industry.siemens.com
<ul style="list-style-type: none"> • to website: Information and Download Center 	http://www.siemens.com/industry/infocenter
<ul style="list-style-type: none"> • to website: Image database 	http://automation.siemens.com/bilddb
<ul style="list-style-type: none"> • to website: CAX-Download-Manager 	http://www.siemens.com/cax
<ul style="list-style-type: none"> • to website: Industry Online Support 	https://support.industry.siemens.com
last modified:	4/28/2023 

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

6GK57938DP000AA0