

product type designation

Antenna ANT795-6MN

ANT795-6MN antenna with omnidirectional Characteristic; incl. N-Connect female plug; 6/8 dBi; IP65 (-40-+70 °C), WLAN 2.4/5 GHz and private 5G networks; Wi-Fi compliance and observe national approvals; mounting on roof and vehicles; compact instructions as hard copy German/English; scope of delivery: 1x ANT795-6MN, for mounting, the mounting aid 6GK5795-6MN01-0AA6 is available.



radio frequencies

type of wireless network / is supported	5G private networks, WLAN
operating frequency / 1	2400 ... 2700 MHz
operating frequency / 2	3400 ... 3800 MHz
operating frequency / 3	4900 ... 5925 MHz
operating frequency / 4	5925 ... 7125 MHz
antenna gain compared to spherical radiator	
• with linear radiation / in operating frequency area 1 / typical	6 dB
• with linear radiation / in operating frequency area 2 / typical	6 dB
• with linear radiation / in operating frequency area 3 / typical	8 dB
• with linear radiation / in operating frequency area 4 / typical	8 dB

electrical data

impedance	50 Ω
polarization	linear vertical
radiation characteristic	omnidirectional
standing wave ratio (VSWR) / maximum	2
radiating angle of the antenna	
• horizontal	360°
• in the 5 GHz frequency band / horizontal	150°
• in the 5 GHz frequency band / vertical	take the antenna diagram into account regarding the horizontal beam angle
number of electrical connections / of the antenna	1
type of electrical connection / of the antenna	N-Connector
design of plug-in connection	female
angle of inclination / downward / maximum	0°

mechanical data

material	
• of outer shell	Polycarbonate

ambient conditions

ambient temperature	
• during operation	-40 ... +80 °C
• during storage	-40 ... +80 °C
• during transport	-40 ... +80 °C
protection class IP	IP65
wind load / maximum	10 N; at 160 km/h

design, dimensions and weights

width	86 mm
-------	-------

height	43 mm
depth	86 mm
net weight	300 g
fastening method	
• mast mounting	No
• flat roof mounting	Yes
• wall mounting	Yes
• roof mounting	Yes
• directly on the device	No
product features, product functions, product components / general	
product feature / silicon-free	Yes
standards, specifications, approvals	
certificate of suitability	Railway application in accordance with NF-F-16-101, NF-F-16-102
certificate of suitability	
• RoHS conformity	Yes
• railway application in accordance with EN 50155	Yes
• fire protection in accordance with EN 45545-2	Yes
Marine classification association / Korean Register of Shipping (KRS)	Yes
product conformity	UL 94-V0
wireless approval	Current national approvals can be found on the Internet under www.siemens.com/funkzulassungen
reference code / according to IEC 81346-2:2019	TFB
further information / internet links	
internet link	
• to web page: selection aid TIA Selection Tool	http://www.siemens.com/snst
• to website: Industrial communication	http://www.siemens.com/simatic-net
• to website: Industry Mall	https://mall.industry.siemens.com
• to website: Information and Download Center	http://www.siemens.com/industry/infocenter
• to website: Image database	http://automation.siemens.com/bilddb
• to website: CAX-Download-Manager	http://www.siemens.com/cax
• to website: Industry Online Support	https://support.industry.siemens.com

last modified:

4/28/2023 

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

[6GK57956MN100AA6](#)