SIEMENS

Data sheet

US2:52BP2B2XB



30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Illuminated Push-Pull Operator Full Voltage, 6V AC LED Lamp Mushroom Head Cap Small 1 3/4" (44.5 mm) Metal, Black with Red Lens 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure I number of command points 1 delivery state as a kit No Actuator Product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring metal color of the front ring metal color of the front ring Metal Contact block/ lampholder Socket design socket design A 9 swith LED number of Lampholders 1 Display Incomponent number of LED modules 1 General technical data Yes dedgree of pollution 1 type of voltage AC/DC of the input voltage AC/DC of the input voltage of the light source Yes degree of pollution 1 type of voltage of the supply voltage of the light source AC/DC of the minal IP20 Supply voltage of the su		
number of command points 1 delivery state as a kit No Actuator product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Front ring product component front ring Yes design of the front ring metal adsign of the front ring metal metal color of the front ring front ring material of the holder Metal Color of the front ring black front ring front ring<		Actuator round
delivery state as a kit No Actualor		
Actuator Or product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring metal color of the front ring metal color of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder metal socket design BA 9s with LED number of LED modules 1 Olareat block/ lampholders 1 Socket design No elight source Yes degree of pollution 1 type of voltage AC/DC e of the operating voltage AC/DC e of the input voltage AC/DC surge voltage of the light source AC/DC voltage of the light source FPO6 voltage of the light source AC/DC surge voltage of the light source AC/DC voltage of the light source AC/DC		
product extension optional light source Yes material of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of LED modules 1 General technical data General technical data product component Yes elight source Yes degree of pollution 1 type of voltage AC/DC e of the input voltage AC/DC C surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage AC/DC supply voltage of the light source AC/DC		No
metal of the actuating element metal mushroom head with plastic lens type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of LED modules 1 General technical data General technical data product component Yes eight source Yes degree of pollution 1 type of voltage Yes of the operating voltage AC/DC of the front ring IP20 Supply voltage of the light source AC/DC supply voltage of the light source AC/DC		
type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring	· · · · · · · · · · · · · · · · · · ·	
number of switching positions 2 Front ring yes design of the front ring standard material of the front ring metal color of the front ring black Holder metal Contact block/ lampholder socket design socket design BA 9s with LED number of LED modules 1 Display 1 material of the includes 1 General technical data Yes product component Yes ilight source Yes degree of pollution 1 type of voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	material of the actuating element	metal mushroom head with plastic lens
Front ring Yes gesign of the front ring standard material of the front ring metal color of the front ring black Holder metal colar of the front ring black Holder Metal Contact block/ lampholder gesign socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data Yes degree of pollution 1 type of voltage AC/DC of the operating voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC	type of unlocking device	
product component front ring Yes design of the front ring standard material of the front ring black Holder Metal Contact block/ lampholder Metal Socket design BA 9s with LED number of lampholders 1 Display 0 number of LED modules 1 General technical data Yes product component No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the light source at AC at 60 Hz AC/DC	number of switching positions	2
design of the front ring standard material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal Contact block/ lampholder socket design socket design BA 9s with LED number of lampholders 1 Display 1 General technical data product component • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	Front ring	
material of the front ring metal color of the front ring black Holder Metal Contact block/ lampholder Socket design socket design BA 9s with LED number of lampholders 1 Display 1 General technical data 1 general technical data Yes degree of pollution 1 tight source Yes degree of pollution 1 type of voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage AC/DC surge of voltage of the light source at AC at 60 Hz AC/DC	product component front ring	Yes
color of the front ring black Holder Metal Contact block/ lampholder Metal contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data	design of the front ring	standard
Holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Impholder ilight source Yes degree of pollution 1 type of voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	material of the front ring	metal
material of the holder Metal Contact block/ lampholder BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Intervention Import light source Yes degree of pollution 1 type of voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC	color of the front ring	black
Contact block/ lampholder socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component No • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	Holder	
socket design BA 9s with LED number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component Image: Socket design • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	material of the holder	Metal
number of lampholders 1 Display 1 number of LED modules 1 General technical data 1 product component No • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage AC/DC supply voltage of the light source AC/DC	Contact block/ lampholder	
Display 1 number of LED modules 1 General technical data 1 product component 1 • lamp transformer No • light source Yes degree of pollution 1 type of voltage AC/DC • of the operating voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC	socket design	BA 9s with LED
number of LED modules 1 General technical data	number of lampholders	1
General technical data product component Image: Im	Display	
product component No e lamp transformer No e light source Yes degree of pollution 1 type of voltage e of the operating voltage AC/DC of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 e of the terminal IP20 Supply voltage AC/DC	number of LED modules	1
• lamp transformerNo• light sourceYesdegree of pollution1type of voltage-• of the operating voltageAC/DC• of the input voltageAC/DC• of the input voltage4 kVprotection class IPIP66• of the terminalIP20Supply voltage of the supply voltage of the light sourceAC/DCsupply voltageAC/DC	General technical data	
• light source Yes degree of pollution 1 type of voltage - • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage of the supply voltage of the light source AC/DC supply voltage of the supply voltage of the light source at AC at 60 Hz AC/DC	product component	
degree of pollution 1 type of voltage - • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage - type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz -	lamp transformer	No
type of voltage AC/DC • of the operating voltage AC/DC • of the input voltage AC/DC surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage type of voltage of the supply voltage of the light source type of voltage of the supply voltage of the light source AC/DC	light source	Yes
of the operating voltage of the input voltage of the input voltage AC/DC AC/DC AC/DC surge voltage resistance rated value 4 kV protection class IP of the terminal IP66 IP20 IP20 Supply voltage of the supply voltage of the light source AC/DC AC/DC supply voltage of the supply voltage of the light source AC/DC	degree of pollution	1
	type of voltage	
surge voltage resistance rated value 4 kV protection class IP IP66 • of the terminal IP20 Supply voltage IP20 supply voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz IP20	 of the operating voltage 	AC/DC
protection class IP IP66 • of the terminal IP20 Supply voltage IP20 type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	 of the input voltage 	AC/DC
of the terminal IP20 Supply voltage type of voltage of the supply voltage of the light source at AC at 60 Hz	surge voltage resistance rated value	4 kV
Supply voltage type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	protection class IP	IP66
type of voltage of the supply voltage of the light source AC/DC supply voltage of the light source at AC at 60 Hz AC/DC	• of the terminal	IP20
supply voltage of the light source at AC at 60 Hz	Supply voltage	
	type of voltage of the supply voltage of the light source	AC/DC
	supply voltage of the light source at AC at 60 Hz	
• rated value 8 6 V	rated value	8 6 V
supply voltage of the light source at DC	supply voltage of the light source at DC	
• rated value 8 6 V	 rated value 	8 6 V
Connections/ Terminals	Connections/ Terminals	
type of electrical connection screw-type terminals	type of electrical connection	screw-type terminals

 of modules and accessories 	Screw-type terminal	
tightening torque of the screws in the bracket	20 N·m	
tightening torque [lbf·in] with screw-type terminals	8 8 lbf-in	
Lamp		
type of light source	LED	
color of the light source	red	
Safety related data		
touch protection against electrical shock	finger-safe	
Ambient conditions		
ambient temperature		
during operation	-35 +70 °C	
during storage	-40 +85 °C	
Installation/ mounting/ dimensions		
shape of the installation opening	round	
Certificates/ approvals		
Further information		
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875 Information- and Downloadcenter (Catalogs, Brochures,) https://www.siemens.com/ic10 Industry Mall (Online ordering system) https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2B2XB Cax online generator		
http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2B2XB		
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2B2XB		
Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,) http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52BP2B2XB⟨=en		

last modified:

5/31/2021 🖸

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens: 52BP2B2XB