SIEMENS

Data sheet

US2:52BP2W2



30mm BlackMax, Epoxy Coated Corrosion Resistant Metal Operator, Round Push-Pull Operator Non-Illuminated Mushroom Head Cap Small 1 3/4" (44.5 mm) Plastic, Red 2 Position Maintained, Pull-to-Release UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards

design of the product Actuator round Enclosure 1 number of command points 1 delivery state as a kit No Actuator material of the actuating element plastic pull-to-unlatch mechanism number of switching positions 2 Front ring yes design of the front ring standard material of the holder metal color of the front ring metal color of the holder Metal General technical data product component protect component 1 e light source No degree of pollution 1 protection class IP IP66 Ambient conditions			
number of command points 1 delivery state as a kit No Actuator	design of the product	Actuator round	
Actuator No Actuator plastic material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring general technical data product component front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data motor product component No élight source No degree of pollution 1 protections ambient temperature é during operation -35 +70 °C - during storage -40 +85 °C	nclosure		
Actuator plastic material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring 2 product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data model product component 1 e light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C ambient temperature -40 +85 °C Installation/ mounting/ dimensions -40 +85 °C	number of command points	1	
material of the actuating element plastic type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring 2 product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data 0 product component 1 • light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C ambient temperature -40 +85 °C Installation/ mounting/ dimensions -35 +70 °C	delivery state as a kit	No	
type of unlocking device pull-to-unlatch mechanism number of switching positions 2 Front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data product component • light source No degree of pollution 1 protection class IP IP66 Ambient temperature -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Image: Store of Stor	ctuator		
number of switching positions 2 Front ring product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data module product component No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C ambient temperature -35 +70 °C oduring storage -40 +85 °C	material of the actuating element	plastic	
Front ring Front ring product component front ring Standard material of the front ring metal color of the front ring black Holder Metal General technical data Metal product component No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C amblent temperature -40 +85 °C Installation/mounting/ dimensions -40 +85 °C	type of unlocking device	pull-to-unlatch mechanism	
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black Holder material of the holder material of the holder Metal General technical data modulate product component No e light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C ambient temperature -40 +85 °C Installation/mounting/ dimensions -35 +70 °C	number of switching positions	2	
design of the front ring standard material of the front ring metal color of the front ring black Holder Metal General technical data	ront ring		
material of the front ring metal color of the front ring black Holder Metal General technical data Metal groduct component No • light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C • during operation -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Installation/ mounting/ dimensions	product component front ring	Yes	
color of the front ring black Holder Metal General technical data Metal product component No • light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C • during operation -35 +85 °C Installation/ mounting/ dimensions -40 +85 °C	design of the front ring	standard	
Holder Metal General technical data	material of the front ring	metal	
material of the holder Metal General technical data Metal product component No e light source No degree of pollution 1 protection class IP IP66 Ambient conditions -35 +70 °C e during operation -35 +70 °C e during storage -40 +85 °C Installation/ mounting/ dimensions	color of the front ring	black	
General technical data product component • light source No degree of pollution 1 protection class IP IP66 Ambient conditions ambient temperature • during operation -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Installation/ mounting/ dimensions	older		
product component No • light source No degree of pollution 1 protection class IP IP66 Ambient conditions IP66 ambient temperature -35 +70 °C • during operation -35 +70 °C • during storage -40 +85 °C	material of the holder	Metal	
• light source No degree of pollution 1 protection class IP IP66 Ambient conditions IP66 ambient temperature -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Installation/ mounting/ dimensions	eneral technical data		
degree of pollution 1 protection class IP IP66 Ambient conditions IP66 ambient temperature -35 +70 °C • during operation -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Installation/ mounting/ dimensions	product component		
protection class IP IP66 Ambient conditions IP66 ambient temperature -35 +70 °C • during operation -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions Installation/ mounting/ dimensions	light source	No	
Ambient conditions ambient temperature • during operation • during storage -40 +85 °C	degree of pollution	1	
ambient temperature -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions -40 +85 °C	protection class IP	IP66	
• during operation -35 +70 °C • during storage -40 +85 °C Installation/ mounting/ dimensions	mbient conditions		
• during storage -40 +85 °C Installation/ mounting/ dimensions	ambient temperature		
Installation/ mounting/ dimensions	 during operation 	-35 +70 °C	
	during storage	-40 +85 °C	
	Installation/ mounting/ dimensions		
shape of the installation opening round	shape of the installation opening	round	
Certificates/ approvals			
Further information			
Siemens has decided to exit the Russian market (see here). https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business Siemens is working on the renewal of the current EAC certificates. Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products of the supervised EAC large the second status of validity of the EAC certification if you intend to import or offer to supply these products of the supervised EAC large the second status of validity of the EAC certification if you intend to import or offer to supply these products of the second s			
EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus). Information on the packaging https://support.industry.siemens.com/cs/ww/en/view/109813875			
Information- and Downloadcenter (Catalogs, Brochures,) <u>https://www.siemens.com/ic10</u> Industry Mall (Online ordering system)			
https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52BP2W2 Cax online generator http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52BP2W2			
Service&Support (Manuals, Certificates, Characteristics, FAQs,) https://support.industry.siemens.com/cs/ww/en/ps/US2:52BP2W2 Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros,)			

_Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, .

7/26/2023

last modified:

5/31/2021 🖸

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens: 52BP2W2