SIEMENS

Data sheet US2:52SX2BABK7

30mm BlackMax, Epoxy Coated Corrosion Resistant Complete Metal Unit Non-Illuminated Selector Switch, Short Lever Black with White Insert 3 Position, B-CAM Maintained with 4 N.O. Heavy Duty Contacts, A600/P600 UL Listed, CSA Certified NEMA 1,3,3R,4,4X,12,13 & Automotive Standards



number of command points delivery state as a kit No Actuator material of the actuating element number of contact modules type of unlocking device number of switching positions Front ring product component front ring design of the front ring material of the front ring material of the front ring material of the front ring moduct function positive opening product component • light source insulation voltage rated value poperating frequency maximum thermal current number of NC contacts for auxiliary contacts number of NC contacts for auxiliary contacts operation at 230 V rated value e at 230 V rated value
Actuator material of the actuating element number of contact modules 4 type of unlocking device rotate-to-unlatch mechanism number of switching positions 3 Front ring product component front ring design of the front ring material of the front ring metal color of the front ring product function positive opening product component • light source insulation voltage rated value protection class IP of the terminal operating frequency maximum thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value final plastic plastic rotate-to-unlatch mechanism netal standard metal
material of the actuating element number of contact modules 4 type of unlocking device number of switching positions 3 Front ring product component front ring design of the front ring material of the front ring color of the front ring black General technical data product function positive opening product component • light source Insulation voltage rated value protection class IP of the terminal operating frequency maximum themal current 10 A Auxillary circuit number of NC contacts for auxilliary contacts o at 110 V rated value end for a voltage rated value for A operational current at AC-15
number of contact modules type of unlocking device number of switching positions Front ring product component front ring design of the front ring material of the front ring color of the front ring black General technical data product function positive opening product component • light source insulation voltage rated value protection class IP of the terminal operating frequency maximum themal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts nature of NO contacts for auxiliary contacts of at 110 V rated value e Insulation voltage at AC-15 of at 110 V rated value for the terminal operational current at AC-15 of at 110 V rated value for the terminal operational current at AC-15 of at 110 V rated value for the terminal operational current at AC-15 of at 110 V rated value for the terminal operational current at AC-15 of at 110 V rated value for the terminal operational current at AC-15 of at 110 V rated value for the terminal operational current at AC-15 operational current at AC-15 operational current at AC-15 operational current at AC-15
type of unlocking device rotate-to-unlatch mechanism number of switching positions 3 Front ring product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black General technical data product function positive opening No product component • light source No insulation voltage rated value 600 V protection class IP IP66 • of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 4 operational current at AC-15 • at 110 V rated value 60 A
number of switching positions Front ring product component front ring design of the front ring material of the front ring color of the front ring black General technical data product function positive opening product component • light source insulation voltage rated value protection class IP • of the terminal operating frequency maximum thermal current Auxilliary circuit number of NC contacts for auxiliary contacts • at 110 V rated value 9 Yes 4 standard Yes Ausiliary circuit 10 A Auxilliary circuit operational current at AC-15 • at 110 V rated value 60 A
product component front ring Yes design of the front ring standard material of the front ring metal color of the front ring black General technical data product function positive opening No product component • light source No insulation voltage rated value 600 V protection class IP • of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxilliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 4 operational current at AC-15 • at 110 V rated value 600 A
product component front ring design of the front ring material of the front ring material of the front ring metal color of the front ring black General technical data product function positive opening product component light source No insulation voltage rated value protection class IP of the terminal operating frequency maximum thermal current Auxiliary circuit number of NC contacts for auxiliary contacts operational current at AC-15 at 110 V rated value 60 A
design of the front ring material of the front ring metal color of the front ring black General technical data product function positive opening No product component • light source Insulation voltage rated value protection class IP of the terminal operating frequency maximum thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value metal
material of the front ring black General technical data product function positive opening No product component • light source No insulation voltage rated value 600 V protection class IP IP66 • of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 4 operational current at AC-15 • at 110 V rated value 60 A
color of the front ring black General technical data product function positive opening No product component • light source No insulation voltage rated value 600 V protection class IP IP66 • of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts 0 number of NO contacts for auxiliary contacts 4 operational current at AC-15 • at 110 V rated value 60 A
product function positive opening No product component ● light source No insulation voltage rated value 600 V protection class IP IP66 ● of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts 10 number of NO contacts for auxiliary contacts 4 operational current at AC-15 ● at 110 V rated value 600 A
product component Ight source Insulation voltage rated value of the terminal operating frequency maximum thermal current Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15
product component Ight source Insulation voltage rated value Frotection class IP Of the terminal Operating frequency maximum Thermal current In A Auxiliary circuit Inumber of NC contacts for auxiliary contacts Inumber of NO contacts for auxiliary contacts Operational current at AC-15 In at 110 V rated value In a No In A In
● light source insulation voltage rated value 600 V protection class IP ● of the terminal Operating frequency maximum thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts operational current at AC-15 ● at 110 V rated value NO 600 V IP66 600 V IP66 600 V IP20 600 1/h 10 A Auxiliary circuit 600 1/h 600 A
insulation voltage rated value protection class IP of the terminal IP20 operating frequency maximum thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 o at 110 V rated value 600 V IP66 000 1/h 10 A 4 000 1/h 10 A Auxiliary circuit 00 000 1/h 10 A 60 A
protection class IP of the terminal IP20 operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 o at 110 V rated value IP66 IP20 00 1/h 10 A 4 00 A
of the terminal operating frequency maximum 600 1/h thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value IP20
operating frequency maximum thermal current 10 A Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value 60 A
thermal current Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value 10 A 4 60 A
Auxiliary circuit number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 • at 110 V rated value 60 A
number of NC contacts for auxiliary contacts number of NO contacts for auxiliary contacts operational current at AC-15 o at 110 V rated value 60 A
number of NO contacts for auxiliary contacts operational current at AC-15 o at 110 V rated value 60 A
operational current at AC-15 • at 110 V rated value 60 A
• at 110 V rated value 60 A
at 230 V rated value 30 A
• at 400 V rated value 15 A
• at 500 V rated value 12 A
Connections/ Terminals
type of electrical connection screw-type terminals
tightening torque of the screws in the bracket 20 N·m
tightening torque [lbf·in] with screw-type terminals 8 lbf·in
Ambient conditions
ambient temperature
• during operation -35 +70 °C
• during storage -40 +85 °C
Installation/ mounting/ dimensions
shape of the installation opening round

Certificates/ approvals

Further information

Siemens has decided to exit the Russian market (see here).

https://press.siemens.com/global/en/pressrelease/siemens-wind-down-russian-business

Siemens is working on the renewal of the current EAC certificates.

Please contact your local Siemens office on the status of validity of the EAC certification if you intend to import or offer to supply these products to an EAC relevant market (other than the sanctioned EAEU member states Russia or Belarus).

Information on the packaging

https://support.industry.siemens.com/cs/ww/en/view/109813875

Information- and Downloadcenter (Catalogs, Brochures,...)

https://www.siemens.com/ic10

Industry Mall (Online ordering system)

https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=US2:52SX2BABK7

Cax online generator

http://support.automation.siemens.com/WW/CAXorder/default.aspx?lang=en&mlfb=US2:52SX2BABK7

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

https://support.industry.siemens.com/cs/ww/en/ps/US2:52SX2BABK7

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, EPLAN macros, ...)

http://www.automation.siemens.com/bilddb/cax_de.aspx?mlfb=US2:52SX2BABK7&lang=en

last modified:	12/21/2020
----------------	------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Siemens:

52SX2BABK7