

Illuminated Emergency-stop pushbutton with 2 positive opening contacts

in a IP65 enclosure

Art.No.: 69043

Weight: 0.195

Country of origin: DE

Model designation: E-Stop 72 2NC L M12(8)

E-Stop 72 2NC L M12(8)




with M12 connection

8-pole

Emergency-Stop button

2 NC (positively-opening)

LED-Ring can be lit

[Link to Product](#)**Illustration**

Product may differ from Image

**Commercial data**

URL Webshop

<https://shop.murrelektronik.com/69043>

GTIN	4048879594813
ECLASS-6.0	27371244
ECLASS-6.1	27371244
ECLASS-7.0	27371244
ECLASS-7.1	27371244
ECLASS-8.0	27371244
ECLASS-8.1	27371244
ECLASS-9.0	27371244
ECLASS-9.1	27371244
ECLASS-10.0.1	27371244
ECLASS-10.1	27371244
ECLASS-11.0	27371244
ECLASS-11.1	27371244
ECLASS-12.0	27371244
ECLASS-13.0	27371244
ECLASS-14.0	27371244
ETIM-5.0	EC002034
ETIM-6.0	EC002034
ETIM-7.0	EC002034
ETIM-8.0	EC002034
EAN	4048879594813

Electrical data

Operating voltage AC/DC LED illumination min.	12 V
Operating voltage AC/DC LED illumination max.	30 V
Operating current LED illumination	15 mA @ 24 V AC/DC

Electrical data | Output

Switching current (AC-15)	30 A
Switching current (DC-13)	2.2 A
Utilization category AC-15 (EN IEC 60947-5-1)	3 A @ 250 V
Utilization category DC-13 (EN IEC 60947-5-1)	2 A @ 24 V

Device protection

Condition lifetime	load-dependent, temperature dependent
--------------------	---------------------------------------

Device protection | Electrical

Degree of protection (EN IEC 60529)	IP65
Electrical lifetime	1,000,000 Cycles

Device protection | Mechanical

Mechanical endurance	1,000,000 Cycles
Operating life B10d	250,000 Cycles

Mechanical data

Bounce time max.	9 ms
------------------	------

Mechanical data | Material data

Material contact	AgNi
------------------	------

Mechanical data | Mounting data

Height	103 mm
Width	72 mm
Depth	91 mm
Mounting method	screwed

Environmental characteristics | Climatic

Operating temperature min.	-25 °C
----------------------------	--------

Operating temperature max.	60 °C
Storage temperature min.	-25 °C
Storage temperature max.	85 °C

Technical Data | Reliability

Lambda normally closed contact	20 %
--------------------------------	------

Connection type 1

Family construction form	M12
No. of poles	8
Coding	A
Gender	male
Color contact carrier	black
PIN 1	NC 1
PIN 2	NC 1
PIN 3	NC 2
PIN 4	NC 2
PIN 7	X 2 -
PIN 8	X 1 +

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Murrelektronik:](#)

[69043](#)