### 1. Features

#### GaNFast<sup>™</sup> Power IC

- Large cooling pad
- Thermally-enhanced version of NV6113

Navitas

Energy • Efficiency • Sustainability

- Enhanced thermals when using CS resistor
- Monolithically-integrated gate drive
- Wide Vcc range (10 to 30 V)
- Programmable turn-on dV/dt
- 200 V/ns dV/dt immunity
- 800 V Transient Voltage Rating
- 650 V Continuous Voltage Rating
- Low 300 mΩ resistance
- Zero reverse recovery charge
- ESD protection 2 kV (HBM), 1 kV (CDM)
- 2 MHz operation

#### Small, low-profile SMT QFN

- 6 x 8 mm footprint, 0.85 mm profile
- Minimized package inductance

#### Sustainability

- RoHS, Pb-free, REACH-compliant
- Up to 40% energy savings vs Si solutions
- System level 4kg CO<sub>2</sub> Carbon Footprint reduction

#### **Product Reliability**

• 20-year limited product warranty (see Section 14 for details)

#### 2. Topologies / Applications

- AC-DC, DC-DC, DC-AC
- QR Flyback, PFC, AHB, Buck, Boost, Half bridge, Full bridge, LLC resonant, Class D
- Wireless power, Solar Micro-inverters, LED lighting, TV SMPS, Server, Telecom

#### 4. Typical Application Circuits



ON

EUTRAL

Company CarbonNeutral.com GàNFast™



QFN 6 x 8 mm

Simplified schematic

#### 3. Description

The NV6123 is a thermally-enhanced version of the popular NV6113 650 V GaNFast<sup>™</sup> power IC, optimized for high-frequency and soft-switching topologies.

Monolithic integration of FET, drive and logic creates an easy-to-use 'digital in, power out' high performance powertrain building block, enabling designers to create the fastest, smallest, most efficient integrated powertrain in the world.

The highest dV/dt immunity, high-speed integrated drive and industry standard low-profile, low-inductance, 6 x 8 mm SMT QFN package allow designers to exploit Navitas GaN technology with simple, quick, dependable solutions for breakthrough power density and efficiency.

Navitas' GaNFast<sup>™</sup> power ICs extend the capabilities of traditional topologies such as flyback, half-bridge, resonant, etc. to MHz+ and enable the commercial introduction of breakthrough designs.





NV6123



## 5. Table of Contents

1. Features	1
2. Description	1
3. Topologies / Applications	1
4. Typical Application Circuits	1
5. Table of Contents	2
6. Specifications	3
6.1. Absolute Maximum Ratings <sup>(1)</sup>	3
6.2. Recommended Operating Conditions <sup>(3)</sup>	3
6.3. ESD Ratings	4
6.4. Thermal Resistance	4
6.5. Electrical Characteristics	5
6.6. Switching Waveforms	6
6.7. Characteristic Graphs	7
7. Internal Schematic, Pin Configurations Functions	and 10
8. Functional Description	11
8.1. Start Up	11
8.2. Normal Operating Mode	12
8.3. Standby Mode	12

8.4. Programmable Turn-on dV/dt Control	12
8.5. Current Sensing	13
8.6. Paralleling Devices	13
8.7. 3.3V PWM Input Circuit	14
8.8. PCB Layout Guidelines	14
8.9. Recommended Component Values	15
8.9.1. Zener Selection	15
8.10. Drain-to-Source Voltage Considerations	16
9. Recommended PCB Land Pattern	17
10. PCB Layout Guidelines	18
11. QFN Package Outline	20
12. Tape and Reel Dimensions	21
13. Ordering Information	23
14. 20-Year Limited Warranty	23
15. Revision History	23

## 6. Specifications

#### 6.1. Absolute Maximum Ratings<sup>(1)</sup>

(with respect to Source (pad) unless noted)

SYMBOL	PARAMETER	MAX	UNITS
V <sub>TDS</sub>	Transient Drain-to-Source Voltage <sup>(2)</sup>	800	V
V <sub>DS</sub>	Drain-to-Source Voltage	-7 to +650	V
V <sub>cc</sub>	Supply Voltage	30	V
V <sub>PWM</sub>	PWM Input Pin Voltage	-3 to +30	V
V <sub>DZ</sub>	V <sub>DD</sub> Setting Pin Voltage	6.6	V
V <sub>DD</sub>	Drive Supply Voltage	7.2	V
V <sub>CP</sub>	Cooling Pad Voltage	-10 to +10	V
l D	Continuous Drain Current (@ T <sub>c</sub> = 100°C)	5	А
	Pulsed Drain Current (10 $\mu$ s @ T <sub>J</sub> = 25°C)	10	A
	Pulsed Drain Current (10 $\mu$ s @ T <sub>J</sub> = 125°C)	7.5	A
dV/dt	dV/dt Slew Rate on Drain-to-Source		V/ns
TJ	Operating Junction Temperature	-55 to 150	°C
T <sub>STOR</sub>	Storage Temperature	-55 to 150	⊃°

GàNFast™

(1) Absolute maximum ratings are stress ratings; devices subjected to stresses beyond these ratings may cause permanent damage.
(2) V<sub>DS(TRAN)</sub> allows for surge ratings during non-repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and repetitive events that are <100us (for example start-up, line interruption) and

#### 6.2. Recommended Operating Conditions<sup>(3)</sup>

SYMBOL	PARAMETER	MIN	ТҮР	MAX	UNITS
V <sub>DZ</sub>	Drive Supply Set Zener Voltage <sup>(4)</sup>	5.8	6.2	6.6	V
V <sub>DD</sub>	Drive Supply Voltage	5.5		7.0	V
I <sub>DD_EXT</sub>	Regulator External Load Current			3.0	mA
R <sub>DD</sub>	Gate Drive Turn-On Current Set Resistance <sup>(5)</sup>	10	25	200	Ω
V <sub>PWM</sub>	PWM Input Pin Voltage		5	Min. of (V <sub>cc</sub> or 20)	V
V <sub>CC</sub>	Supply Voltage			24	V
T <sub>c</sub>	Operating Case Temperature	-40		125	°C

(3) Exposure to conditions beyond maximum recommended operating conditions for extended periods of time may affect device reliability.

(4) Use of Zener diode other than 6.2 V is not recommended. See for recommended part numbers of 6.2 V Zener diodes.

(5) R<sub>DD</sub> resistor <u>must be used</u>. Minimum 10 Ohm to ensure application and device robustness.

#### 6.3. ESD Ratings

SYMBOL	PARAMETER	МАХ	UNITS
НВМ	Human Body Model (per JS-001-2014)	2,000	V
CDM	Charged Device Model (per JS-002-2014)	1,000	V

ĜàNFast™

#### 6.4. Thermal Resistance

SYMBOL	PARAMETER	ТҮР	UNITS
R <sub>eJC</sub> <sup>(6)</sup>	Junction-to-Case	2.2	°C/W
R <sub>eJA</sub> <sup>(6)</sup>	Junction-to-Ambient	40	°C/W

(6) R₀ measured on DUT mounted on 1 square inch 2 oz Cu (FR4 PCB)

## 6.5. Electrical Characteristics

Typical conditions:  $V_{DS}$  = 400 V,  $V_{CC}$  = 15 V,  $V_{DZ}$  = 6.2 V,  $F_{SW}$  = 1 MHz,  $T_{AMB}$  = 25 °C,  $I_D$  = 2.5 A,  $R_{DD}$  = 10  $\Omega$  (or specified)

ĜàNFast™

SYMBOL	PARAMETER	MIN	ТҮР	МАХ	UNITS	CONDITIONS	
		V <sub>cc</sub> Sup	ply Chara	acteristic	s		
I <sub>QCC</sub>	V <sub>cc</sub> Quiescent Current		0.9	1.5	mA	V <sub>PWM</sub> = 0 V	
I QCC-SW	V <sub>cc</sub> Operating Current		1.5		mA	F <sub>sw</sub> = 1 MHz, V <sub>DS</sub> = Open	
	Low-Side Logic Input Characteristics						
V <sub>PWMH</sub>	Input Logic High Threshold (rising edge)			4	V		
V <sub>PWML</sub>	Input Logic Low Threshold (falling edge)	1			V		
V <sub>I-HYS</sub>	Input Logic Hysteresis		0.5		V		
T <sub>ON</sub>	Turn-on Propagation Delay		11		ns	Fig.1, Fig.2	
T	Turn-off Propagation Delay		9		ns	Fig.1, Fig.2	
T <sub>R</sub>	Drain rise time		6		ns	Fig.1, Fig.2	
T <sub>F</sub>	Drain fall time		3		ns	Fig.1, Fig.2	
		Switchi	ng Chara	cteristics	;		
F <sub>sw</sub>	Switching Frequency			2	MHz		
t <sub>PW</sub>	Pulse width	0.02		1000	μs		
		GaN FE	ET Chara	cteristics			
I DSS	Drain-Source Leakage Current		0.1	25	μA	V <sub>DS</sub> = 650 V, V <sub>PWM</sub> = 0 V	
I <sub>DSS</sub>	Drain-Source Leakage Current		3	50	μA	V <sub>DS</sub> = 650 V, V <sub>PWM</sub> = 0 V, T <sub>C</sub> = 125 °C	
R <sub>DS(ON)</sub>	Drain-Source Resistance		300	430	mΩ	V <sub>PWM</sub> = 6 V, I <sub>D</sub> = 2.5 A	
R <sub>DS(ON)</sub>	Drain-Source Resistance		621		mΩ	V <sub>PWM</sub> = 6 V, I <sub>D</sub> = 2.5 A, T <sub>C</sub> = 125 °C	
V <sub>SD</sub>	Source-Drain Reverse Voltage		3.2	5	V	V <sub>PWM</sub> = 0 V, I <sub>SD</sub> = 2.5 A	
Q <sub>oss</sub>	Output Charge		10		nC	V <sub>DS</sub> = 400 V, V <sub>PWM</sub> = 0 V	
Q <sub>RR</sub>	Reverse Recovery Charge		0		nC		
C <sub>oss</sub>	Output Capacitance		12		pF	V <sub>DS</sub> = 400 V, V <sub>PWM</sub> = 0 V	
C_0(er) (7)	Effective Output Capacitance, Energy Related		16		pF	V <sub>DS</sub> = 400 V, V <sub>PWM</sub> = 0 V	
C_((8)	Effective Output Capacitance, Time Related		25		pF	V <sub>DS</sub> = 400 V, V <sub>PWM</sub> = 0 V	

(7)  $C_{_{O(er)}}$  is a fixed capacitance that gives the same stored energy as  $C_{_{OSS}}$  while  $V_{_{DS}}$  is rising from 0 to 400 V

(8)  $C_{O(tr)}$  is a fixed capacitance that gives the same charging time as  $C_{OSS}$  while  $V_{DS}$  is rising from 0 to 400 V

Navitas



#### 6.6. Switching Waveforms

(T<sub>c</sub> = 25 °C unless otherwise specified)



Fig. 1. Inductive switching circuit



Fig. 2. Propagation delay and rise/fall time definitions

Navitas

#### 6.7. Characteristic Graphs

(GaN FET,  $T_{C}$  = 25 °C unless otherwise specified)



Fig. 3. Pulsed Drain current ( $I_D$  PULSE) vs. drain-to-source voltage ( $V_{DS}$ ) at T = 25 °C



Fig. 5. Source-to-drain reverse conduction voltage



Fig. 7.  $V_{PWMH}$  and  $V_{PWML}$  vs. junction temperature(T<sub>J</sub>)



*GàNFast*<sup>™</sup> NV6123

Fig. 4. Pulsed Drain current ( $I_D$  PULSE) vs. drain-to-source voltage ( $V_{DS}$ ) at T = 125 °C



Fig. 6. Drain-to-source leakage current (I<sub>DSS</sub>) vs. drain-to-source voltage (V<sub>DS</sub>)







## ĜaNFast™ NV6123

### **Characteristic Graphs (Cont.)**



Fig. 9. Output capacitance  $(C_{OSS})$  vs. drain-to-source voltage  $(V_{DS})$ 



Fig. 11. Charge stored in output capacitance ( $Q_{OSS}$ ) vs. drain-to-source voltage ( $V_{DS}$ )







Fig. 10. Energy stored in output capacitance ( $E_{OSS}$ ) vs. drain-to-source voltage ( $V_{DS}$ )



Fig. 12.  $V_{CC}$  operating current ( $I_{QCC-SW}$ ) vs. operating frequency ( $F_{SW}$ )







## NV6123

#### **Characteristic Graphs (Cont.)**



Fig. 15. Slew rate (dV/dt) vs. gate drive turn-on current set resistance ( $R_{DD}$ ) at T = 25 °C



Fig. 17. Max. thermal transient impedance (Z<sub>thJC</sub>) vs. pulse width (t<sub>p</sub>)



ĜàNFast™

### 7. Internal Schematic, Pin Configurations and Functions



ĜàNFast™

			Package Top View
Pin			Dependention
Number	Symbol	1/0(*)	Description
1,7,8,9,12,13,14,24,25,26,29,30,31	СР	Т	Metal cooling pad on bottom of package for thermal management. CP must be connected to Source or circuit PGND. Do not leave CP unconnected or floating!
2,3,4,5,6	S	O, G Source of power FET & GaN IC supply ground.	
10	Dz	I	Gate drive supply voltage set pin (6.2 V Zener to GND).
11	V <sub>DD</sub>	I	Gate drive supply voltage. Gate drive turn-on current set pin (using $R_{_{DD}}$ ).
27	PWM	I	PWM input
28	V <sub>cc</sub>	Р	Supply voltage (10V to 24V)
15,16,17,18,19,20,21,22,23	D	Р	Drain of power FET

(1) I = Input, O = Output, P = Power, G = GaN IC Ground, T = Thermal

Energy • Efficiency • Sustainability

#### 8. Functional Description

Navitas

The following functional description contains additional information regarding the IC operating modes and pin functionality.

#### 8.1. Start Up

When the V<sub>CC</sub> supply is first applied, care should be taken such that the V<sub>DD</sub> and D<sub>Z</sub> pins are up at their correct voltage levels before the PWM input signal starts. The V<sub>DD</sub> pin ramp up time is determined by the internal regulator current at this pin and the external C<sub>VDD</sub> capacitor. Also, since the D<sub>Z</sub> pin voltage sets the V<sub>DD</sub> voltage level, the V<sub>DD</sub> pin will ramp up together with the D<sub>z</sub> pin (Fig. 18).

For half-bridge configurations, it is important that the  $V_{CC}$  supply, the  $D_Z$  pin, and the  $V_{DD}$  supply of the high-side GaNFast power IC are all charged up to their proper levels before the first high-side PWM pulses start. For LLC applications, a long on-time PWM pulse to the low-side (> 10 µs) is typically provided by the LLC controller to allow the supply pins of the high-side device to charge up (through the external bootstrap diode) to their correct levels before the first high-side PWM pulses start (Fig. 19).

For active clamp flyback (ACF) applications, the halfbridge must be ready very quickly due to the soft-start mode of the ACF controller. When the first few PWM pulses are generated by the ACF controller, the highside supply pins of the power IC will require a few lowside pulses to charge up (through the external bootstrap diode) before the high-side starts to switch (Fig. 20).



NV6123

GàNFast™







Fig. 20. ACF half-bridge start-up timing diagram



#### 8.2. Normal Operating Mode

During Normal Operating Mode, all of the internal circuit blocks are active.  $V_{CC}$  is operating within the recommended range of 10 V to 24 V, the  $V_{DD}$  pin is at the voltage set by the Zener diode at the  $D_Z$  pin (6.2 V), and the internal gate drive and power FET are both enabled. The external PWM signal at the PWM pin determines the frequency and duty-cycle of the internal gate of the power FET. As the PWM voltage toggles above and below the rising and falling input thresholds (4 V and 1 V), the internal gate of the power FET toggles on and off between  $V_{DD}$  and 0 V (Fig. 21). The drain of the power ground) and a higher voltage level (650 V max), depending on the external power conversion circuit topology.



Fig. 21. Normal operating mode timing diagram

#### 8.3. Standby Mode

For applications where a low standby power is required, an external series cut-off circuit (Fig. 22) can be used to disconnect Vcc of the GaNFast power IC from the main  $V_{\text{CC}}$  supply of the power supply. This will reduce  $V_{\text{CC}}$ current consumption when the converter is in burst mode during light-load or open load conditions. The Vcc cut-off circuit consists of a series PMOS FET that is turned on and off with a pull-down NMOS FET. The gate of the NMOS is controlled by an external ENABLE signal that should be provided by the main controller of the power supply. The capacitor value at the V<sub>CC</sub> pin should then be selected according to the desired start-up speed, each time the ENABLE signal toggles high. A 22 nF capacitor at V<sub>CC</sub>, for example, will give a typical start-up time of approximately 2 μs. An additional 200 kΩ resistor is placed across the PMOS cut-off FET to provide a small V<sub>CC</sub> voltage level for proper start-up.



Fig. 22. Standby mode V<sub>CC</sub> cut-off circuit

#### 8.4. Programmable Turn-on dV/dt Control

During first start-up pulses or during hard-switching conditions, it is desirable to limit the slew rate (dV/dt) of the drain of the power FET during turn-on. This is necessary to reduce EMI or reduce circuit switching noise. To program the turn-on dV/dt rate of the internal power FET, a resistor ( $R_{DD}$ ) is placed in between the  $V_{DD}$  capacitor and the  $V_{DD}$  pin. This resistor ( $R_{DD}$ ) sets the turn-on current of the internal gate driver and therefore sets the turn-on falling edge dV/dt rate of the drain of the power FET (Fig. 23). A typical turn-on slew-rate change with respect to  $R_{DD}$  is shown in Fig. 15.

Minimum 10  $\Omega$  R<sub>DD</sub> is required.



Fig. 23. Turn-on dV/dt slew rate control

Energy • Efficiency • Sustainability



#### 8.5. Current Sensing

For many applications it is necessary to sense the cycleby-cycle current flowing through the power FET. To sense the current flowing through the GaNFast power IC, a standard current-sensing resistor can be placed in between the source and power ground (Fig. 24). In this configuration, all of the components around the GaNFast power IC (C<sub>VCC</sub>, C<sub>VDD</sub>, D<sub>Z</sub>, etc.) should be grounded with a single connection at the source. Also, an additional RC filter can be inserted between the PWM signal and the PWM pin (100  $\Omega$ , 100 pF typical). This filter is necessary to prevent false triggering due to high-frequency voltage spikes occurring at the source node due to external parasitic inductance from the source PCB trace or the current-sensing resistor itself. For increased cooling pad PCB copper area it may be desired to connect CP to the circuit PGND. Fig. 24 shows the components around the GaNFast power IC grounded at the source pins (S and CP connected to PGND). This allows for all CP pins and CP pad to be connected to a large and continuous thermal copper area without being obstructed by the current sensing resistor. CP must be connected to source (S) or circuit PGND! Do not leave CP floating!



Fig. 24. Current sensing circuit

#### 8.6. Paralleling Devices

For some applications it is desirable to parallel ICs in order to reduce conduction losses and temperatures. Two GaNFast power ICs can be connected in parallel in a PFC boost application working in boundaryconduction mode (BCM) only. This configuration is shown in Fig. 25. The paired pins that are connected together include the drain pins (D), the source pins (S), the  $V_{cc}$  pins, the PWM pins, and the  $D_z$ . A single  $D_z$ diode can be shared by both ICs. The VDD pins are not connected together and require separate V<sub>DD</sub> supply capacitors ( $C_{VDD1}$ ,  $C_{VDD2}$ ) and separate turn-on current set resistors (R<sub>DD1</sub>, R<sub>DD2</sub>). Each IC should have its own local V<sub>CC</sub> supply filter capacitor ( $C_{VCC1}$ ,  $C_{VCC2}$ ). The PWM pins can have a single filter resistor ( $R_{PWM}$ ) but separate filter capacitors ( $C_{PWM1}$ ,  $C_{PWM2}$ ) should be placed at the PWM pin of each IC. When designing the PCB layout for the two paralleled ICs, the drain and source connections should be made as symmetrical as possible two avoid any parasitic inductance or capacitance mismatch.



Fig. 25. Boost schematic using two parallel ICs





#### 8.7. 3.3V PWM Input Circuit

For some applications where a 3.3 V PWM signal is required (DSP, MCU, etc.) an additional buffer can be placed before the PWM input pin (Fig. 26) with the buffer supply voltage connected to the  $V_{DD}$  capacitor.



Fig. 26. 3.3 V PWM input buffer circuit

#### 8.8. PCB Layout Guidelines

The design of the PCB layout is critical for good noise immunity, sufficient thermal management, and proper operation of the IC. Typical PCB layout examples for without current sensing resistor and with current sensing resistor are shown in Section 10. The following rules should be followed carefully during the design of the PCB layout:

GàNFast™

- 1) Place all IC filter and programming components directly next to the IC. These components include ( $C_{VCC}$ ,  $C_{VDD}$ ,  $R_{PWM}$ ,  $C_{PWM}$ ,  $R_{DD}$  and  $D_7$ ).
- Keep ground trace of IC filter and programming components separate from power GND trace. Do not run power GND currents through ground trace of filter components!
- 3) For best thermal management, place thermal vias in the source pad area to conduct the heat out through the bottom of the package and through the PCB board to other layers (see Section 10 for correct layout examples).
- Use large PCB thermal planes (connected with thermal vias to the source pad) and additional PCB layers to reduce IC temperatures as much as possible (see Section 0 for correct layout examples).
- 5) For half-bridge layouts, do not extend copper planes from one IC across the components or pads of the other IC!
- For high density designs, use a 4-layer PCB and 2 oz. copper to route signal connections. This allows layout to maintain large thermal copper planes and reduce power device temperature.

#### 8.9. Recommended Component Values

The following table (Table I) shows the recommended component values for the external filter capacitors, Zener diode, and  $R_{DD}$  connected to the pins of this GaNFast power IC. These components should be placed as close as possible to the IC. Please see PCB Layout guidelines for more information. The Zener diode at the  $D_z$  pin should be a low-current type with a flat Zener, and the min/max limits must be followed.  $R_{DD}$  must be a minimum of 10  $\Omega$  to ensure application and device robustness.

GàNFast

SYM	DESCRIPTION	MIN	ТҮР	MAX	UNITS
$\rm C_{_{VCC}}$	Maximum $V_{cc}^{}$ supply capacitor		0.1		μF
$\rm C_{_{VDD}}$	V <sub>DD</sub> supply capacitor		0.01		μF
$R_{_{\mathrm{DD}}}$	Gate drive turn-on current set resistor	10	25	200	Ω
$R_{_{\mathrm{PWM}}}$	PWM filter resistor		100		Ω
C PWM	PWM filter capacitor		100		pF

Table I. Recommended component values.

#### 8.9.1. Zener Diode Selection

The Zener voltage is a critical parameter that sets the internal reference for gate drive voltage and other circuitry. The Zener diode needs to be selected such that the voltage on the  $D_Z$  pin is within recommended operating conditions (5.8 V to 6.6 V) across operating temperature (-40°C to 125°C) and bias current (10 µA to 1 mA). To ensure effective operation, the current vs. voltage characteristics of the Zener diode should be measured down to 10 µA to ensure flat characteristics across the current operating range (10 µA to 1 mA). The recommended part numbers meet these requirements (See 13.). If the Zener selected by user does not ensure that the voltage on the D<sub>Z</sub> pin is always within the recommended operating range, the functionality and reliability of the GaNFast power IC can be impacted.

Only the following Zener diodes are to be used (Table II).

SYM	DESCRIPTION	PART NO.	SUPPLIER	MIN	ТҮР	MAX	UNITS
		BZT52B6V2 RHG Taiwan Semiconductor Corporation					
D	D <sub>Z</sub> V <sub>DD</sub> set Zener diode (D <sub>Z</sub> pin)	MM3Z6V2ST1G	ON-Semiconductor	5.8	62	6.6	V
Z		PDZ6.2B.115	Nexperia (NXP)	0.0	0.2	0.0	v
		PLVA662A.215	Nexperia (NXP)				
		LM3Z6V2T1	Leshan Radio Company				

Table II. Qualified Zener diode components

GàNFast



Fig. 27. Increasing Zener bias current for stable Zener voltage

#### 8.10. Drain-to-Source Voltage Considerations

For single ended topologies, such as quasi-resonant (QR) flyback, the drain-to-source voltage (V<sub>DS</sub>) of the GaN Power IC should be carefully designed in order to ensure there is sufficient derating to provide exceptional quality and long-term reliability. The different voltage stress levels found in a typical QR flyback topology can be analyzed using as a reference. When the device is switched off each cycle, the energy stored in the transformer magnetizing and leakage inductances will cause the V<sub>DS</sub> to spike to the level of V<sub>SPIKE</sub>. The clamp circuit of the QR system should be designed such that V<sub>SPIKE</sub> stays below the Absolute Maximum rated V<sub>DS</sub> of 650 V on a cycle-by-cycle basis in continuous operation. Following the dissipation of the spike energy due to the leakage inductance, the device V<sub>DS</sub> will be determined by the addition of the bus voltage (rectified AC input voltage) and the transformer reflected voltage which is defined in as the V<sub>DS-OFF</sub>. To ensure sufficient design margin and long-term reliability, it is recommended to design the system such that V<sub>DS-OFF</sub> follows a typical derating of 80% from absolute maximum voltage. Finally, the transient drain-to-source voltage rating (V<sub>TDS</sub>) is provided in order to provide a margin for events that could occur on a non-repetitive basis, such as line surge due to lightning strikes. V<sub>TDS</sub> ensures excellent device robustness provided any non-repetitive drain-to-source voltages are maintained less than 750 V. For half-bridge based topologies, such as LLC or PFC, VDs voltage is clamped to the bus voltage. VDs should be designed such that it meets the V<sub>DS-OFF</sub> derating guideline. The V<sub>TDS</sub> of 750 V can also be used for non-repetitive events such as lightning surge.





NV6123





ĜàNFast<sup>™</sup> NV6123

All dimensions are in mm



ĜàNFast™

#### 10. PCB Layout Guidelines

#### Without CS Resistor:





GàNFast™

#### With CS Resistor:







#### 11. QFN Package Outline







## 12. Tape and Reel Dimensions





# ĜàNFast™ NV6123

7" Reel



13" Reel



## 13.Ordering Information

Part Number	Operating Temperature Grade	Storage Temperature Range	Package	MSL Rating	Packing (Tape & Reel)
NV6123 RA	-40 °C to +125 °C T <sub>CASE</sub>	-55 °C to +150 °C T <sub>CASE</sub>	6 x 8 mm QFN	1	1,000 : 7" Reel
NV6123	-40 °C to +125 °C TCASE	-55 °C to +150 °C TCASE	6 x 8 mm QFN	1	5,000 : 13" Reel

GàNFast™

#### 14. 20-Year Limited Product Warranty

The 20-year limited warranty applies to all packaged Navitas GaNFast Power ICs in mass production, subject to the terms and conditions of, Navitas' express limited product warranty, available at <a href="https://navitassemi.com/terms-conditions">https://navitassemi.com/terms-conditions</a>. The warranted specifications include only the MIN and MAX values only listed in Absolute Maximum Ratings, ESD Ratings and Electrical Characteristics sections of this datasheet. Typical (TYP) values or other specifications are not warranted.



#### 15. Revision History

Date	Status	Notes
Aug 18, 2019	Preliminary	First publication
Nov 22, 2019	Initial Release	Added Section 8.10, updated Section 8.3 and figure 22.
Jun 22, 2020	Revision	Updated guidelines in Section 8.1: Fast startup. Updated RDD specification. This datasheet revision applies to product prior to PCN2020-09-15
Oct 27, 2020	Revision	Datasheet updated in alignment with PCN2020-09-15. Product is marked with Lot Code ending in Z for traceability
Apr 11, 2022	Revision	Added 20-Year Limited Product Warranty
Oct 11, 2022	Revision	Added Carbon Neutral logo

#### Additional Information

DISCLAIMER Navitas Semiconductor Inc. (Navitas) reserves the right to modify the products and/or specifications described herein at any time and at Navitas' sole discretion. All information in this document, including descriptions of product features and performance, is subject to change without notice. Performance specifications and the operating parameters of the described products are determined in the independent state and are not guaranteed to perform the same way when installed in customer products. The information contained herein is provided without representation or warranty of any kind, whether express or implied. This document is presented only as a guide and does not convey any license under intellectual property rights of Navitas or any third parties.

Navitas' products are not intended for use in applications involving extreme environmental conditions or in life support systems. Products supplied under Navitas <u>Terms and Conditions</u>.

Navitas Semiconductor, Navitas, GaNFast and associated logos are registered trademarks of Navitas. Copyright ©2022 Navitas Semiconductor Inc. All rights reserved



Contact info@navitassemi.com

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Navitas Semiconductor: NV6123 NV6123-RA