

HCS885XF



HCS885XF Smart GNSS Helical Antenna for Precise Heading

Overview

The HCS885XF is a multi-band (L1/L5), multi-constellation integrated GNSS receiver/antenna with RTK corrections and PointPerfect® PPP-RTK augmentation compatibility. The HCS885XF is capable of providing sub 1 meter accuracy stand alone, sub 6 cm accuracy with PPP-RTK corrections and sub 1 cm with RTK corrections. It is capable of moving base RTK Precise Heading, and can act as either base or rover. It is based on the Calian HC885SXF antenna, making it light-weight and very suited for unmanned aerial vehicle (UAV) applications that require precise location and precise heading.



Interference Resilience

The HCS885XF incorporates a latest generation multi-band (L1/L5) GNSS receiver IMU with a Tallysman precision tuned multi-band (L1/L5) helical antenna that provides excellent axial ratios and operates without the requirement for a ground plane. The state of the art GNSS receiver supports concurrent tracking of all four major constellations (GPS, BeiDou, Galileo and GLONASS) in multiple frequency bands. The concurrent multi-band (L1/L5) access to all four satellite constellations improves the receiver's convergence capability to deliver a quick, precise and reliable position solution.

The multi-band architecture is the most effective method for the removal of ionospheric error, and the L5 band provides superior interference and multipath performance vs. L2. The HCS885XF employs Tallysman eXtended Filter (XF) technology which mitigates near-band and out-of-band interference such as LTE signals and their harmonics, enabling operation in the most challenging deployments.

PPP-RTK, RTK and Precise Heading

The HCS885XF supports PointPerfect PPP-RTK augmentation, over network connections, and RTK base/rover capability, with moving base RTK Precised Heading, particularly useful for UAV and robotic applications. The HCS885XF can be configured as a multi-receiver base/rover pair. Combining fast survey-in of the base unit with moving base RTK enhances the location accuracy as well as the heading accuracy. HCS885XF mounts fluxh with three threaded inserts for secure attachment and provides a rubber O-ring around the outer edge for seal. Control, corrections and position output are delivered via a 6 pin JST receptacle connector inset into the base.



Mechanical Dimensions (mm)

Features

- Improved noise immunity with multi-band u-blox NEO F9P GNSS receiver
- PointPerfect PPP-RTK (networked)
- RTK Base/Rover configurations and Moving Base RTK Precise Heading
- Excellent Right-Hand circular polarized signal reception
- Multi-band GNSS receiver has high resilience to ionospheric errors
- Light-weight precision-tuned helical element; with excellent axial ratios and Calian's Tallysman eXtended Filtering
- 5V operation
- CMOS signalling with RS232 option
- Industrial grade IP67 enclosure
- Surface mount with O-ring seal
- 6-pin JST port for Pixhawk framework compatibility

HCS885XF Smart GNSS Antenna

Specifications

Antenna

Architecture.....	Multi-band (L1/L5), Helical
Axial Ratio.....	≤ 0.5 dB at Zenith
PCV.....	±3 mm
Frequencies.....	GPS/QZSS: L1 C/A, L5; GLO: L1O1F; GAL: E1-B/C, E5a; BDS: B1I & B2a
SBAS L1 C/A.....	WAAS, EGNOS, MSAS L1Sb, GAGAN
Channels.....	184-channel u-blox F9 engine
Anti-jamming.....	Active Continuous Wave detection

Interface

Pwr, Gnd	
HCS885XF-29.....	Data, opt. timepulse or TX2/RX2: RS-232
HCS885XF-49.....	Data, opt. timepulse or TX2/RX2: CMOS
Connector.....	6 Position JST Receptacle Connector, 1.25mm

Serial Protocol

Output.....	NMEA 0183, UBX Binary, RTCM v3.3, SPARTN v2.0
Baud Rate.....	Configurable
Update Rate (PVT).....	7 Hz (4); 8 Hz (GPS+GAL+BDS); 18 Hz (GPS+GAL); 20 Hz (GPS+GLO); 11 Hz (GPS+BDS); 25 Hz (GPS)

Mechanical

Dimensions.....	44.55 mm dia. x 52.75 mm H
Weight.....	38 g
Mounting Method.....	3x M2.5 screws
Cable Length.....	no cable

Electrical

Voltages.....	5 VDC
Current.....	TBD

Environmental

Operating Temperature.....	-40°C to +85°C
Storage Temperature.....	-40°C to +85°C
Weatherproof.....	IP67
Shock.....	Vertical axis 50G, other axis 30G
	3 axis sweep – 15 min
Vibration.....	10-200 Hz log sweep 3G

Sensitivity (4 Constellations)

Tracking & Nav.....	-167 dBm
Reacquisition.....	-160 dBm
Hot starts.....	-157 dBm
Cold starts.....	-148 dBm

Acquisition

Cold start.....	27 sec
Aided start.....	3 sec
Reacquisition.....	3 sec

Position and Velocity Accuracy (4 Constellations)

Horizontal PVT/SBAS/RTK (CEP).....	1.5m/ 1.0m/ 0.01+1ppm
Horizontal PPP-RTK (CEP).....	<0.1m SPARTN;
Vertical PVT/SBAS/RTK (R50).....	2.0m/ 1.5m/ 0.01m+1ppm
Vertical PPP-RTK (R50).....	<0.20m SPARTN;
Typical Convergence.....	<12s RTK; <65s SPARTN;
Velocity accuracy.....	0.05m/s

Heading

Dynamic Heading Accuracy.....	0.3°
Precise Heading Accuracy.....	TBD

Timing

Timing Accuracy.....	30 ns RMS
----------------------	-----------

Ordering Information:

33-HCS885XF-29-PC0 (JST 6 pos. receptacle, 1.25mm; Data, opt. Timepulse, TX2, RX2: RS-232; PC0 = NMEA out, no adaptor cable.)
33-HCS885XF-49-PC0 (JST 6 pos. receptacle, 1.25mm; Data, opt. Timepulse, TX2, RX2: CMOS; PC0 = NMEA out, no adaptor cable.)

33-HCS885XF-29-PC0 SDK Test Adaptor required for programming
33-HCS885XF-49-PC0 SDK Test Adaptor required for programming

33-0095-13 (5V RS-232)
33-0095-7 (5V CMOS)

About Calian GNSS: With global headquarters and manufacturing in Ottawa, Canada, Calian GNSS is a leading manufacturer of high-precision antennas and components for Global Navigation Satellite System (GNSS) applications. Calian GNSS' mission is to support the needs of a new generation of positioning systems by delivering unprecedented antenna precision at competitive prices. Learn more at www.calian.com/GNSS

© 2024 Calian GNSS Ltd. All rights reserved. Calian, the "Confidence. Engineered." tag line and the Calian logo are trademarks or registered trademarks of Calian GNSS Ltd. and/or its affiliates in Canada and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. This document contains Calian proprietary information. Use, disclosure, copying or distribution of information requires the written permission of Calian GNSS Ltd. The information presented is subject to change without notice. Calian assumes no responsibility for any errors or omissions in this document. Calian GNSS Ltd. hereby disclaims any and all warranties and liabilities of any kind.

Contact us:
info.gnss@calian.com
T: +1 613 591-3131

Calian GNSS Ltd.
36 Steacie Drive,
Ottawa ON
K2K 2A9 Canada

www.calian.com/GNSS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Calian:](#)

[33-HCS885XF-29](#) [33-HCS885XF-49](#) [33-HCS885XF-49-PC0](#) [33-HCS885XF-29-PC0](#)