

TW5384



TW5384 Smart GNSS Antenna for High Accuracy Positioning

Overview

The TW5384 is a multi-band (L1/L2), multi-constellation integrated GNSS receiver/antenna with RTK for Precise Point Positioning. The TW5384 is capable of providing sub 1 meter accuracy stand alone, sub 6 cm accuracy with PPP-RTK corrections, and sub 1 cm with RTK corrections to support the most demanding positioning applications.

Interference Resilience


The TW5384 incorporates a latest generation multi-band (L1/L2) GNSS receiver with a Tallysman Accutenna® multi-band (L1/L2) dual feed patch. The state of the art GNSS receiver supports concurrent tracking of all four major constellations (GPS, BeiDou, Galileo and GLONASS) in multiple frequency bands. The multi-band (L1/L2) architecture is highly effective method for the removal of ionospheric error. The TW5384 employs multi-stage filtering with low noise figure LNAs, combined with the dual feed Accutenna®, which greatly improves the rejection of multi-path signal interference, to offer exceptional performance to meet the most stringent precise positioning applications.

Precise Point Positioning

The TW5384 is designed to meet the most demanding of positioning applications. The receiver offers support for a broad range of corrections services (RTK base/rover or network) allowing performance optimization according to each application's unique requirements. The concurrent multi-band (L1/L2) access to all four satellite constellations improves the receiver's convergence capability to deliver a quick, precise and reliable position solution which is unaffected by ionospheric errors, and improved resilience to jamming.

The TW5384 accepts RTCM RTK messaged from a base station, Virtual Reference Station or SPARTN SSR message type via the PointPerfect subscription service. TW5384 may also be configured as an RTK base station or moving RTK base for Precise Heading.

The TW5384 provides sub 6 cm positioning accuracy in conjunction with PPP-RTK applied corrections and sub 1 cm with RTK.



Mechanical Dimensions (mm)

Features

- Improved noise immunity with multi-band ublox ZED-F9P GNSS receiver
- PointPerfect PPP-RTK, RTK Base/Rover, Moving Baseline Precise Heading
- Improved multi-path rejection with Dual feed Accutenna®
- Multi-band GNSS receiver is resilient to ionospheric errors
- High reliability timing with expansive constellation array
- Exceptional position performance standalone without correction services
- Broad 5V-36V operation
- RS-422 differential (or RS-232) signalling
- Industrial grade IP69K enclosure
- Rugged fixed mount
- Multiple cable lengths (5m, 15m and 25m)
- Available with conical radome

TW5384 Smart GNSS Antenna

Specifications

Antenna

Architecture.....	Multi-band (L1/L2), Dual Feed
Axial Ratio.....	L1: < 1 dB typical.
Frequencies.....	GPS L1C/A L2C, GLO L1OF L2OF, GAL E1B/C E5b, BDS B1I B2I, QZSS L1C/A L2C
SBAS L1 C/A.....	WAAS, EGNOS, MSAS, GAGAN
Channels.....	184-channel u-blox F9 engine
Anti-jamming	Active CW detection

Interface

Pwr, Gnd	
33-5384-07-yy-zz.....	Data, Timerpulse: RS-422 levels
33-5384-27-yy-zz.....	Data: RS-232; Timepulse: RS-422

Serial Protocol

Output.....	NMEA 0183, UBX Binary, RTCM v3.3, SPARTN v2.0
Baud Rate.....	Configurable
Update Rate (PVT)	9 Hz (4); 10 Hz (GPS+GAL+BDS); 20 Hz (GPS+GAL); 20 Hz (GPS+GLO); 16 Hz (GP+BDS); 25 Hz (GPS)

Mechanical

Dimensions	66.5 mm dia. x 21 mm H
Weight.....	135 g
Mounting Method	Industrial grade fixed Mount
Cable Length.....	5, 15, 25m with RJ45 termination

Electrical

Voltages	5 V to 36 VDC
Current	0.5 Watts (nominal operating) Measured @ 5VDC supply

Environmental

Operating Temperature.....	-40°C to +85°C
Storage Temperature.....	-40°C to +85°C
Weatherproof	IP69K
Shock.....	Vertical axis 50G, other axis 30G 3 axis sweep – 15 min
Vibration.....	10-200 Hz log sweep 3G

Sensitivity

Tracking & Nav	-167 dBm
Reacquisition	-160 dBm
Hot starts	-157 dBm
Cold starts	-148 dBm

Acquisition

Cold start	25 sec
Aided start	2 sec
Reacquisition	2 sec

Horizontal Position Accuracy (4 Constellations)

Standard PVT	1.5m CEP
Standard SBAS	1.0m CEP
Corrected RTK.....	0.01m + 1ppm CEP
Augmented SPARTN (PPP-RTK).....	<0.06m CEP
SPARTN Convergence.....	<45 sec*

Heading

Dynamic Heading Accuracy	0.3° (30 m/sec)
Precise Heading Accuracy (static)	0.4°(min 1m baseline)

Timing

Timing Accuracy.....	30 ns RMS
----------------------	-----------

Ordering Information:

33-5384-07-yy-zz-PC0	(RJ45; Data and Timepulse: RS-422; PC0 = NMEA out, no adaptor cable.)
33-5384-27-yy-zz-PC0	(RJ45; Data: RS-232, Timepulse: RS422; PC0 = NMEA out, no adaptor cable.)

yy = Radome (00=grey conical, 10=grey low profile, 01=white conical, 11=white low profile)
zz = Cable length in meters. Standard is 5m. (15m and 25m are special order only)

33-5384-07-yy-zz-PC0 SDK Test Adaptor required for programming	33-0095-10
33-5384-27-yy-zz-PC0 SDK Test Adaptor required for programming	33-0095-13

About Calian GNSS: With global headquarters and manufacturing in Ottawa, Canada, Calian GNSS is a leading manufacturer of high-precision antennas and components for Global Navigation Satellite System (GNSS) applications. Calian GNSS' mission is to support the needs of a new generation of positioning systems by delivering unprecedented antenna precision at competitive prices. Learn more at www.calian.com/GNSS

© 2024 Calian GNSS Ltd. All rights reserved. Calian, the "Confidence. Engineered." tag line and the Calian logo are trademarks or registered trademarks of Calian GNSS Ltd. and/or its affiliates in Canada and certain other countries. All other trademarks mentioned in this document are the property of their respective owners. This document contains Calian proprietary information. Use, disclosure, copying or distribution of information requires the written permission of Calian GNSS Ltd. The information presented is subject to change without notice. Calian assumes no responsibility for any errors or omissions in this document. Calian GNSS Ltd. hereby disclaims any and all warranties and liabilities of any kind.

Contact us:
info.gnss@calian.com
T: +1 613 591-3131

Calian GNSS Ltd.
36 Steacie Drive,
Ottawa ON
K2K 2A9 Canada

www.calian.com/GNSS

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Calian:](#)

[33-5384-07-10-05-PC0](#) [33-5384-27-10-05-PC0](#)