

XLR CHASSIS CONNECTORS

4 PIN E SERIES - VERTICAL PCB MOUNT

Locking vertical PCB mount 4 pin chassis connector with plastic body perfect for use in DC power, aviation, communications, and other AV applications.

Other Available Mounting Option: Horizontal



IO-XLR4-M-EV

IO-XLR4-F-EV

SPECIFICATIONS

PRODUCT

Gender: Male (IO-XLR4-M-EV)

Female (IO-XLR4-F-EV)

Contacts: 4

ELECTRICAL

Capacitance Between Contacts: ≤ 3.4 pF

Capacitance Between Contact and Ground: ≤ 3.2 pF

Contact Resistance: $< 6 \text{ m}\Omega$

Insulation Resistance: ≥ 5000 MΩ

Dielectric Strength: 1500V @ 60s

Current Rating: 3A / 50V AC

Grounding: Separate ground terminal. Grounds to

shell of mating connector and panel

ENVIRONMENTAL

Standard Compliance: IEC 61076-2-103

UL Flammability Rating: UL94 V-0

Temperature Range: -40° C $\sim +70^{\circ}$ C $(-40^{\circ}$ F $\sim +158^{\circ}$ F)

MECHANICAL

Lifetime: > 1000 Mating Cycles

Wiring: Vertical PCB Mount

Locking Device: Latch Lock

Mounting Direction: Rear

Solderability: Complies with IEC

60068-2-20

MATERIAL

Contacts: Gold Plated Brass

Ground Terminal: Nickel Plated Brass


Shell: Polyamide

Shell Finish: Black

Push Button: Nickel Plated Brass

Latch: Nickel Plated Carbon Steel

Panel Cutout



FEATURES & APPLICATIONS

E Series XLR chassis connectors offer the most cost-effective solution for design-in applications where the termination method is to a printed circuit board. The small footprint makes this our XLR receptacle with the highest packing density available. These connectors feature a compact all plastic housing with precision machined, one piece, gold plated contacts to help prolong the useful life of the connectors. They also come with a separate nickel plated ground pin that grounds the connector to the panel. The compact form factor of the these connectors makes them perfect for situations where space saving is a priority or space for a connector is limited.

Available in 3, 4, or 5 pin, Male or Female variations with options for vertical or horizontal PCB mounting.

PART NUMBER BREAKDOWN:

IO-XLR4-M-EV

Series Identifier IO-XLR4-M-EV Number of Pins IO-XLR4-M-EV Gender IO-XLR4-M-EV Series Identifier IO-XLR4-M-EV

H = Horizontal PCB Mount V = Vertical PCB Mount

STANDARDS & CLASSIFICATIONS





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Io Audio:

IO-XLR4-F-EV IO-XLR4-M-EV