

XLR CHASSIS CONNECTORS

5 PIN E SERIES - VERTICAL PCB MOUNT

Locking vertical PCB mount 5 pin chassis connector with plastic body for audio and lighting control.

Other Available Mounting Option: Horizontal PCB Mount

SPECIFICATIONS

PRODUCT

Gender: Male (IO-XLR5-M-EV)

Female (IO-XLR5-F-EV)

Contacts: 5

ELECTRICAL

Capacitance Between Contacts: ≤ 2 pF

Capacitance Between Contact and Ground: ≤ 2.4 pF

Contact Resistance: < 6 mΩ

Insulation Resistance: ≥ 5000 MΩ

Dielectric Strength: 1500V @ 60s

Current Rating: 3A / 50V AC

Grounding: Separate ground terminal. Grounds to shell of mating connector and panel

ENVIRONMENTAL

Standard Compliance: IEC 61076-2-103

UL Flammability: UL94V-0

Temperature Range: -40°C ~ +70° C (-40°F ~ +158°F)





IO-XLR5-M-EV

IO-XLR5-F-EV

MECHANICAL

Lifetime: > 1000 Mating Cycles Wiring: Vertical PCB Mount Locking Device: Latch Lock Mounting Direction: Rear Solderability: Complies with IEC 60068-2-20

MATERIAL


Contacts: Gold Plated Brass Ground Terminal: Nickel Plated Brass Shell: Polyamide Shell Finish: Black Push Button: Nickel Plated Brass Latch: Nickel Plated Carbon Steel

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc. 10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com



Panel Cutout



FEATURES & APPLICATIONS

E Series XLR chassis connectors offer the most cost-effective solution for design-in applications where the termination method is to a printed circuit board. The small footprint makes this our XLR receptacle with the highest packing density available. These connectors feature a compact all plastic housing with precision machined, one piece, gold plated contacts to help prolong the useful life of the connectors. They also come with a separate nickel plated ground pin that grounds the connector to the panel. The compact form factor of the these connectors makes them perfect for situations where space saving is a priority or space for a connector is limited.

Available in 3, 4, or 5 pin, Male or Female variations with options for vertical or horizontal PCB mounting.

PART NUMBER BREAKDOWN:

IO-XLR5-M-EV Series Identifier IO-XLR5-M-EV Number of Pins IO-XLR5-M-EV Gender IO-XLR5-M-EV Series Identifier IO-XLR5-M-EV H = Horizontal PCB Mount V = Vertical PCB Mount

STANDARDS & CLASSIFICATIONS

Product specifications may change without prior notification

Io Audio Technologies® is a registered trademark of Knight Electronics, Inc. 10557 Metric Dr. Dallas, TX 75243 | 214-340-0265 | 800-323-2439 | Fax: 214-340-5870 | www.ioaudiotechnologies.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

IO-XLR5-F-EV IO-XLR5-M-EV