

6-positions Vertical Type SRRN Series

| [Photo](#) | [Dimensions](#) | [Terminal Configuration](#) | [Circuit Diagram](#) | [Packing Specifications](#) | [Shaft Style](#) | [Attached Parts](#) | [Soldering Conditions](#) |

PRINT


Part number		SRRN134300	
Number of wafer		1	
Poles		4	
Positions		3	
Changeover angle		30±3°	
Changeover timing		Non shorting	
Rotational torque		70±30mN·m	
Actuator configuration		18-tooth serration	
Actuator length		L: 15mm	
Operating temperature range		-30℃ to +65℃	
Rating (max.)/(min.) (Resistive load)		0.15A 12V DC/50μA 3V DC	
Electrical performance	Contact resistance (Initial performance/After lifetime)	50mΩ max./100mΩ max.	
	Insulation resistance	100MΩ min. 500V DC	
	Voltage proof	500V AC for 1 minute	
Mechanical performance	Terminal strength	5N for 1 minute	
	Actuator strength	Rotational direction	1N·m
		Push direction	100N
	Wobble of actuator (load at the tip of shaft: 5N)	Measuring position from mounting surface	10mm
		Shaft wobble (max. value)	0.17mm max.
		Applicable mounting dimension	15mm

Durability	Operating life without load	10,000 cycles 70mΩ max.
	Operating life with load (at max. rated load)	10,000 cycles 100mΩ max.
Environmental performance	Cold	-40±2℃ for 96h
	Dry heat	85±2℃ for 96h
	Damp heat	40±2℃, 90 to 95%RH for 96h
Minimum order unit (pcs.)	Japan	100
	Export	600
3D CAD (STEP)		<a href="#">↓</a>
Certificate of Compliance to RoHS regulations		<a href="#">↓</a>

## Photo




## Dimensions



## Terminal Configuration

Unit : mm

Common terminal	Terminal
-----------------	----------



## Circuit Diagram

Number of poles	4	
Circuit diagram		
Dummy terminals	3-positions	—

1. Standard poles per step.
2. The following mark in the above table indicate a stopper with the shaft turned fully counterclockwise when viewed from direction A of the diagrams.



## Packing Specifications

### Bulk


Number of packages (pcs.)	1 case / Japan	100
	1 case / export packing	600
Export package measurements (mm)	369×349×367	

## Shaft Style

### \* 18-tooth Serration Shaft

The shaft shows the position in which it is turned fully counterclockwise.


### Cutting Shaft




	15	6	1	7
	20	10	2	11

### Details About Serration

- (1) The mold dimensions of standard serration and the dimensions of test jigs are as shown in the figure at left.
- (2) Position of the serration bottom  
When the shaft is turned fully counterclockwise, the position of the serration bottom is on the AA line.
- (3) Slitting angle  
The slitting angle (position) is not specified.



### Attached Parts



The following parts are included with the product.

### Soldering Conditions

#### Reference for Dip Soldering

Items	Preheating temperature	-
	Preheating time	-
Dip soldering	Soldering temperature	260±5℃
	Duration of immersion	10±1s

#### Reference for Hand Soldering

Soldering temperature	350±10℃
Soldering time	3+1/0s

---

Notes are common to this series/models.

1. This site catalog shows only outline specifications. When using the products, please obtain formal specifications for supply.
2. All the axis are cutting shafts.
3. Please place purchase orders per minimum order unit (integer).
4. Products other than those listed in the above chart are also available. Please contact us for details.

## Inquiries about Products

 **Inquiry**

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Alps Alpine:](#)

[SRRN134300](#)