## XZCP12V12L2

Pre wired connectors XZ, elbowed female, M12, 5 pins, cable PUR 2 m



#### Main Range of Product Telemecanique Cabling components Accessory / separate Cabling accessory part category Accessory / Separate Pre-wired connectors Part Type Series name

General purpose

Complementary

Complementary		
Electrical connection	Elbowed female connector M12, 5 pins	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	6.56 ft (2 m)	
Cable outer diameter	0.23 in (5.9 mm)	
Cable composition	5 x 0.34 mm²	
Wire insulation material	PUR	
[Ue] rated operational voltage	60 V AC 75 V DC	
Line Rated Current	4 A	
Contact resistance	5000 μOhm	
Minimum insulating resistance	1 GΩ	

#### Environment

IP Degree of Protection	IP67 IP69K IP65	
Product Certifications	cULus	
Ambient air temperature for operation	-40176 °F (-4080 °C) static 23176 °F (-580 °C) flexing	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	

#### Ordering and shipping details

Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389119634953
Returnability	No
Country of origin	CZ

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	7.87 in (20.0 cm)
Package 1 Length	7.28 in (18.5 cm)
Package 1 Weight	2.89 oz (82.0 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	4.37 lb(US) (1.982 kg)
Package 3 Height	5.91 in (15 cm)

### Offer Sustainability

phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
☑ REACh Declaration
Pro-active compliance (Product out of EU RoHS legal scope) EEU RoHS  Declaration
Yes
₫Yes

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Telemecanique Sensors:

XZCP12V12L2