XZCP1440L5

Pre wired connectors XZ, elbowed female, M12, 3 pins, cable PUR 5 m





Main	
Range of Product	Telemecanique Cabling components
Accessory / separate part category	Cabling accessory
Accessory / Separate Part Type	Pre-wired connectors

General purpose

Complementary

Cable connector fixing	Screw-on Metal
	Metal
Collar material	motal .
Status LED	2 NPN LEDs
Cable length	16.40 ft (5 m)
Cable outer diameter	0.20 in (5.2 mm)
Cable composition	3 x 0.34 mm²
Wire insulation material	PUR
[Ue] rated operational voltage	1030 V DC
Line Rated Current	4 A
Contact resistance	5000 μOhm
Minimum insulating resistance	1 GΩ
Net Weight	0.40 lb(US) (0.18 kg)

Series name

Environment

Environment		
IP Degree of Protection	IP69K IP67 IP65	
Product Certifications	cULus	
Ambient air temperature for operation	-40176 °F (-4080 °C) static 23176 °F (-580 °C) flexing	
Ambient Air Temperature for Storage	-40176 °F (-4080 °C)	

Ordering and shipping details

0 11 0	
Category	22483-MACHINE CABLES
Discount Schedule	DS3
GTIN	3389110763294
Returnability	No
Country of origin	CZ

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.79 in (2.0 cm)
Package 1 Width	7.09 in (18.0 cm)
Package 1 Length	7.09 in (18.0 cm)
Package 1 Weight	4.97 oz (140.9 g)
Unit Type of Package 2	S02
Number of Units in Package 2	20
Package 2 Height	5.91 in (15 cm)
Package 2 Width	11.81 in (30 cm)
Package 2 Length	15.75 in (40 cm)
Package 2 Weight	6.91 lb(US) (3.136 kg)
Package 3 Height	5.91 in (15 cm)


Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) E EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	₫Yes
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information

Contractual warranty

Marranti	10 months	
vvarranty	18 months	
,		

Dimensions




L: Lenght of cable

Product data sheet Connections and Schema

XZCP1440L5

Connections and Schemes

Connector



BN: Brown BK: Black BU: Blue

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Telemecanique Sensors:

XZCP1440L5