## Product data sheet Characteristics

## 9007C62B2Y128Y223

## C series, Limit switch, 9007, 600 V 10amp +options

Product availability: Non-Stock - Not normally stocked in distribution facility Important message: We have updated the process to order Telemecanique Sensors products. For more information, please contact your Telemecanique Sensors representative at (US.salesorders@tesensors.com). You can find all product information on the Telemecanique Sensors website: https://tesensors.com/us/en

#### Commercial status

This Product is Obsolete: SEP 01, 2023

#### ⚠ This Product is Obsolete

#### Main

| Device short name | С          |
|-------------------|------------|
| Series name       | Heavy duty |

| Complementary              |                                       |  |
|----------------------------|---------------------------------------|--|
| Line Rated Current         | 10 A                                  |  |
| Body Material              | Zinc alloy                            |  |
| Contact code designation   | R300<br>A600                          |  |
| Contacts material          | Silver alloy (Ag/Ni)                  |  |
| Contact operation          | Snap action                           |  |
| Localisation on device     | Screw stainless steel<br>Head<br>Body |  |
| Maximum displacement angle | 90 °                                  |  |
| Product Compatibility      | 9007C                                 |  |
| Specificity of operator    | Standard pre-travel                   |  |
| Switch actuation           | CW and CCW                            |  |
| Tilting angle              | 10 °                                  |  |
| Torque Value               | 4 Lbf.In (0.5 N.m)                    |  |
| Tripping angle             | 4 °                                   |  |

#### Environment

| Ambient air temperature for operation | -4085 °C (-40185 °F)           | 1 |
|---------------------------------------|--------------------------------|---|
| Product Certifications                | CE[RETURN]UL Listed[RETURN]CSA | 1 |

#### Ordering and shipping details

| Category          | US10DS121499 |  |
|-------------------|--------------|--|
| Discount Schedule | 0DS1         |  |
| GTIN              | 785901895206 |  |
| Returnability     | Yes          |  |
| Country of origin | MX           |  |
|                   |              |  |

## Packing Units

| Unit Type of Package 1       | PCE                  |  |
|------------------------------|----------------------|--|
| Number of Units in Package 1 | 1                    |  |
| Package 1 Height             | 10.16 ln (25.806 cm) |  |
| Package 1 Width              | 4.00 In (10.16 cm)   |  |
| Package 1 Length             | 25.81 ln (65.548 cm) |  |
| Package 1 Weight             | 20.00 Oz (566.99 g)  |  |
| Package 1 Weight             | 20.00 Oz (566.99 g)  |  |

## Environmental data

| Packaging without single use plastic   | No                                       |  |
|--|--|--|
| Packaging made with recycled cardboard   | No                                       |  |
| California proposition 65  WARNING: This product can expose you to chemicals including: Diisor late (DINP), which is known to the State of California to cause cancer, a cyl phthalate (DIDP), which is known to the State of California to cause s or other reproductive harm. For more information go to www.P65Warn |  |  |
| Environmental Disclosure   | Product Environmental Profile            |  |
| Circularity Profile  | No need of specific recycling operations |  |
| Take-back  | No                                       |  |
|  |  |  |

### Contractual warranty

| Warranty | 18 months |  |
|----------|-----------|--|

Product Life Status : End of commercialisation

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Telemecanique Sensors:

9007C62B2Y128Y223