



CB2420A Battery Charger



Features:

- Input: Single-phase 115 - 277 VAC
- Output: Battery charging 24 VDC; 20 A
- Suited for the following battery types:
Open Lead Acid, Sealed Lead Acid, lead Gel and Ni-Cd (option)
- Automatic diagnostic of battery status. Charging curve IUoUo, constant voltage and current
- Switching technology, output voltage 28.8 VDC
- Three charging levels: Boost, Trickle, Recovery.
- Protected against short circuit, inverted polarity, over load.
- Signal output (contact free) for fault battery state
- Protection degree IP20 - DIN rail mountable

INPUT

BATTERY OUTPUT

GENERAL DATA

ENVIRONMENT

SAFETY & EMC

OTHERS

Cat. No.

CB2420A

Input Data

Nominal Input Voltage (2 x VAC)
Input Voltage range (VAC)
Inrush Current (Vn and In Load) I2t
Frequency
Input Current
Internal Fuse
External Fuse (recommended)

115 ~ 230 ~ 277 VAC
90 ~ 135 / 180 ~ 305 VAC
 $\leq 35 \text{ A} \leq 5 \text{ msec.}$
47 ~ 63 Hz $\pm 6\%$
(115 ~ 230 VAC) 8 ~ 4.2 A
10 A
16 A (MCB curve B)

Battery Output (Battery Care)

Boost charge (25°C) (typ. at I_n)
Max. time Bust Charge (typ. at I_n)
Min. time Bust Charge (typ. at I_n)
Trickle charge (25°C) (typ. at I_n)
Recovery Charge
Charging. Max I_{batt} (I_n)
Adjustable charging current (% I_n)
Efficiency (50% - I_n)
Charging current limiting I_{adj}
Quiescent Current
Charging Curve automatic: IUoUo
Detection of element in short circuit
Short-circuit protection
Over Load protection
Over Voltage Output protection
Power Supply Mode
Jumper Configuration battery type
(V cell) Ni-Cd (optional)

28.8 VDC
15 h
1 min.
27.5 VDC
2 ~ 18 VDC
20 A $\pm 5\%$
20 - 100
91%
20 - 100 % I_n
 $\leq 5 \text{ mA}$
3 stage
Yes
Yes
Yes
Yes
Yes
2.23;2.25;2.27;2.3;
1.41-1.5 (20 elem.)

General Data

Insulation voltage (In / Out)
Insulation voltage (In / PE)
Insulation voltage (Out / PE)
Protection Class (EN/IEC 60529)
Protection class
Reliability: MTBF IEC 61709
Pollution Degree Environment
Connection Terminal Blocks screw Type
Dimensions (W-H-D)
Weight

3000 VAC
1605 VAC
500 VAC
IP20
I, with PE connected
> 300.000 hours
2
4 mm(30-10AWG)
150x115x135 mm (5.91 x 4.53 x 5.32 in.)
1.5 Kg approx. (3.31 lbs)

Climate Data

Ambient temperature (operation)
De Rating Ta > 50°C
Ambient temperature Storage
Humidity at 25°C no condensation
Cooling

-25 - +70°C (-13~158°F)
- 2.5%(In) / °C
-40 - +85°C (-40~185°F)
95% to 25°C
Auto Convection

Norms and Certifications

Conforming to:

IEC/EN 60335-2-29,EN60950/UL1950, Electrical safety, 89/336/EEC,
EMC Directive, 2006/95/EC (Low Voltage),DIN41773 (Charging cycle),
Emission:IEC 61000-6-4,Immunity: IEC 61000-6-2.CE

Signal Output (free switch contact)

Main or Backup Power
Low Battery
Fault Battery

Yes
Yes
Yes

Type of Signal Output Contact

Max. current can be switched (EN60947.4.1):
Max. DC1: 30 VDC 1 A; AC1: 60 VAC 1 A
Min.1mA at 5 VDC

Resistive load
Min load

For the latest on Altech Power Supply specifications please visit www.altechcorp.com/power.

CB2420A Battery Charger

Altech Corp.

Technical Features


The CB series battery chargers are designed with advanced multi-stage battery charging method, completely automatic and suited to meet the most advanced requirements of battery manufacturers. The Battery Care concept is based on algorithms that implement rapid and automatic charging, battery charge optimization during time, flat batteries recovery and real time diagnostic during installation and operation. The Real Time Autodiagnostic system, monitoring battery faults such as, elements in short circuit, accidental reverse polarity connection, disconnection of the battery, they can easily be detected and removed by help of Blink Code of Diagnosis Led; during the installation and after sell. Each device is suited for all battery types, by means of jumpers it is possible setting predefined curves for Open Lead Acid, Sealed Lead Acid, Gel, Ni-Cd(option). They are programmed for two charging levels, boost and trickle. A rugged casing with bracket for DIN rail mounting provide IP20 protection degree. They are extremely compact and cost-effective.

Charging



Automatic multi-stage charging and real time diagnostic allow fast recharge and recovery of deep discharged batteries, adding value and reliability to the system hosting. Type of charging is Voltages and current stabilized IUoUo. The state of charging battery and Autodiagnosis of the systems are identified by a flashing code on a Diagnosis LED and Fault Battery LED:

	State	Diagnosis LED	Battery Fault LED
Charging Type	Trickle	1 Blink/sec	OFF
	Boost	2 Blink/sec	OFF
	Recovery	5 Blink/sec	OFF
Auto diagnosis	Reverse polarity	1 Blink	ON
	Battery No connect	2 Blink	ON
	Element in Short C.	3 Blink	ON
	Replace Battery	5 Blink	ON

Jumper for Battery Type Selection




Jumper for Functional Setting




- 1 Jumper present: life test enabled.
- 2 Jumper present: fast test enabled.
- 3 Jumper present: fast recovery charge enabled only for size 3. Possibility to recharge the battery also when the voltage is close to zero with the maximum power of the device.

Wiring Diagram



CB Charging Diagram



PSC Class 2 Series
Compact Housing

PSA Flex Series
1 Phase

PSB Flex Series
2 & 3 Phase

PS-S Slim Series
Plastic Housing

PS Low Profile Series
Plastic Housing

PS Industrial Series
1, 2 & 3 Phase

PSC & W Series
1 and 2 Phase

CB Type
DC UPS Systems

CB Type
Battery Chargers

Accessories

Appendix

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Altech:](#)

[CB2420A](#)