

**SERIES:** SF500G | **DESCRIPTION:** THERMAL PAD**FEATURES**

- 3.5 W/m*K thermal conductivity
- naturally tacky
- silicone based
- electrical isolation
- sizes to match CUI peltier footprints

**SPECIFICATIONS**

parameter	test method/conditions/description	min	typ	max	units
material	silicone elastomer				
color	blue				
thickness	ASTM D751		0.5		mm
specific gravity	ASTM D297		3.0		g/cc
hardness	ASTM D2240	25		80	shore 00
tensile strength	ASTM D412		25		psi
continuous use temperature		-58		200	°C
dielectric breakdown voltage	ASTM D149	2500			V
dielectric constant [1 MHz]	ASTM D150		6.0		
volume resistivity	ASTM D257		10 ¹³		Ω*cm
thermal conductivity	ASTM D5470		3.5		W/m*K
RoHS	yes				

PART NUMBER KEY**SF500G - XXXX 05**

Base Number

Footprint Size (mm):

10x10 = 1010

15x15 = 1515

15x30 = 1530

20x20 = 2020

20x40 = 2040

26.25x50 = 2650

30x12 = 3012

30x30 = 3030

31.25x30 = 3130

40x40 = 4040

41.25x45 = 4145

50x50 = 5050

70x70 = 7070

REVISION HISTORY

rev.	description	date
1.0	initial release	11/02/2018
1.01	brand update	03/24/2020
1.02	logo, datasheet style update	08/05/2022
1.03	CUI Devices rebranded to Same Sky	09/12/2024

The revision history provided is for informational purposes only and is believed to be accurate.



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Same Sky:](#)

[SF500G-101005](#) [SF500G-151505](#) [SF500G-153005](#) [SF500G-202005](#) [SF500G-204005](#) [SF500G-265005](#) [SF500G-707005](#) [SF500G-301205](#) [SF500G-303005](#) [SF500G-313005](#) [SF500G-404005](#) [SF500G-414505](#) [SF500G-505005](#)