

Additional Resources: Product Page | PCB Footprint

date 09/12/2024

page 1 of 3

MODEL: UJ2-B-HR-G-TH | DESCRIPTION: USB RECEPTACLE

FEATURES

- USB Type B receptacle
- board lock
- USB 2.0





SPECIFICATIONS

	·				
parameter	conditions/description	min	typ	max	units
USB standard	USB 2.0				
rated input voltage				5	Vdc
rated input current				1.5	А
contact resistance ¹	between terminals and mating plug			30	mΩ
insulation resistance	between adjacent contacts	1000			МΩ
voltage withstand	between adjacent contacts	500			Vac
insertion force				35	N
withdrawal force		10			N
life			1,500		cycles
operating temperature		-40		85	°C
flammability rating	UL94V-0				
RoHS	yes				

Note:

SOLDERABILITY

parameter	conditions/description	min	typ	max	units
wave soldering	for 3-7 seconds	255	265	275	°C

^{1.} When measured at 20 mV / 100 mA.
2. All specifications measured at 10-35°C, humidity at 45-85%, under standard atmospheric pressure, unless otherwise noted.

MECHANICAL DRAWING

units: mm tolerance: X. ±0.50 mm X.X ±0.30 mm X.XX ±0.20 mm X.XXX ±0.10 mm unless otherwise specified

D-

D+

GND

SHIELD

PIN 1 2

3

4

SHELL


.2 D.	: 111111 20 mm .10 mm herwise speci	fied		
	PIN	CONNECTIONS		/ \
	SIGNAL NAME	DESCRIPTION	MATING SEQUENCE	
	Vaus	power	SECOND	

THIRD

SECOND

FIRST


DESCRIPTION	MATERIAL	PLATING/COLOR	
insulator	LCP (UL94V-0)	black	
contact	copper alloy t=0.25 mm	contact area: gold flash solder area: tin over nickel	
shell	SPCC / copper alloy t=0.30 mm	nickel	





USB 2.0 DIFFERENTIAL PAIR


ground for power

metal shell









Recommended PCB Layout Top View

Additional Resources: Product Page | PCB Footprint

SAME SKY | MODEL: UJ2-B-HR-G-TH | DESCRIPTION: USB RECEPTACLE

date 09/12/2024 | **page** 3 of 3

REVISION HISTORY

rev.	description	date	
1.0	initial release	08/23/2023	
1.01	CUI Devices rebranded to Same Sky	09/12/2024	

The revision history provided is for informational purposes only and is believed to be accurate.



Same Sky offers a one (1) year limited warranty. Complete warranty information is listed on our website.

Same Sky reserves the right to make changes to the product at any time without notice. Information provided by Same Sky is believed to be accurate and reliable. However, no responsibility is assumed by Same Sky for its use, nor for any infringements of patents or other rights of third parties which may result from its use.

Same Sky products are not authorized or warranted for use as critical components in equipment that requires an extremely high level of reliability. A critical component is any component of a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Same Sky:

UJ2-B-HR-G-TH