
	8	3	7		6	1	5	ŧ	4
	THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF L-COM, INC. ANY REPRODUCTIONS IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF L-COM, INC. IS PROHIBITED.								
		WIRING MAR	0	]		$\exists$			
	"P1"	COLOR	"P2"	-		Þ			
D	1	BLACK	1	_		1			
	2	BROWN	2	-		ſ			
	3	RED	3	-		$\exists$			
	4	ORANGE	4	-		)			
	5	YELLOW	5	-					
	6	GREEN	6						— LENGTH ——
_	7	BLUE	7						
	8	PURPLE	8				–2X, MOLDED HOOD AND		
	9	GRAY	9				STRAIN RELIEF, WITH 360°		
	10	WHITE	10	_		/	METAL FOIL SHIELD, I	PVC,	
	11	PINK	11	_		_ /	LIGHT GRAY (400C)		
	12	LIGHT GREEN		_		–/			
С	13	BLACK / WHIT	E 13			4			
5	14	BROWN / WHI	TE 14			~			
	15	RED / WHITE	15						



SHELL

DRAIN WIRE



6



-U.L. STYLE 2464 15 COND., 26AWG STRANDED TINNED COPPER WITH ALUM/POLY FOIL SHIELD AND DRAIN WIRE PLUS TINNED COPPER BRAID SHIELD JACKET: PVC, LIGHT GRAY, (PANTONE 400C)

LENGTH FEET [METERS]			
1.0 [.31]			
2.5 [.76]			
5.0 [1.52]			
10.0 [3.05]			
15.0 [4.57]			
25.0 [7.62]			

UNLESS OTHERWISE SPECIFIED,	
DIMENSIONS ARE IN INCHES [mm]	DF
OVERALL CABLE LENGTH TOLERANCE:	C
≤12 [305] = +1 [25] / -0 >12 [305] ≤60 [1524] = +2[51] / -0	CI
>60 [1524] [ ≤120 [ 3048] = +4 [ 102] / -0	R
>120`[3048] <300`[7620] = +6`[152] / -0 >300 [7620] = +5% / -0%	Ał
	S
ALL OTHER DIMENSIONAL TOLERANCES: .X = ±.2 [5.08]	(
$.XX = \pm .02 [.51]$ $.XXX = \pm .005 [.13]$	
PROJECTION	
+(+)++	
$\varphi = 1$	
3	Τ

3

Ε

ſ

## NOTES:

8

B

А

SHELL

- 1. CABLE ASSEMBLY SHALL BE TESTED FOR CONTINUITY.
- 2. CABLE ASSEMBLY SHALL BE INDIVIDUALLY PACKAGED IN ACCORDANCE WITH L-COM SPECIFICATION PS-0031.

## **REGULATORY COMPLIANCE:**

CE2011/65/EU(ROHS DIRECTIVE)


	2	1								
REVISIONS										
REV	DESCRIPTION	DATE	CHANGED BY							
А	INITIAL RELEASE		12/17/13	D.GRIFFIN						

D

С

В

-4X 4-40 UNC-2A THUMBSCREW



## 2X, DB15 MALE CONNECTOR





## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

infinite Electronics:

<u>CSMNRA15-4MM-5</u> <u>CSMNRA15-4MM-15</u> <u>CSMNRA15-4MM-2.5</u> <u>CSMNRA15-4MM-10</u> <u>CSMNRA15-4MM-25</u> CSMNRA15-4MM-1