

FDI 4.3" Resistive Touch Screen LCD GUI

The 4.3" Resistive Touch LCD GUI, **uEZGUI-1788-43WQR-BA**, provides a cost effective resistive touch option in the standalone microcontroller-based **μEZ®** GUI product family. Featuring a beautiful resistive touch TFT LCD panel, this product is a high value "off-the-shelf" Graphical User Interface (GUI) or Human Machine Interface (HMI) design for easy integration into a variety of end customer applications.

The Future Designs, Inc. **μEZ®** GUI product family is our standalone microcontroller-based solution designed for the easy integration of modern human machine interfaces (HMI) into a variety of end applications. Each **μEZ** GUI product includes a display with supporting hardware and FDI's open source **μEZ / FreeRTOS** software. FDI's **μEZ** GUI development kits include everything needed to kick off a **μEZ** GUI project including JTAG debugger, power supply, cables, microSD card and full documentation. Once your design is complete, we offer cost-effective production modules for prototypes or high-volume production.

FDI also offers engineering design and production support services. We are committed to saving our customers time, money and hassle. So, no matter how much (or little) support you need along the way, we can make your project concept a reality.

μEZ GUI Products are available for immediate order at www.TeamFDI.com or from any of our franchised distributors.



Module Features

- 4.3" WQVGA 480 x 272 4-Wire Resistive Touch Screen LCD Panel
- NXP LPC1788 120MHz CPU with 512KB internal Flash
- 8MB of NOR Flash (optional to 32MB)
- 8MB of SDRAM (optional to 32MB)
- MicroSD Memory Card Socket
- USB Device Mini-AB for 5.0 VDC power and PC communications
- USB Host support through adapter cable
- NV Data Storage via 4KB Internal EEPROM
- Internal Real-Time Clock with Supercap Backup
- Speaker, 3-axis Accelerometer, Temperature Sensor
- Mini-JTAG Debug Connector
- External Expansion via two I/O Connectors (70 pins)
 - UART, I2C, SPI, USB Host/Device, RMII Ethernet

Development Kit Part #: **uEZGUI-1788-43WQR**
Development Kit MSRP (Qty 1) : \$299.00 (USD)
Production Module Part #: **uEZGUI-1788-43WQR-BA**
Production Module MSRP (Volume) <\$140.00 (USD)

Production guaranteed until 2024 or longer.



Sales@TeamFDI.com
(256) 883-1240



TeamFDI.com



YouTube.com/
FDIProducts

Technical Specifications

Production Module

- Part number: **uEZGUI-1788-43WQR-BA**
- MSRP (Volume) <\$140.00 (USD)
- Contrast Ratio: 500 : 1 typical
- Brightness: 300 nits typical
- Horizontal Viewing Angle: 80° L / 80° R
- Vertical Viewing Angle: 55° U / 80° D
- Power consumption typ/max: 350 / 500mA
- Overall Size: 116.8(W) x 72.1(H) x 12.9(D) mm
- Operating Temperature Range: -20°C to +70°C
- Viewable area: 95.0(W) x 53.9(H) mm
- Weight: 100g
- Resolution: 480x272
- Glass Overlay: 0.55mm
- Glass Hardness: 2H

Development Kit

- Part number: **uEZGUI-1788-43WQR**
- MSRP (Qty 1): \$299.00 (USD)
- Includes uEZGUI-1788-43WQR-BA Production Module
- AC power supply
- Mini JTAG debugger with cables
- USB device cables for power and PC communications
- 4GB (or larger) microSD memory card
- Documentation and example software



uEZ Software

μEZ® (pronounced Muse) is an open source rapid development platform that allows companies to focus on innovation and their value-added applications while minimizing development time and maximizing software reuse. μEZ components comprise three primary categories to simplify embedded application development: Operating System Abstraction Layer (μEZ® OSAL), Sub-system drivers (ex: μEZ® TCP/IP, μEZ® USB, μEZ® Driver), and Hardware Abstraction Layer (μEZ® HAL)

FreeRTOS with Tasks, Semaphores, Mutex, Queues

SafeRTOS option for safety critical real-time applications

emWin Graphics library free with NXP ARM MCUs

FAT FS for USB/SD card with long-file name support

USB Host/Device including mass storage, HID Libraries

Wi-Fi library with integration into TCP/IP Stack from GainSpan

SEGGER JTAG development and production SW integration

10/100 Ethernet support with lwIP TCP/IP Stack

Memory SDRAM, NOR Flash, SPIFI Flash support

Audio PWM, DAC, and I2S support

TFT LCD support for QVGA, VGA, WQVGA, WVGA Displays

Multiple compilers and IDEs supported

Modbus TCP/IP and RTU support

Serial Comms I2C, SPI, UART, RS232, RS485, CAN & GPIO

Bootloader for field updates over SD/USB/Serial (affordable μEZ+)



Sales@TeamFDI.com
(256) 883-1240



TeamFDI.com



YouTube.com/
FDIProducts

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Future Designs, Inc. \(FDI\):](#)

[UEZGUI-1788-43WQR-BA](#)