1325

80W POWER SUPPLY WITH USB OUTPUT

Applications

The 1325's small size and quiet operation make it ideal for laboratory, work shop, or educational applications where bench space is limited.

- Educational labs
- Technical schools
- Internal training facilities
- Hobbyists



Overview

The 1325 is DC power supply which gives 80 W of power output. By using a digital + / - keypad operation control, you can easily set the output voltage and current levels.

Only 8 inches long, this unit fits on the bench where others units wouldn't.

The USB output is perfect for charging a cell phone.

Features

• Power: 80 W

Voltage: 1-16 VDC

Current: 0-5 A

• USB charging port, 5 VDC and 1.2 A Max

Small compact size

• 3-Digit display shows voltage or current

 Automatic crossover and constant current (CC)

Constant voltage operation (CV)

Tracking Over Voltage Protection (OVP)

Over Temperature Protection (OTP)



1325

All specifications apply to the unit after a temperature stabilization time of 15 minutes over an ambient temperature range of 25 $^{\circ}$ C \pm 5 $^{\circ}$ C.

1325 Power Supply	
Electrical Specificaitons	
Output Voltage	1–16 VDC
Output Current	0-5 A
Switching Operation Frequency	80 kHz to 120 kHz
Efficiency at Max Power	≥82%
Voltmeter and Ampmeter Display	3 Digit 7-Segments LED
Voltmeter Accuracy	+1% rdg + 3 digits.
Ammeter Accuracy	+1% rdg + 5 digits
Resolution	0.1V, 0.01A
Line Input	100-120 VAC (50-60 Hz) ±10%
Full Load Input Current at 110 VAC	1.8 A
Cooling System	Natural Convection
Constant Voltage Characteristics	
Load regulation (10%-90%)	±50 mV
Line regulation (min to max)	±20 mV
Ripple (rms)	±20 mV
Noise (peak to peak)	±100 mV
Constant Current Characteristics	
Load regulation (10%-90%)	±30 mA
Line regulation (min to max)	±10 mA
USB Output	
Output Voltage	5 V (±5%)
Output Current	1.2 A Max



1325

1325 Power Supply		
Environmental Conditions		
Operating Temp/Humidity	max RH of 80% at 31°C decreasing linearly to 50% at 40°C	
Altitude	up to 2,000 m	
Polution Degree	Polution Degree 2	
Mechanical Characteristics		
Weight	3.0 lbs (1.4 kg)	
Dimensions	2.8 x 6.0 x 7.9 in (70 x 150 x 200 mm)	

Specifications are subject to change without notice. To ensure the most current version of this manual, please download the current version from our website: globalspecialties.com.





Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Global Specialties:

1325