

Quality Products. Service Excellence.

Type 4X Polyester Junction Box w/ Raised Lid (Solid and Window) PJ

Series

Continuous Hinge Door with Snap Latches



Panel Sold Separately







Application

- Designed for use as instrument enclosures, electric, hydraulic or pneumatic control housings, electrical junction boxes or terminal wiring enclosures.
- Provides outstanding insulation and protection where equipment may be hosed down or be very wet.
- Ideal in applications with high temperatures or highly corrosive environments.

Standards

- UL 508A Type 1, 2, 3, 4, 4X, 12 and 13
- cUL Type 1, 2, 3, 4, 4X, 12 and 13 per CSA 22.2 No. 94
- Complies with
 - NEMA Type 1, 2, 3, 4, 4X, 12, & 13
 - IEC 60529, IP66

Construction

- Molded fiberglass polyester enclosure with matching cover is easily punched, cut, or drilled.
- Enhanced UV inhibitors protect against outdoor weathering.
- Standard JIC sizes under 18"x16".
- Threaded brass inserts are provided for optional inner panel or terminal kit mounting. Mounting hardware is included.
- Stainless steel draw type "snap latch" door fasteners.
- Door fasteners include a provision for padlocking.
- Enclosures are available with bonded polycarbonate viewing windows.
- Door is supported with a continuous stainless steel hinge.
- Captive oil resistant gasket provides a positive seal.
- Threaded brass inserts are provided for mounting feet to the rear of the enclosure.
- Stainless steel mounting brackets and hardware are provided for mounting to the rear of the enclosure.
- Operating temperatures between 130°C and -40°C (266°F to -40°F).
- Impact index of 6.78J (5 ft/lb).
- For corrosion resistance information, please refer to table in the Technical Information section.

Finish

- Fiberglass polyester material has a gray finish.
- Optional inner panels are available in white powder coated finished steel or unfinished aluminum, or fiberglass.

Accessories

- Additional Inner Panels
- Swing Panels

- Terminal Kit Assemblies
- Pole Mounting Kit

- PJ/PJU/PCJ Replacement Hardware Kits
- Climate Control

- PJ Stainless Replacement Mounting Feet
- General Accessories

New and improved PDF part drawing files with more detail now available.

Click part number in table below to access PDF, DXF, and STEP files.

Solid Cover	Window	E	Enclosure			Optional Inner Panel		
Part No.	Cover Part No.	н	W	D	н	D	Part No.	
PJ664RL	PJ664RLW	6.10	6.10	4.18	4.88	4.88	14R0505	
PJ864RL	PJ864RLW	8.00	6.12	4.13	6.75	4.88	14R0705	
PJ1084RL	PJ1084RLW	10.13	8.26	4.13	8.75	6.88	14R0907	
PJ1086RL	PJ1086RLW	10.13	8.26	6.13	8.75	6.88	14R0907	
PJ12106RL	PJ12106RLW	12.13	10.26	6.13	10.75	8.88	14R1109	
PJ12124RL	PJ12124RLW	13.33	11.85	4.13	12.32	13.72	14R1111	
PJ12126RL	PJ12126RLW	13.33	11.85	6.13	12.32	13.72	14R1111	
PJ14126RL	PJ14126RLW	14.13	12.26	6.13	12.75	10.88	14R1311	
PJ16148RL	PJ16148RLW	16.27	14.40	8.13	14.75	12.88	14R1513	
PJ18168RL	PJ18168RLW	18.40	16.40	8.13	16.88	14.88	P1868	
PJ20168RL	PJ20168RLW	20.00	16.00	8.13	18.44	14.44	P2068	
PJ24208RL	PJ24208RLW	24.00	20.00	8.13	21.00	17.00	18P2117	
PJ24248RL ¹	PJ24248RLW ¹	24.00	24.00	8.13	21.00	21.00	18P2121	
PJ30248RL1	PJ30248RLW ¹	30.00	24.00	8.13	27.00	21.00	18P2721	
PJ242010RL ¹	PJ242010RLW ¹	24.00	20.00	10.13	21.00	17.00	18P2117	
PJ242410RL ¹	PJ242410RLW ¹	24.00	24.00	10.13	21.00	21.00	18P2121	
PJ302410RL ¹	PJ302410RLW ¹	30.00	24.00	10.13	27.00	21.00	18P2721	

Alternative inner panel options also available. ¹ Uses larger mounting foot.

Tags: PJ, polyester, fiberglass, non-metallic, raised lid, junction box, NEMA 4X, Type 4X, outdoor, window, continuous hinge, snap latch

Data subject to change without notice

© 2024. Hammond Manufacturing Ltd. All rights reserved.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Hammond:

PJ24208RL PJ24248RLW PJ242410RL PJ302410RL PJ18168RL PJ24248RL PJ242010RL PJ20168RL PJ18168RLW PJ302410RLW PJ30248RL PJ14126RLW PJ14126RL PJ20168RLW PJ664RLW PJ242410RLW PJ12106RLW PJ16148RLW PJ24208RLW PJ12106RL PJ664RL PJ1086RL PJ242010RLW PJ16148RL PJ1086RLW PJ864RL PJ30248RLW PJ864RLW PJ1084RL PJ12124RLW PJ12126RLW PJ1084RLW PJ12124RL PJ12126RL