

# Han Q High Density -M-



Image is for illustration purposes only. Please refer to product description.

Part number	09 12 021 3001
Specification	Han Q High Density -M-
HARTING eCatalogue	<a href="https://b2b.harting.com/09120213001">https://b2b.harting.com/09120213001</a>

## Identification

Category	Inserts
Series	Han® Q
Identification	High Density

## Version

Termination method	Crimp termination
Gender	Male
Size	3 A
Number of contacts	21
Details	Please order crimp contacts separately.

## Technical characteristics

Conductor cross-section	0.09 ... 0.56 mm²
Rated current	6.5 A
Rated voltage	50 V
Rated voltage	50 V AC 120 V DC
Rated impulse voltage	0.8 kV
Pollution degree	3
Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 ... +125 °C
Mating cycles	≥500



**Pushing Performance**  
Since 1945

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Yes
California Proposition 65 substances	Nickel Naphthalene
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Approvals	DNV GL

## Commercial data

Packaging size	10
Net weight	3 g
Country of origin	Romania
European customs tariff number	85366990
GTIN	5713140018129
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09120213001](#)