

## Han Megabit HMC insert male



Part number	09 14 208 3016
Specification	Han Megabit HMC insert male
HARTING eCatalogue	https://b2b.harting.com/09142083016

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Modules
Type of module	Han <sup>®</sup> Megabit HMC module
Description of the module	Insert 2x 4 contacts 2 cable entries
Version	
Termination method	Crimp termination
Gender	Male
Number of contacts	8
further contacts	+ shielding
Details	Please order crimp contacts separately. Please order adapter module separately.

#### Technical characteristics

Details

Conductor cross-section	0.14 2.5 mm²
Wire outer diameter	≤3.5 mm
Rated current	10 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3

Han-Modular<sup>®</sup> Compact and Han-Modular<sup>®</sup> Twin.

Not suitable for hoods/housings low construction as well as Han-Modular<sup>®</sup> Eco,

Page 1 / 3 | Creation date 2024-11-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 14 208 3016 Han Megabit HMC insert male



#### Technical characteristics

Rated current acc. to UL	2 A AWG 26 AWG 20 6 A AWG 18 8 A AWG 16 AWG 14
Rated voltage acc. to UL	30 V
Transmission characteristics	Cat. 5 Class D up to 100 MHz
Data rate	100 Mbit/s
Contact resistance, shielding	≤100 mΩ
Limiting temperature	-40 +85 °C
Mating cycles	≥10,000
Note on the mating cycles	Mating cycles with other HMC components

#### Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (shielding)	Zinc die-cast, nickel-plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

### Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Approvals	DNV GL
Commercial data	
Packaging size	1

Page 2 / 3 | Creation date 2024-11-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com Product data sheet 09 14 208 3016 Han Megabit HMC insert male



#### Commercial data

Net weight	42 g
Country of origin	Romania
European customs tariff number	85389099
GTIN	5713140187627
ETIM	EC000438
eCl@ss	27440218 Module for industrial connectors (data)

Page 3 / 3 | Creation date 2024-11-30 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09142083016 9142083016