

# M23 09 Female -solder (termination)



Part number	09 15 109 2702
Specification	M23 09 Female -solder (termination)
HARTING eCatalogue	https://b2b.harting.com/09151092702

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Inserts
Series	Circular connectors M23
Identification	Signal
Element	Inserts

#### Version

Termination method	Solder termination
Gender	Female
Number of contacts	9
Number of signal contacts	8
Number of special contacts	1
Specification of special contacts	Auxiliary contact

#### Technical characteristics

Conductor cross-section	1 mm² max.
Rated current (signal)	8 A
Rated voltage (signal)	200 V
Rated impulse voltage (signal)	2.5 kV
Pollution degree (signal)	3
Rated current (special contact)	20 A
Rated voltage (special contact)	200 V
Rated impulse voltage (special contact)	2.5 kV
Pollution degree (special contact)	3



## Technical characteristics

Insulation resistance	>10 <sup>10</sup> Ω
Limiting temperature	-40 +125 °C
Mating cycles	≥500

# Material properties

Polyamide (PA)
White
Copper alloy
Gold plated
V-0
compliant with exemption
6(c): Copper alloy containing up to 4 % lead by weight
compliant with exemption
50
Not contained
Not contained
Yes
Lead
052d6da0-30ef-44e8-bbe4-e75780521d22
Yes
Lead

# Specifications and approvals

UL / CSA	UL 1977 ECBT2.E235076	
UL / CSA	OL 1977 ECB12.E235076	

## Commercial data

Packaging size	5
Net weight	8.602 g
Country of origin	Germany
European customs tariff number	85366990
GTIN	5713140163010
ETIM	EC003557
eCl@ss	27440223 Contact insert for circular connectors

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

# HARTING:

09151092702 9151092702