


# SEK-18 SV MA STD STR29 RLG 26P PL2



| Part number        | 09 18 526 6904                        |
|--------------------|---------------------------------------|
| Specification      | SEK-18 SV MA STD STR29 RLG 26P<br>PL2 |
| HARTING eCatalogue | https://b2b.harting.com/09185266904   |

Image is for illustration purposes only. Please refer to product description.

## Identification

| Category                   | Connectors     |
|----------------------------|----------------|
| Series                     | SEK Standard   |
| Element                    | Male connector |
| Description of the contact | Straight       |

#### Version

| Termination method | Wave soldering termination |
|--------------------|----------------------------|
| Connection type    | PCB to cable               |
| Number of contacts | 26                         |
| Termination length | 2.9 mm                     |
| Locking type       | With long levers           |

# Technical characteristics

| Contact rows                       | 2                         |
|------------------------------------|---------------------------|
| Contact spacing (termination side) | 2.54 mm                   |
| Rated current                      | 1 A                       |
| Insulation resistance              | >10 <sup>9</sup> Ω        |
| Contact resistance                 | ≤20 mΩ                    |
| Limiting temperature               | -55 +125 °C               |
| Insertion and withdrawal force     | ≤52 N                     |
| Performance level                  | 2<br>acc. to IEC 60603-13 |
| Mating cycles                      | ≥250                      |

Page 1 / 3 | Creation date 2024-04-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Technical characteristics

| Test voltage U <sub>r.m.s.</sub>   | 1 kV  |
|--|---|
| Isolation group  | IIIa (175 ≤ CTI < 400)  |
|  |   |
| Material properties  |   |
| Material (insert)  | Thermoplastic resin (PBT)   |
| Colour (insert)  | Grey  |
| Material (contacts)  | Copper alloy  |
| Surface (contacts)   | Noble metal over Ni Mating side<br>Sn over Ni Termination side                    |
| Material flammability class acc. to UL 94  | V-0   |
| RoHS   | compliant   |
| ELV status   | compliant   |
| China RoHS   | e   |
| REACH Annex XVII substances  | Not contained   |
| REACH ANNEX XIV substances   | Not contained   |
| REACH SVHC substances  | Not contained   |
| California Proposition 65 substances   | Yes   |
| California Proposition 65 substances   | Antimony trioxide<br>Lead<br>Nickel   |
| Fire protection on railway vehicles  | EN 45545-2 (2020-08)  |
| Requirement set with Hazard Levels   | R26   |
|  |   |
| Specifications and approvals   |   |
| Specifications and approvals Specifications  | IEC 60603-13  |
|  | IEC 60603-13<br>UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079        |
| Specifications   | UL 1977 ECBT2.E102079   |
| Specifications<br>UL / CSA   | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079                        |
| Specifications UL / CSA Railway classification   | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079                        |
| Specifications UL / CSA Railway classification Commercial data                           | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079<br>F3/I3               |
| Specifications UL / CSA Railway classification Commercial data Packaging size            | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079<br>F3/I3               |
| Specifications UL / CSA Railway classification Commercial data Packaging size Net weight | UL 1977 ECBT2.E102079<br>CSA-C22.2 No. 182.3 ECBT8.E102079<br>F3/I3<br>100<br>9 g |

Page 2 / 3 | Creation date 2024-04-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 18 526 6904 SEK-18 SV MA STD STR29 RLG 26P PL2



Commercial data


ETIM

eCl@ss

EC002637

27460201 PCB connector (board connector)

Cross section of solder termination



# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09185266904