

SEK-19 SV HT MA STD STR29 RLG 06P PL3



| Part number | 09 19 506 7904 |
|--------------------|--|
| Specification | SEK-19 SV HT MA STD STR29 RLG 06P PL3 |
| HARTING eCatalogue | https://b2b.harting.com/09195067904 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------------------|----------------|
| Series | SEK Standard |
| Element | Male connector |
| Description of the contact | Straight |

Version

| Termination method | Reflow soldering termination (THR) |
|--------------------|------------------------------------|
| Connection type | PCB to cable |
| Number of contacts | 6 |
| Termination length | 2.9 mm |
| Locking type | With long levers |

Technical characteristics

| Contact rows | 2 |
|------------------------------------|---|
| Contact spacing (termination side) | 2.54 mm |
| Rated current | 1 A |
| Insulation resistance | >10 ⁹ Ω |
| Contact resistance | ≤20 mΩ |
| Limiting temperature | -55 +125 °C (during reflow soldering max. +240 °C for 60 s) |
| Insertion force | ≤18 N |
| Withdrawal force | ≤18 N |
| Performance level | 3 acc. to IEC 60603-13 |

Page 1 / 3 | Creation date 2024-04-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Technical characteristics

| Mating cycles | ≥50 |
|----------------------------------|----------------------|
| Test voltage U _{r.m.s.} | 1 kV |
| Isolation group | II (400 ≤ CTI < 600) |

Material properties

| Material (insert) | Thermoplastic resin (PCT) |
|---|--|
| Colour (insert) | Beige |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Noble metal over Ni Mating side Sn over Ni Termination side |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |
| Fire protection on railway vehicles | EN 45545-2 (2020-08) |
| Requirement set with Hazard Levels | R26 |

Specifications and approvals

| Specifications | IEC 60603-13 |
|----------------|--|
| UL / CSA | UL 1977 ECBT2.E102079 CSA-C22.2 No. 182.3 ECBT8.E102079 |

Commercial data

| Packaging size | 100 |
|--------------------------------|---------------|
| Net weight | 5.91 g |
| Country of origin | Romania |
| European customs tariff number | 85366990 |
| GTIN | 5713140036505 |
| ETIM | EC002637 |

Page 2 / 3 | Creation date 2024-04-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com Product data sheet 09 19 506 7904 SEK-19 SV HT MA STD STR29 RLG 06P PL3




Commercial data

eCl@ss

27460201 PCB connector (board connector)

Cross section of solder termination



Page 3 / 3 | Creation date 2024-04-27 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09195067904