

### SEK mezz Fe 50P THT 2.9mm PL3



| Part number        | 09 19 550 7824                      |
|--------------------|-------------------------------------|
| Specification      | SEK mezz Fe 50P THT 2.9mm PL3       |
| HARTING eCatalogue | https://b2b.harting.com/09195507824 |

Image is for illustration purposes only. Please refer to product description.

#### Identification

| Category                   | Connectors       |
|----------------------------|------------------|
| Series                     | SEK Mezzanine    |
| Element                    | Female connector |
| Description of the contact | Straight         |

#### Version

| Termination method | Reflow soldering termination (THR) Wave soldering termination |
|--------------------|---|
| Connection type    | PCB to PCB<br>Motherboard to daughtercard                     |
| Number of contacts | 50  |
| Termination length | 2.9 mm  |

#### Technical characteristics

| Contact rows                       | 2   |
|------------------------------------|---|
| Contact spacing (termination side) | 2.54 mm   |
| Rated current                      | 1 A   |
| Insulation resistance              | >10 <sup>9</sup> Ω  |
| Contact resistance                 | ≤20 mΩ  |
| Limiting temperature               | -55 +125 °C (during reflow soldering max. +240 °C for 60 s) |
| Insertion force                    | ≤150 N  |
| Withdrawal force                   | ≤150 N  |
| Performance level                  | 3   |
| Mating cycles                      | ≥50   |



#### Technical characteristics

| Test voltage U <sub>r.m.s.</sub> | 1 kV                   |
|----------------------------------|------------------------|
| Isolation group                  | IIIa (175 ≤ CTI < 400) |

#### Material properties

| Material (insert)                         | Liquid crystal polymer (LCP)                             |
|---|--|
| Colour (insert)                           | Black  |
| Material (contacts)                       | Copper alloy   |
| Surface (contacts)                        | Sn over Ni Termination side<br>Au over Pd/Ni Mating side |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant  |
| ELV status                                | compliant  |
| China RoHS                                | е  |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Not contained  |
| California Proposition 65 substances      | Not contained  |

#### Specifications and approvals

| Specifications | IEC 60603-13                      |
|----------------|-----------------------------------|
| UL / CSA       | UL 1977 ECBT2.E102079             |
|                | CSA-C22.2 No. 182.3 ECBT8.E102079 |

#### Commercial data

| Packaging size                 | 50                                       |
|--------------------------------|--|
| Net weight                     | 12.65 g                                  |
| Country of origin              | China                                    |
| European customs tariff number | 85366990                                 |
| GTIN                           | 5713140212626                            |
| ETIM                           | EC002637                                 |
| eCl@ss                         | 27460201 PCB connector (board connector) |

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## HARTING:

09195507824 9195507824