



Pushing Performance  
Since 1945

# Han PushPull Power 4/0 M-L (straight)



Image is for illustration purposes only. Please refer to product description.

Part number	09 35 002 3004
Specification	Han PushPull Power 4/0 M-L (straight)
HARTING eCatalogue	<a href="https://b2b.harting.com/09350023004">https://b2b.harting.com/09350023004</a>

## Identification

Category	Connectors
Series	Han® PushPull (V14)
Identification	Power
Element	Male
Specification	Straight
Features	Intuitive locking mechanism

## Version

Termination method	Solder termination
Shielding	Unshielded
Number of contacts	5
Locking type	PushPull

## Technical characteristics

Rated current	16 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Limiting temperature	-40 ... +70 °C
Mating cycles	≥500
Degree of protection acc. to IEC 60529	IP65 IP67



**Pushing Performance**  
Since 1945

## Technical characteristics

Isolation group	I ( $600 \leq CTI$ )
Vibration resistance	5-150 Hz, 5 g, 0.35 mm, 2h/axis
Shock resistance	5 g / 30 ms, 3 shocks / axis and direction

## Material properties

Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material (hood/housing)	Thermoplastic
Colour (hood/housing)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	IEC 61076-3-118 EN 45545-2
UL / CSA	UL 1977 ECBT2.E235076 CSA-C22.2 No. 182.3 ECBT8.E235076
Approvals	DNV GL

## Commercial data

Packaging size	10
Net weight	4.94 g
Country of origin	Romania



**Pushing Performance**  
Since 1945

Commercial data

European customs tariff number	85366990
GTIN	5713140053694
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09350023004](#)