

PP-V4-CA-USB2A-PP/IP20-P-P-STR-1.5



| Part number | 09 45 445 1912 |
|--------------------|-------------------------------------|
| Specification | PP-V4-CA-USB2A-PP/IP20-P-P-STR-1.5 |
| HARTING eCatalogue | https://b2b.harting.com/09454451912 |

Image is for illustration purposes only. Please refer to product description.

Identification

Limiting temperature

| Category Series Element | System cabling HARTING PushPull (V4) |
|-------------------------------|---|
| | |
| Element | |
| | Cable assemblies |
| Specification | Pre-assembled on both sides |
| Connector 1 | HARTING PushPull (V4) USB 2.0 Type A |
| Connector 2 | IP20 USB 2.0 Type A |
| Type of cable | Copper cable (round) |
| Version | |
| Cable length | 1.5 m |
| Number of cores | 4 |
| Core structure | 2x AWG 26/7 2x AWG 24/11 |
| Shielding | Shielded |
| Technical characteristics | |
| Rated current | 1.5 A |
| Rated voltage | 30 V DC |
| Data rate | 480 Mbit/s |
| | |
| Insulation resistance | > 1.6 x 10 ⁶ Ω |

Page 1 / 3 | Creation date 2024-03-21 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

-40 ... +85 °C



Technical characteristics

| Insertion force | ≤35 N |
|---|---|
| Withdrawal force | ≥15 N |
| Mating cycles | ≥750 |
| Degree of protection acc. to IEC 60529 | IP65 IP67 |
| Cable diameter | 4.9 mm |
| Test voltage U _{r.m.s.} | 0.5 kV (contact-contact) 0.5 kV (contact-ground) |
| Impedance | 90 Ω ±15 % |
| Material properties | |
| Material (insert) | Liquid crystal polymer (LCP) |
| Material (contacts) | Copper alloy |
| Surface (contacts) | Sn over Ni Termination side Au over Ni Mating side |
| Material (cable) | PVC |
| Colour (cable) | Black |
| Material (overmoulding) | Polyamide (PA) |
| Colour (overmoulding) | Black |
| Material flammability class acc. to UL 94 | V-0 |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | e |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Naphthalene |
| Specifications and approvals | |
| Specifications | IEC 61076-3-106 Variant 4 (V4) |
| Commercial data | |
| Packaging size | 1 |
| Net weight | 89 g |
| | |

Page 2 / 3 | Creation date 2024-03-21 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Commercial data

| Country of origin | Malaysia |
|--------------------------------|--|
| European customs tariff number | 85444290 |
| GTIN | 5713140262720 |
| ETIM | EC002599 |
| eCl@ss | 27060390 Ready-made data cable (unspecified) |

Page 3 / 3 | Creation date 2024-03-21 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany

Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09454451912 9454451912