

HPP V4 / V14 Signal PFT insert 10-pole



| Part number | 09 45 545 9010 |
|--------------------|--|
| Specification | HPP V4 / V14 Signal PFT insert 10-pole |
| HARTING eCatalogue | https://b2b.harting.com/09455459010 |

Image is for illustration purposes only. Please refer to product description.

Identification

| Category | Connectors |
|----------------|-----------------------------|
| Series | HARTING PushPull (V4) |
| Identification | Signal |
| Element | Inserts |
| Specification | for panel feed through HIFF |

Version

| Termination method | Crimp termination |
|--------------------|--|
| Shielding | Fully shielded, 360° shielding contact |
| Number of contacts | 10 |
| Pack contents | incl. male insert |

Technical characteristics

| Conductor cross-section | 0.13 0.82 mm² |
|------------------------------------|---------------|
| Conductor cross-section | AWG 26 AWG 18 |
| Wire outer diameter | ≤2.1 mm |
| | 2.4 mm |
| Contact spacing (termination side) | 3 mm |
| | 2.4 mm |
| Contact spacing (mating side) | 3 mm |
| Rated current | 5 A |
| Rated voltage | 50 V |
| Rated impulse voltage | 1.5 kV |
| Pollution degree | 3 |
| | |



Technical characteristics

| Clearance distance | ≥1.4 mm |
|----------------------------------|--|
| Creepage distance | ≥1.4 mm |
| Insulation resistance | >10 ⁹ Ω |
| Contact resistance | ≤10 mΩ |
| Limiting temperature | -40 +85 °C |
| Insertion force | 50 N |
| Withdrawal force | 50 N |
| Mating cycles | ≥500 |
| Test voltage U _{r.m.s.} | 1.5 kV (contact-contact) 1.5 kV (contact-ground) |
| Isolation group | I (600 ≤ CTI) |

Material properties

| Material (contacts) | Copper alloy |
|--------------------------------------|---|
| Surface (contacts) | Noble metal over Ni Mating side Noble metal over Ni Termination side |
| RoHS | compliant |
| ELV status | compliant |
| China RoHS | е |
| REACH Annex XVII substances | Not contained |
| REACH ANNEX XIV substances | Not contained |
| REACH SVHC substances | Not contained |
| California Proposition 65 substances | Yes |
| California Proposition 65 substances | Lead Nickel |

Specifications and approvals

| Specifications | IEC 61076-3-106 Variant 4 (V4) |
|----------------|-----------------------------------|
| UL / CSA | UL 1977 ECBT2.E102079 |
| | CSA-C22.2 No. 182.3 ECBT8.E102079 |
| Approvals | DNV GL |
| PROFINET | Yes |

Commercial data

| Packaging size | 1 | | |
|----------------|---|--|--|
|----------------|---|--|--|



Commercial data

| Net weight | 17 g |
|--------------------------------|---|
| Country of origin | Germany |
| European customs tariff number | 85366990 |
| GTIN | 5713140061453 |
| ETIM | EC000438 |
| eCl@ss | 27440205 Contact insert for industrial connectors |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09455459010