

# MIN D MA 50p crimp terminal with 4-40 UNC



| Part number        | 09 67 050 5602                           |
|--------------------|--|
| Specification      | MIN D MA 50p crimp terminal with4-40 UNC |
| HARTING eCatalogue | https://b2b.harting.com/09670505602      |

Image is for illustration purposes only. Please refer to product description.

### Version

| Termination method | Crimp termination                  |
|--------------------|------------------------------------|
| Gender             | Male                               |
| Size               | D-Sub 5                            |
| Connection type    | PCB to cable                       |
|                    | Cable to cable                     |
| Number of contacts | 50                                 |
| Locking type       | Fixing flange with thread 4-40 UNC |

#### Technical characteristics

| 1 Commodi Charactoriotico        |                           |
|----------------------------------|---------------------------|
| Conductor cross-section          | 0.09 0.82 mm²             |
| Conductor cross-section          | AWG 28 AWG 18             |
| Clearance distance               | ≥1 mm                     |
| Creepage distance                | ≥1 mm                     |
| Insulation resistance            | >10 <sup>10</sup> Ω       |
| Tightening torque                | ≤0.6 Nm Female screw lock |
| Limiting temperature             | -55 +125 °C               |
| Insertion force                  | ≤167 N                    |
| Withdrawal force                 | ≥14.5 N<br>≤111 N         |
| Test voltage U <sub>r.m.s.</sub> | 1 kV                      |
| Hot plugging                     | No                        |



## Material properties

| Material (insert)                         | Thermoplastic resin, glass-fibre filled (PBTP) Shell: Plated steel   |
|---|--|
| Colour (insert)                           | Black  |
| Material (contacts)                       | Copper alloy   |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption   |
| RoHS exemptions                           | 6(a) / $6(a)$ -I: Lead as an alloying element in steel for machining purposes and in galvanised steel containing up to 0,35 % lead by weight / Lead as an alloying element in steel for machining purposes containing up to 0,35 % lead by weight and in batch hot dip galvanised steel components containing up to 0,2 % lead by weight |
| ELV status                                | compliant with exemption   |
| China RoHS                                | 50   |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | Lead   |
| ECHA SCIP number                          | ecef7555-f643-4ceb-a337-fc54762297f1   |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Antimony trioxide Lead Nickel  |
|   |  |

## Specifications and approvals

| Specifications | DIN 41652<br>IEC 60807-3 |
|----------------|--------------------------|
| Specification  | CECC 75301-802           |
| UL / CSA       | UL 1977 ECBT2.E102079    |

#### Commercial data

| Packaging size                 | 25                     |
|--------------------------------|------------------------|
| Net weight                     | 13.303 g               |
| Country of origin              | Germany                |
| European customs tariff number | 85389099               |
| GTIN                           | 5713140093744          |
| eCl@ss                         | 27440214 D-Sub coupler |

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

**HARTING**:

09670505602 9670505602