

## D SUB MIXED MA SOLDER CRIMP COAX 50 OHMS



	Part number	09 69 281 5143
	Specification	D SUB MIXED MA SOLDER CRIMP COAX 50 OHMS
	HARTING eCatalogue	https://b2b.harting.com/09692815143

Image is for illustration purposes only. Please refer to product description.

#### Identification

Category	Contacts			
Series	D-Sub			
Identification	Mixed			
Type of contact	Coaxial contact			
Description of the contact	Straight for cables RG 58 CU, 141 AU			
Features	Outer ferrule: crimp in tool cavity A			
Version				
Termination method	Solder/crimp termination			
Gender	Male			
Manufacturing process	Turned contacts			
Technical characteristics				
Rated current	≤2 A			
Rated voltage	250 V			
Insulation resistance	>10 <sup>9</sup> Ω			
Contact resistance	2.7 m $\Omega$ for inner contact die 2.7 m $\Omega$ for outer ferrule			
Impedance	50 Ω			
Stripping length	3 mm for inner contact die 5 mm Shielding 9.5 mm cable jacket			
Limiting temperature	-55 +135 °C			

Page 1 / 3 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



### Technical characteristics

Insertion force	≤7 N		
Withdrawal force	≤7 N		
Performance level	NM 30 (S4) 1		
Mating cycles	≥500		
Test voltage U <sub>r.m.s.</sub>	0.75 kV @ 50 Hz		
Frequency	0 2 GHz		
Material properties			
Material (contacts)	PBFE / PBTP / PI		
Surface (contacts)	Noble metal over Ni		
Layer thickness	≥0.76 µm		
Layer thickness	≥30 µinch		
Material (locking)	Copper alloy		
RoHS	compliant with exemption		
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight		
ELV status	compliant with exemption		
China RoHS	50		
REACH Annex XVII substances	Not contained		
REACH ANNEX XIV substances	Not contained		
REACH SVHC substances	Yes		
REACH SVHC substances	Lead		
ECHA SCIP number	ecef7555-f643-4ceb-a337-fc54762297f1		
California Proposition 65 substances	Yes		
California Proposition 65 substances	Lead Nickel		

#### Commercial data

Packaging size	20
Net weight	2.6 g
Country of origin	Czechia
European customs tariff number	85366990
GTIN	5713140098947
ETIM	EC000796

Page 2 / 3 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com



Commercial data

eCl@ss

27440204 Contact for industrial connectors

Page 3 / 3 | Creation date 2024-02-10 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electronics GmbH | Marienwerderstraße 3 | 32339 Espelkamp | Germany Phone +49 5772 47-97200 | electronics@HARTING.com | www.HARTING.com

# **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09692815143