

1		2		3		4		5		6		7		8																																																																																																																																																																																																																																																																																																																																																																																																												
A	har-flexicon terminal block vertical, push-in RoHS compliant															Cable connection <table><tr><td>Type</td><td colspan="4">har-flexicon 5.0TWPV</td><td colspan="4">har-flexicon 5.0 TTPV</td></tr><tr><td>Part numbers</td><td colspan="4">1403xx16101xxx</td><td colspan="4">1402xx16101xxx</td></tr><tr><td>Conductor size AWG max</td><td colspan="4">12 AWG</td><td colspan="4"></td></tr><tr><td>Conductor size AWG min</td><td colspan="4">30 AWG</td><td colspan="4"></td></tr><tr><td>Conductor size solid max</td><td colspan="4">2,5 mm²</td><td colspan="4"></td></tr><tr><td>Conductor size solid min</td><td colspan="4">0,2 mm²</td><td colspan="4"></td></tr><tr><td>Conductor size stranded max</td><td colspan="4">2,5 mm²</td><td colspan="4"></td></tr><tr><td>Conductor size stranded min</td><td colspan="4">0,2 mm²</td><td colspan="4"></td></tr><tr><td>Conductor size stranded for end sleeve</td><td colspan="4">n.a.</td><td colspan="4"></td></tr><tr><td>Stripping length max</td><td colspan="4">10 mm</td><td colspan="4"></td></tr><tr><td>Stripping length min</td><td colspan="4">10 mm</td><td colspan="4"></td></tr></table> Packging unit type har-flexicon 5.00 TWPV <table><tr><th>Type of packaging</th><th>No. of poles (xx)</th><th>Quantity</th><th>MOQ</th><th>Index (xxx)</th><th>Remark</th></tr><tr><td>box</td><td>2</td><td>300</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>3</td><td>200</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>4 - 5</td><td>150</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>6 - 12</td><td>100</td><td>1</td><td>000</td><td></td></tr><tr><td>box</td><td>13 - 18</td><td>50</td><td>1</td><td>000</td><td></td></tr></table> type har-flexicon 5.00 TTPV <table><tr><th>Type of packaging</th><th>No. of poles (xx)</th><th>Quantity</th><th>MOQ</th><th>Index (xxx)</th><th>Remark</th></tr><tr><td>box</td><td>2 - 3</td><td>100</td><td>100</td><td>000</td><td></td></tr><tr><td>box</td><td>4</td><td>75</td><td>75</td><td>000</td><td></td></tr></table>															Type	har-flexicon 5.0TWPV				har-flexicon 5.0 TTPV				Part numbers	1403xx16101xxx				1402xx16101xxx				Conductor size AWG max	12 AWG								Conductor size AWG min	30 AWG								Conductor size solid max	2,5 mm ²								Conductor size solid min	0,2 mm ²								Conductor size stranded max	2,5 mm ²								Conductor size stranded min	0,2 mm ²								Conductor size stranded for end sleeve	n.a.								Stripping length max	10 mm								Stripping length min	10 mm								Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark	box	2	300	1	000		box	3	200	1	000		box	4 - 5	150	1	000		box	6 - 12	100	1	000		box	13 - 18	50	1	000		Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark	box	2 - 3	100	100	000		box	4	75	75	000																																																																																																																																																																																																																																				
	Type	har-flexicon 5.0TWPV				har-flexicon 5.0 TTPV																																																																																																																																																																																																																																																																																																																																																																																																																				
Part numbers	1403xx16101xxx				1402xx16101xxx																																																																																																																																																																																																																																																																																																																																																																																																																					
Conductor size AWG max	12 AWG																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size AWG min	30 AWG																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size solid max	2,5 mm ²																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size solid min	0,2 mm ²																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size stranded max	2,5 mm ²																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size stranded min	0,2 mm ²																																																																																																																																																																																																																																																																																																																																																																																																																									
Conductor size stranded for end sleeve	n.a.																																																																																																																																																																																																																																																																																																																																																																																																																									
Stripping length max	10 mm																																																																																																																																																																																																																																																																																																																																																																																																																									
Stripping length min	10 mm																																																																																																																																																																																																																																																																																																																																																																																																																									
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark																																																																																																																																																																																																																																																																																																																																																																																																																					
box	2	300	1	000																																																																																																																																																																																																																																																																																																																																																																																																																						
box	3	200	1	000																																																																																																																																																																																																																																																																																																																																																																																																																						
box	4 - 5	150	1	000																																																																																																																																																																																																																																																																																																																																																																																																																						
box	6 - 12	100	1	000																																																																																																																																																																																																																																																																																																																																																																																																																						
box	13 - 18	50	1	000																																																																																																																																																																																																																																																																																																																																																																																																																						
Type of packaging	No. of poles (xx)	Quantity	MOQ	Index (xxx)	Remark																																																																																																																																																																																																																																																																																																																																																																																																																					
box	2 - 3	100	100	000																																																																																																																																																																																																																																																																																																																																																																																																																						
box	4	75	75	000																																																																																																																																																																																																																																																																																																																																																																																																																						
B	General information <table><tr><td colspan="6">Design</td><td colspan="6">PCB Terminal Block</td><td colspan="3"></td></tr><tr><td colspan="2">Type</td><td colspan="3">har-flexicon 5.0 TWPV</td><td colspan="3">har-flexicon 5.0 TTPV</td><td colspan="3"></td><td colspan="3"></td><td rowspan="18">B</td></tr><tr><td colspan="2">Part numbers</td><td colspan="3">1403xx16101xxx</td><td colspan="3">1402xx16101xxx</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Contact pitch</td><td colspan="3">5 mm</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">No. of contacts</td><td colspan="3">2 - 18 poles</td><td colspan="3">2 - 4 poles</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Rated surge voltage (II/2)</td><td colspan="3">4 kV</td><td colspan="3"></td><td colspan="3">(overvoltage cat. II / pollution degree 2)</td><td colspan="3"></td></tr><tr><td colspan="2">Rated surge voltage (III/2)</td><td colspan="3">4 kV</td><td colspan="3"></td><td colspan="3">(overvoltage cat. III / pollution degree 2)</td><td colspan="3"></td></tr><tr><td colspan="2">Rated surge voltage (III/3)</td><td colspan="3">4 kV</td><td colspan="3"></td><td colspan="3">(overvoltage cat. III / pollution degree 3)</td><td colspan="3"></td></tr><tr><td colspan="2">Rated Voltage</td><td colspan="3">300 V</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Rated voltage (II/2)</td><td colspan="3">600 V</td><td colspan="3"></td><td colspan="3">(overvoltage cat. II / pollution degree 2)</td><td colspan="3"></td></tr><tr><td colspan="2">Rated voltage (III/2)</td><td colspan="3">300 V</td><td colspan="3"></td><td colspan="3">(overvoltage cat. III / pollution degree 2)</td><td colspan="3"></td></tr><tr><td colspan="2">Rated voltage (III/3):</td><td colspan="3">300 V</td><td colspan="3"></td><td colspan="3">(overvoltage cat. III / pollution degree 3)</td><td colspan="3"></td></tr><tr><td colspan="2">Working current</td><td colspan="3">12 A</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Usegroup B, rated voltage / current</td><td colspan="3">300 V / 12 A</td><td colspan="3">300 V / 12 A</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Usegroup C, rated voltage / current</td><td colspan="3">- / -</td><td colspan="3">- / -</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Usegroup D, rated voltage / current</td><td colspan="3">300 V / 12 A</td><td colspan="3">300 V / 12 A</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Contact resistance</td><td colspan="3">max. 15 mOhm</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Insulation resistance</td><td colspan="3">min. 10⁹ Ohm (500 V DC)</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Temperature range</td><td colspan="3">-40°C ... +110°C</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Termination technology</td><td colspan="3">wave solder</td><td colspan="3">THR / SMC reflow</td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Insertion force</td><td colspan="3">n.a</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Withdrawal force</td><td colspan="3">n.a</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Hot plugging</td><td colspan="3">No</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Mechanical Shock IEC 61373 (05/10)</td><td colspan="3">5g/30ms, each 3 shocks, 3 axis/two directions. No contact disturbance > 1µs</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">Random Vibration IEC 61373 (05/10)</td><td colspan="3">class1 cat B, ASD level 0,964(m/s²)²/Hz, RMS value 5,72m/s²; 3x5h. No contact disturbance > 1µs</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">RoHS - compliant</td><td colspan="3">Yes</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr><tr><td colspan="2">UL file</td><td colspan="3">E314677</td><td colspan="3"></td><td colspan="3"></td><td colspan="3"></td></tr></table>															Design						PCB Terminal Block									Type		har-flexicon 5.0 TWPV			har-flexicon 5.0 TTPV									B	Part numbers		1403xx16101xxx			1402xx16101xxx									Contact pitch		5 mm												No. of contacts		2 - 18 poles			2 - 4 poles									Rated surge voltage (II/2)		4 kV						(overvoltage cat. II / pollution degree 2)						Rated surge voltage (III/2)		4 kV						(overvoltage cat. III / pollution degree 2)						Rated surge voltage (III/3)		4 kV						(overvoltage cat. III / pollution degree 3)						Rated Voltage		300 V												Rated voltage (II/2)		600 V						(overvoltage cat. II / pollution degree 2)						Rated voltage (III/2)		300 V						(overvoltage cat. III / pollution degree 2)						Rated voltage (III/3):		300 V						(overvoltage cat. III / pollution degree 3)						Working current		12 A												Usegroup B, rated voltage / current		300 V / 12 A			300 V / 12 A									Usegroup C, rated voltage / current		- / -			- / -									Usegroup D, rated voltage / current		300 V / 12 A			300 V / 12 A									Contact resistance		max. 15 mOhm												Insulation resistance		min. 10 ⁹ Ohm (500 V DC)												Temperature range		-40°C ... +110°C												Termination technology		wave solder			THR / SMC reflow									Insertion force		n.a												Withdrawal force		n.a												Hot plugging		No												Mechanical Shock IEC 61373 (05/10)		5g/30ms, each 3 shocks, 3 axis/two directions. No contact disturbance > 1µs												Random Vibration IEC 61373 (05/10)		class1 cat B, ASD level 0,964(m/s ²) ² /Hz, RMS value 5,72m/s ² ; 3x5h. No contact disturbance > 1µs												RoHS - compliant		Yes												UL file		E314677												1403xx16101xxx														
	Design						PCB Terminal Block																																																																																																																																																																																																																																																																																																																																																																																																																			
Type		har-flexicon 5.0 TWPV			har-flexicon 5.0 TTPV									B																																																																																																																																																																																																																																																																																																																																																																																																												
Part numbers		1403xx16101xxx			1402xx16101xxx																																																																																																																																																																																																																																																																																																																																																																																																																					
Contact pitch		5 mm																																																																																																																																																																																																																																																																																																																																																																																																																								
No. of contacts		2 - 18 poles			2 - 4 poles																																																																																																																																																																																																																																																																																																																																																																																																																					
Rated surge voltage (II/2)		4 kV						(overvoltage cat. II / pollution degree 2)																																																																																																																																																																																																																																																																																																																																																																																																																		
Rated surge voltage (III/2)		4 kV						(overvoltage cat. III / pollution degree 2)																																																																																																																																																																																																																																																																																																																																																																																																																		
Rated surge voltage (III/3)		4 kV						(overvoltage cat. III / pollution degree 3)																																																																																																																																																																																																																																																																																																																																																																																																																		
Rated Voltage		300 V																																																																																																																																																																																																																																																																																																																																																																																																																								
Rated voltage (II/2)		600 V						(overvoltage cat. II / pollution degree 2)																																																																																																																																																																																																																																																																																																																																																																																																																		
Rated voltage (III/2)		300 V						(overvoltage cat. III / pollution degree 2)																																																																																																																																																																																																																																																																																																																																																																																																																		
Rated voltage (III/3):		300 V						(overvoltage cat. III / pollution degree 3)																																																																																																																																																																																																																																																																																																																																																																																																																		
Working current		12 A																																																																																																																																																																																																																																																																																																																																																																																																																								
Usegroup B, rated voltage / current		300 V / 12 A			300 V / 12 A																																																																																																																																																																																																																																																																																																																																																																																																																					
Usegroup C, rated voltage / current		- / -			- / -																																																																																																																																																																																																																																																																																																																																																																																																																					
Usegroup D, rated voltage / current		300 V / 12 A			300 V / 12 A																																																																																																																																																																																																																																																																																																																																																																																																																					
Contact resistance		max. 15 mOhm																																																																																																																																																																																																																																																																																																																																																																																																																								
Insulation resistance		min. 10 ⁹ Ohm (500 V DC)																																																																																																																																																																																																																																																																																																																																																																																																																								
Temperature range		-40°C ... +110°C																																																																																																																																																																																																																																																																																																																																																																																																																								
Termination technology		wave solder			THR / SMC reflow																																																																																																																																																																																																																																																																																																																																																																																																																					
Insertion force		n.a																																																																																																																																																																																																																																																																																																																																																																																																																								
Withdrawal force		n.a																																																																																																																																																																																																																																																																																																																																																																																																																								
Hot plugging		No																																																																																																																																																																																																																																																																																																																																																																																																																								
Mechanical Shock IEC 61373 (05/10)		5g/30ms, each 3 shocks, 3 axis/two directions. No contact disturbance > 1µs																																																																																																																																																																																																																																																																																																																																																																																																																								
Random Vibration IEC 61373 (05/10)		class1 cat B, ASD level 0,964(m/s ²) ² /Hz, RMS value 5,72m/s ² ; 3x5h. No contact disturbance > 1µs																																																																																																																																																																																																																																																																																																																																																																																																																								
RoHS - compliant		Yes																																																																																																																																																																																																																																																																																																																																																																																																																								
UL file		E314677																																																																																																																																																																																																																																																																																																																																																																																																																								
C	Isulator material <table><tr><td colspan="2">har-flexicon 5.0 TWPV</td><td colspan="2">har-flexicon 5.0 TTPV</td></tr><tr><td>Material</td><td>PA</td><td colspan="2">PA / PPA</td></tr><tr><td>Color</td><td>green</td><td colspan="2">black / orange</td></tr><tr><td>UL classification</td><td colspan="3">UL 94-V0</td></tr><tr><td>Material group acc. to IEC 60664-1</td><td colspan="3">I (CTI > 600)</td></tr></table> Contact material <table><tr><td colspan="2">termination zone</td><td colspan="2">contact zone</td></tr><tr><td colspan="2"></td><td colspan="2"></td></tr><tr><td>Contact material</td><td>Copper alloy</td><td>har-flexicon 5.0 TWPV</td><td>har-flexicon 5.0 TTPV</td></tr><tr><td>Plating</td><td>Sn</td><td>Copper alloy</td><td>1.4310 / AISI 301</td></tr><tr><td></td><td></td><td>Ni</td><td>-</td></tr></table>															har-flexicon 5.0 TWPV		har-flexicon 5.0 TTPV		Material	PA	PA / PPA		Color	green	black / orange		UL classification	UL 94-V0			Material group acc. to IEC 60664-1	I (CTI > 600)			termination zone		contact zone						Contact material	Copper alloy	har-flexicon 5.0 TWPV	har-flexicon 5.0 TTPV	Plating	Sn	Copper alloy	1.4310 / AISI 301			Ni	-	Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²																																																																																																																																																																																																																																																																																																																																																																		
	har-flexicon 5.0 TWPV		har-flexicon 5.0 TTPV																																																																																																																																																																																																																																																																																																																																																																																																																							
Material	PA	PA / PPA																																																																																																																																																																																																																																																																																																																																																																																																																								
Color	green	black / orange																																																																																																																																																																																																																																																																																																																																																																																																																								
UL classification	UL 94-V0																																																																																																																																																																																																																																																																																																																																																																																																																									
Material group acc. to IEC 60664-1	I (CTI > 600)																																																																																																																																																																																																																																																																																																																																																																																																																									
termination zone		contact zone																																																																																																																																																																																																																																																																																																																																																																																																																								
Contact material	Copper alloy	har-flexicon 5.0 TWPV	har-flexicon 5.0 TTPV																																																																																																																																																																																																																																																																																																																																																																																																																							
Plating	Sn	Copper alloy	1.4310 / AISI 301																																																																																																																																																																																																																																																																																																																																																																																																																							
		Ni	-																																																																																																																																																																																																																																																																																																																																																																																																																							
D	Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²															Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²																																																																																																																																																																																																																																																																																																																																																																																																										
	E	Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²															Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²																																																																																																																																																																																																																																																																																																																																																																																																									
F		Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²															Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²																																																																																																																																																																																																																																																																																																																																																																																																									
	Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²															Derating The current carrying capacity is limited by maximum temperature of materials for inserts and contacts including terminals. The current capacity curve is valid for continuous, non interrupted current loaded contacts of connectors when simultaneous power on all contacts is given, without exceeding the maximum temperature. Control and test procedures according to DIN IEC 60512-5 Electrical Load [A] Temperature [°C] Reduction Factor 0,8 No. of Position 3 Derating Curve, 2.5mm² Derating Curve, 1.5mm² Derating Curve, 1mm² Derating Curve, 0.75mm²																																																																																																																																																																																																																																																																																																																																																																																																										

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

[14030616101000](#) [14031016101000](#) [14030316101000](#) [14030816101000](#) [14030216101000](#) [14030416101000](#)
[14031816101000](#) [14031516101000](#) [14031616101000](#) [14030516101000](#) [14030716101000](#) [14031116101000](#)
[14030916101000](#) [14031216101000](#) [14020316101000](#) [14020416101000](#) [14020216101000](#)