

LC connector single mode 3mm



Part number	20 10 125 8220
Specification	LC connector single mode 3mm
HARTING eCatalogue	https://b2b.harting.com/20101258220

Image is for illustration purposes only. Please refer to product description.

Identification	
Category	Contacts
Type of contact	LC contact
Description of the contact	Singlemode for cable diameter up to 3 mm
Version	
Manufacturing process	Turned contacts
Technical characteristics	
Limiting temperature	-40 +75 °C
Material properties	
RoHS	compliant with exemption
	compliant with exemption 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight
RoHS	6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with
RoHS RoHS exemptions	6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight
RoHS RoHS exemptions ELV status	6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight compliant with exemption
RoHS RoHS exemptions ELV status China RoHS	 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight compliant with exemption
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances	 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight compliant with exemption 50 Not contained
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances REACH ANNEX XIV substances	 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight compliant with exemption 50 Not contained Not contained
RoHS RoHS exemptions ELV status China RoHS REACH Annex XVII substances REACH SVHC substances REACH SVHC substances	 6(b) / 6(b)-II: Lead as an alloying element in aluminium containing up to 0,4 % lead by weight / Lead as an alloying element in aluminium for machining purposes with a lead content up to 0,4 % by weight compliant with exemption 50 Not contained Not contained Yes

Page 1 / 2 | Creation date 2024-01-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



Material properties

California Proposition 65 substances	Antimony trioxide Lead Nickel Naphthalene
Commercial data	
Packaging size	2
Net weight	1.06 g
Country of origin	Germany
European customs tariff number	85367000
GTIN	5713140133648
ETIM	EC000796
eCl@ss	27440204 Contact for industrial connectors

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

20101258220