

## DIN 41626 male connector for 230 Åm HCS



Image is for illustration purposes only. Please refer to product description.

Part number	20 10 230 4211
Specification	DIN 41626 male connector for 230 Åm HCS
HARTING eCatalogue	<a href="https://b2b.harting.com/20102304211">https://b2b.harting.com/20102304211</a>

### Identification

Category	Contacts
Series	DIN 41626
Type of contact	FO contact
Description of the contact	for SI fibre (HCS®) 200/230 µm

### Version

Gender	Male
Manufacturing process	Turned contacts

### Material properties

RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead



**Pushing Performance**  
Since 1945

## Commercial data

Packaging size	1
Net weight	3 g
Country of origin	Germany
European customs tariff number	85367000
GTIN	5713140133686
eCl@ss	27440204 Contact for industrial connectors

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[20102304211](#)