

09 66 323 6801	M3	2					Dat.	Name	 All Dim. in mm Orig. Size DIN A 4	D-Sub male standard 25 poles with solder pins and nuts	Maßstab/ Scale 1,5:1
09 66 323 7801	M3	3				Detail.	23-NOV-01	JB			
09 66 323 5801	M3	0,76 µm Au				Insp.					
09 66 323 6802	4-40 UNC	2				Stand.					
09 66 323 7802	4-40 UNC	3				HARTING EURL F-95972 Paris				TB 09 66 323 X80X	Blatt/ Page 1 /
09 66 323 5802	4-40 UNC	0,76 µm Au	29733	23-NOV-01	JB						
Part number	nut thread	Performance level	Mod.	Dat.	Name					Sub.	

09 66 323 6801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 323 5802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 323 5801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats

2D files

Typenblatt

Typenblatt

09 66 323 6802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 323 7801
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 323 7802
D-Sub - S PCB connector

Other applications

gender	male connector, right angled
Termination	Turned solder pins
shell	tinned metal shell with dimples
Number of contacts	25 way
Row pitch	Row separation 2.84 mm
Board fixing	without snap-in-clips
Grounding	without grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09663235801](#)