

09 66 211 6501
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 211 5502
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 211 5501
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats
2D files

Typenblatt

Typenblatt

09 66 211 6502
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 211 7501
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 211 7502
D-Sub - S PCB connector

Other applications

gender	female connector, straight
Termination	Stamped solder pins
shell	tinned metal shell
Number of contacts	15 way
Board fixing	without grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[HARTING:](#)

[09662115502](#)