

09 66 152 5616
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 5615
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level S4
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.



Data sheets are available in following formats
2D files

Typenblatt

Typenblatt

09 66 152 6615
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 6616
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level 2
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 7615
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	M 3
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

09 66 152 7616
D-Sub - S PCB connector

Other applications

gender	female connector, right angled
Termination	Stamped solder pins - low profile
shell	tinned metal shell
Number of contacts	9 way
Row pitch	Row separation 2.54 mm
Board fixing	with grounding board locks
flange	UNC4-40
Performance level	Performance level 3
Material	PBTP

Note: Obligatory information about HARTING products can be obtained exclusively from the data sheets.

Inquiry

The data sheet is up to date

2D files

PDF

DXF

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

HARTING:

09661525615 09661525616