PRODUCT DATA DRAWING

MATERIAL:

BODIES,	
COUPLING NUT:	STAINLESS STEEL PER AMS-5640,
	ALLOY UNS S30300, TYPE 1

LOCK RINGS, CONTACTS: BERYLLIUM COPPER PER ASTM B196, ALLOY No. UNS C17300, TD04

SLEEVE: BRASS PER ASTM B16, ALLOY UNS No. C36000

BELLOWS: ELECTRO-DEPOSITED GOLD OVER NICKEL

INSULATORS: PTFE PER ASTM D1710, TYPE I, GRADE 1, CLASS B

GASKETS: SILICONE RUBBER PER A-A-59588, CLASS 2B, GRADE 50/60

RESISTOR ELEMENTS: ALUMINA SUBSTRATE WITH TANTALUM NITRIDE RESISTOR

FINISH:

BODIES, COUPLING NUT: PASSIVATED PER AMS-2700, TYPE 2

2 IN-LBS

CONTACTS, SLEEVE: GOLD PER ASTM B488, TYPE II, CODE C, CLASS 1.27; OVER NICKEL PER AMS-QQ-N-290, CLASS 1, .00005" MIN.

PERFORMANCE:

IMPEDANCE: 50 OHMS FREQ. RANGE: DC TO 18.0 GHz VSWR: SEE TABLE 1 **OPERATING TEMP.:** -55°C TO +125°C 2 WATT (POWER INPUT DERATED LINEARLY AVG. POWER: FROM 25°C TO 0.5 WATTS AT 125°C) 500 WATTS (PEAK POWER FOR A DÚTY CYCLE PEAK POWER: OF 5X10⁻⁴ MÀXIMUM PULSE DURATION OF 5 MICROSECONDS) ENGAGEMENT/


DISENGAGEMENT:

.312[7.92] HEX Ø.298[7.56] (0.298[7.56]) (1/4-36 UNS-2A) .250 [6.35] ACROSS 2 FLATS

TABLE 1								
dB VALUE	ATTENUATION		VSWR					
UD VALUE	ACCURACY	DC-2 GHz	2-4 GHz	4-8 GHz	8-12.4 GHz	12.4-18 GHz	DIM.	
0 dB	+0 /-0.3 dB						.870	
0.5-6.5 dB	±0.3 dB						.870	
7-8.5 dB	±0.4 dB						.870	
9-14.5 dB	±0.5 dB						.870	
15-20 dB	±0.6 dB	1.10:1	1.15:1	1.20:1	1.25:1	1.35:1	.870	
21-29 dB	±1.0 dB						1.040	
30-39 dB	±1.0 dB]					1.040	
40 dB	±1.0 dB]					1.040	
50 dB	±2.0 dB						1.350	

MATERIAL: FINISH:	SEE NOTES SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X° ±1°0' X°X' ±15' DECIMAL: .X ±.030 .XX ±.010	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES. 1005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63. MIL-STD-10. 6) DIA'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN 005 T.I.R. 7) REMOVE ALL BURRS			Microwave, Centrepark West Drive, Suite Vest Palm Beach, FL 33409	
SURFACE AR	^{REA:} N/A PROPRIETARY	.XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994			NS AND TOLERANCES 6) DIA.'S ON COMMON CENTERS TO BE CONCENTRIC SMA PLUG -		LUG TO JACK M JATOR DC TO 18
	ATION CONTAINED IN THIS DRAWING	THIRD ANGLE PROJECTION	DRAWN:	FED 03/07/11			
ANY REPROD	PROPERTY OF SV MICROWAVE, INC. DUCTION IN PART OR AS A WHOLE E WRITTEN PERMISSION OF		CHECKED:	PJS 03/07/11	B SIZE CAGE CODE	SF0929-62	200-XXX
	VE, INC IS PROHIBITED.	Ψ	APPROVED:	PJS 03/07/11	SCALE: 4:1		SHEET 1 OF 2

REVISION HISTORY					
REV	DESCRIPTION	DATE	APPROVED		
-	DCN 38051	03/11	PJS		



PRODUCT DATA DRAWING

MAY VARY FROM 1 CHARACTER TO 3 CHARACTERS

dB VALUE TO "XXX" NUMBER CHART

dB VALUE	"XXX" NUMBER
10.5	105
11	11
11.5	115
12	12
12.5	125
13	13
13.5	135
14	14
14.5	145
15	15
15.5	155
16	16
16.5	165
17	17
17.5	175
18	18
18.5	185
19	19
19.5	195
20	20
21	21

dB VALUE	"XXX" NUMBER
22	22
23	23
24	24
25	25
26	26
27	27
28	28
29	29
30	30
31	31
32	32
33	33
34	34
35	35
36	36
37	37
38	38
39	39
40	40
50	50

MATERIAL: FINISH:	SEE NOTES SEE NOTES	DIMENSIONS ARE IN INCHES TOLERANCES: FRACTIONAL: ±1/64 ANGULAR: X* ±1°0' X*X' ±15' DECIMAL: .X ±.030	UNLESS OTHERWISE SPECIFIED 1) ALL DIMENSIONS ARE IN INCHES [MILLIMETERS] 2) ALL DIMENSIONS ARE AFTER PLATING. 3) BREAK CORNERS & EDGES. 005 R. MAX. 4) CHAM. 1ST & LAST THREADS. 5) SURFACE ROUGHNESS 63.MIL-STD-10. 6) DIA 'S ON COMMON CENTERS TO BE CONCENTRIC WITHIN T.I.R. 7) REMOVE ALL BURRS		2400 0	Microwave, Centrepark West Drive, Suite Vest Palm Beach, FL 33409	
SURFACE AR		.XX ±.010 .XXX ±.005 INTERPRET DIMENSIONS AND TOLERANCES PER ASME Y14.5M - 1994			TITLE: SMA PLUG TO JACK MICRO ATTENUATOR DC TO 18 GHz		
	TION CONTAINED IN THIS DRAWING	THIRD ANGLE PROJECTION	DRAWN:	FED 03/07/11	SIZE CAGE CODE		
ANY REPRODU	ROPERTY OF SV MICROWAVE, INC. JCTION IN PART OR AS A WHOLE WRITTEN PERMISSION OF		CHECKED:	PJS 03/07/11	B 95077	SF0929-62	200-XXX
	E, INC IS PROHIBITED.		APPROVED:	PJS 03/07/11	SCALE: 4:1		SHEET 2 OF 2

dB VALUE	"XXX" NUMBER
0	0
0.5	0.5
1	1
1.5	1.5
2	2
2.5	2.5
3	3
3.5	3.5
4	4
4.5	4.5
5	5
5.5	5.5
6	6
6.5	6.5
7	7
7.5	7.5
8	8
8.5	8.5
9	9
9.5	9.5
10	10

REVISION HISTORY				
REV	DESCRIPTION	DATE	APPROVED	
-	DCN 38051	03/11	PJS	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: <u>SF0929-6200-5.5</u>