	ROPRIETARY RIGHTS	<u>S</u> THIS		TAINS CON		TECHNICAL DAT	TA, INCLUDI	NG TRADE SEC	RETS, PROPR	RIETARY TO	
NOTICE OF PROPRIETARY RIGHTS THIS DOCUMENT CONTAINS CONFIDENTIAL TECHNICAL DATA, INCLUDING TRADE SECRETS, PROPRIETAR TIMES MICROWAVE SYSTEMS. DISCLOSURE OF THIS DATA IS EXPRESSLY CONDITIONED UPON YOUR ASSENT THAT ITS USE IS LIMITED TO USE WI YOUR COMPANY DNLY. ANY OTHER USE IS STRICTLY PROHIBITED WITHOUT THE PRIOR WRITTEN CONSENT OF TIMES MICROWAVE SYSTEMS.											
	SYM REVISION DESCRIPTION						DFTM	DATE	APPD	DATE	
	AI	RELE	ASED F	FOR F	PRODU	JCTION	X. A. M	6/3/11	J.D.B.	6/3/11	
	В	CHANC	ED PER	CDC :	#34607	7/36250	D.J.H.	9/24/12	J.D.B.	9/25/12	
						RECOMMENDED CABLE STRIPPING DIM'S.					
	(Ø15.1)		5.8 HEX.>		C0.3	3	- 21.1 -				
(23.25) (30.3)				5> ø9.5 1		- ¢12.4	3i]	2,2			
		 		∮Ø7.€	55		_ ø10.9 			- (ø20)	
ALL PARTS SATISFIED ROHS REQUIREMENTS											
						Impedance50 QFrequency range0~11GHz					
MATERIALS A	MATERIALS AND PLATING			UNIT: MICRO-INCHES			Voltage rating 500V(rms)				
BODY/SHELL	BRASS C3604	ALB	ALBALOY 80 MIN/COPPER			Dielectric 1000V					
				GOLD 50 MIN/NICKEL/COPPER			withstanding voltage				
INSULATOR	TEFLON MIL-P-1946	_				Contact re	esistance		<u>Center contact≤3 mΩ</u> Outer contact≤2 m Ω		
GASKET	SILICONE	RED				Insulation resistance ≥500					
FERRULE	BRASS	LOY 80 MIN/COPPER			Insertion loss		According to the cable				
SHRINK TUBING PO BLA			ALK			RF- leakage		N/A			
						VSWR			≦1.35 MAX@0-6GHz		
MECHANICAL CHARACTERISTICS Force to engage and disengage N/A						ENVIRONMENTAL CHARACTERISTICS Temperature range -55°C- +125°C					
Center contact retention force 6 lbs Min						· ·	Thermal Shock MIL-STD-202,Method 107,Con				
	Coupling torque			15 in-lbs Min		Vibration		STD-202,1 STD-202,1			
				60 lbs Min		Shock		-STD-202,N			
Durability > 500 cycles						Climatic Class IEC 60068 55/155/56					
ALI MACHINED			_ DIMENSIONS ARE IN mm SURFACES FINISH 1.6 RMS MAX.			DATE 6/3/11 TIMES MICROWAVE SYSTEMS					
USED DN: 0-4	NGLES $\pm 1^{\circ}$ FRACTIONS $\pm N/A$			APPD. J. D. E	1 3. F	OR LMR	IC MALE 400 cae	BLE			
SCALE: N/A SIZE A DO NOT SCALE DRAWING DEPT 68999 DATE 6/3/11 1 0f 1 SD3190-2671										71 🕅 B	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: TC-400-TM-RA-D