


NOTES:

1. ELECTRICAL:  
A. IMPEDANCE: 50Ω (NOMINAL)  
B. FREQUENCY RANGE: 0-6 GHz  
C. CONTACT RESISTANCE: CENTER: 20mΩ MAX.; MEASURED AT 10mA MAX. 25 mΩ MAX AFTER CYCLING  
OUTSIDE: 10mΩ MAX. 15 mΩ MAX AFTER CYCLING  
D. INSULATION RESISTANCE: 500MΩ MIN.; MEASURED AT 100 VDC.  
E. WITHSTANDIN VOLTAGE: NO LINE OR INSULATION BREAKDOWN: 200 VAC FOR 1 MIN.  
F. V.S.W.R. : 1.3 MAX. AT DC TO 3GHz, 1.4 MAX. AT 3 TO 6GHz  
G. TYPICAL INSERTION LOSS : .0022\*L\*√Frequency in GHz]±.087\*√Frequency in GHz]
2. PHYSICAL:  
A. FEMALE CONTACT HOLDING FORCE: 0.15N MIN. : MEASURED WITH A Ø0.475MM PIN GAUGE.  
B. DURABILITY: 30 CYCLES  
C. TEMPERATURE RANGE: -40°C TO +90°C.  
D. AMC CONNECTOR MATING FORCE: 15N TYPICAL  
E. AMC CONNECTOR DEMATING FORCE: 10N TYPICAL - 20N MAX  
F. AMC INTERFACE IS FULLY COMPATIBLE WITH "U.FL" SERIES PRODUCT.
3. MATERIALS AND FINISHES: (IN MICROMETERS)  
CONNECTOR BODY: PHOSPHOR BRONZE, SILVER PLATED (0.76 MIN.) OVER COPPER (1 MIN)  
CONNECTOR CENTER CONTACT: PHOSPHOR BRONZE, GOLD PLATED (0.076 MIN.) OVER NICKEL (2 MIN)  
CONNECTOR INSULATOR: HIGH TEMP PLASTIC UL 94V-0, BLACK  
CABLE JACKET: FEP  
CABLE DIELECTRIC: FEP  
CABLE CENTER CONDUCTOR: ANNEALED COPPER WIRE STRANDED, SILVER PLATED  
CABLE OUTER CONDUCTOR: ANNEALED COPPER WIRE BRAID, TIN PLATED
4. PACKAGING:  
A. PAKCAGED IN BAGS OF 100 PIECES

THIRD ANGLE PROJ.


REVISIONS

REV	DESCRIPTION	DATE	ECO	APPR
-	RELEASE TO MFG.	-----	-----	-----
F	REDRAWN, ADDED NOTE 1G,485 AND COD, ADD ORIENTAION AND COLOR, 5.28±0.4 WAS 5.2 REF REMOVED 4±0.4, 2.41±0.2 WAS 2.68 REF	10/2/14	50005	EW





EXAMPLE SHOW :  
A-IPAC113-XXXYZ

SCALE 3.000



CABLE ASSEMBLY TOLERANCE		
OVERALL LENGTH L (mm)	STANDARD TOLERANCE (mm)	ORIENTATION TOLERANCE
35<L<100	± 4	±30°
100<L<200	± 4	±45°
200 < L 500	± 8	
500 < L 1000	± 12	
1000 < L	±1.5 %	



CUSTOMER OUTLINE DRAWING

ALL OTHER SHEETS ARE FOR INTERNAL USE ONLY

UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE:  
<0.5mm ± 0.05mm 0.5 - 6mm ±0.1mm 6 - 30mm ±0.2mm 30 - 120mm ± 0.3mm ANGLES ±1°

MATERIAL  
-

DRAWN  
SUNDE

DATE  
25-Nov-14

TITLE  
CABLE ASSY  
AMC, PLUG

Amphenol RF

www.amphenolrf.com

REFERENCE  
EAR # 1434 AND

APPROVED  
HARRY

DATE  
25-Nov-14

SCALE: 8.0:1.0 SHEET 2 OF 2

DRAWING NO. A-IPAX113-XXXYZ

CONFIGURATION LEVEL: ☐ ☐ ☐

CAD FILE

DWG SIZE  
B

REV  
F

ITEM NO. A-IPAX113-XXXYZ

PART NO. A-IPAX113-XXXYZ

NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol corp. (2) must be returned upon request; and (3) are confidential and not to be disclosed to any person other than those to whom they are given by Amphenol Corp. the furnishing of these drawings, specifications, or other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[A-1PA-113-200G2](#) [A-1PA-113-500G2](#) [A-1PA-113-070B2](#) [A-1PA-113-220B2](#)