
District AND FUNC-SEX. District AND FUNC-SEX. <thdistrict and="" func-sex.<="" th=""> District AND FUNC-SEX.<</thdistrict>				1351	03-03-XX.XX		
Base Color D Rikk	NOTES:					REV	DESC
Set 2441 Set 2441 Convert 1 all - 100, 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2441 Convert 1 all - 100, 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 2400 Set 2440 Convert 1 all - 1000 Restruct 1 Set 2400 Restruct 1 Set 24000 Set 2440 Convert 1 all - 10000 Restruct 1 Restruct 1 Restruct 1 Restruct 1 Restruct 1 Restruct 1 Restruc	1. MATERIALS AND FINISHES:			THIRD A	NGLE PROJ. 🕀 🖯	NC	
A. ΙΜΡΤΟΝΤΕ 32, ΝΗΗ ΙΜΠΑΙ Image: A Comparison of the Co	SMA RIGHT ANGLE CRIMP PLUG - P/N: 132182					В	SEE S
B. F-2TABLE A. BOATTTYN SINGLE 245/R P. SAN DO RE MARKED. SINGLE 245/R EXCOUNTING METERSING SINGLE 245/R P. SAN DO RE MARKED. SINGLE 245/R INDIA AND HOLDS/NCTSLETASALSY INDIA AND HOLDS/NCTSLETASALSY MEST SPERING TOTING INDIA AND HOLDS/NCTSLETASALSY SPERING MEST SPERING TOTING	2. ELECTRICAL:						
A. BURNETTE S. DESTITU DE MARKET AND SUPPORTAL KR. 19305-03-XX,XX, AND DATE COCE Image: Control of Market De Market	A. IMPEDANCE: 50 OHM, NOMINAL						L.
B. BAS TO 3E MARKED. AND FOLERANCE USE TABLES: Image: Control of the state of the s	3. PACKAGING:						
Image: Start Doubles							
Image: Start Doubles			I ENGTH	AND THIFRANCE (SEE	TARIES)		
TYP. (2x) SMA. RIGHT ANGLE LRIMP PLUG SMA. RIGHT ANGLE LRIMP PLUGE SMA. RIGHT ANGLE STOLE SMA. RIGHT ANGLE STOLE							
TYP. (2x) SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG MILESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: MATERIAL UNLESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: NUMERS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: UNLESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: NAMELER STRA RIGHT ANGLE DEVANCE DECIMAL MATERIAL DEVANCE DECIMAL SMA. RIGHT ANGLE							
TYP. (2x) SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG MILESS OTHERWIST SPECIFIED; TOLERANCES ARE AS FOLLOWS: MATERIAL UNLESS OTHERWIST SPECIFIED; TOLERANCES ARE AS FOLLOWS: NUMERS OTHERWIST SPECIFIED; TOLERANCES ARE AS FOLLOWS: MATERIAL DRAWN SMA. RIGHT ANGLE							
TYP. (2x) SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG DESIGN REQUIREMENTS: SMA. RIGHT ANGLE CRIMP PLUG MILESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: MATERIAL UNLESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: NUMERS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: UNLESS OTHERWIST SPECIFIED, TOLEPANCES ARE AS FOLLOWS: NAMELER STRA RIGHT ANGLE DEVANCE DECIMAL MATERIAL DEVANCE DECIMAL SMA. RIGHT ANGLE							
DESIGN REQUIREMENTS:		J DOUBLE BRAID CABLE					
 SMA RIGHT ANGLE CRIMP PLUG SMA RIGHT ANGLE CRIMP PLUG 			0				
SMA_RIGHT_ANGLE_CRIMP_PLUG ^{1135103-03-06.00} ⁻ ^{6.00} [0.152] - 135103-03-M0.25 ^{9.84} [0.250] ^{1135103-03-M0.25} ^{9.84} [0.250] 135103-03-12.00 - 12.00 [0.305] ^{1135103-03-M0.25} ^{9.84} [0.250] 135103-03-18.00 - 18.00 [0.457] ^{1135103-03-M0.25} ^{9.84} [0.250] - 135103-03-40.00 - ^{1135103-03-M0.50} ^{19.69} [0.500] - 135103-03-340.00 - ^{1135103-03-M0.75} ^{24.00} [0.610] - 135103-03-36.00 - ^{36.00} [0.914] - 135103-03-46.00 - ^{36.00} [0.914] - 135103-03-46.00 - ^{36.00} [0.127] 135103-03-46.00 - ^{40.00} [1.219] ^{40.00} [1.219] VSWR :1 MAX X CONTINUITY ^{1135103-03-M0.05 ¹¹⁰⁰ Marct AMPHENDL RF MARKETING FOR DUOTE}			PART NUMBER				
135103-03-12.00 - 12.00 [0.305] 135103-03-18.00 - 18.00 [0.457] - 135103-03-18.00 - 18.00 [0.457] - 135103-03-48.00 - 135103-03-48.00 - [0.10] - 135103-03-48.00 - 135103-03-48.00 - [0.10] - 0 135103-03-48.00 - 135103-03-48.00 - 48.00 [1.219] 0 135103-03-48.00 - 48.00 [1.219] - - CUSTO 1 VSWR :1 MAX MH-POT : SOU VRMS - <							
135103-03-18.00 - 18.00 [0,457] - 135103-03-80.00 - 24.00 [0,610] 135103-03-24.00 - 24.00 [0,610] - 135103-03-80.00 - 24.00 [0,914] - 135103-03-80.00 - 36.00 [0,914] - 135103-03-48.00 - 48.00 [1,219] - 135103-03-48.00 - 48.00 [1,219] - 135103-03-48.00 - 48.00 [1,219] - 100 [1,219] - - 100 [1,219] - VSW R :1 MAX X HI-POT : 500 VRMS - - - INS. LOSS : dBMAX O THER OTHER OTHER CUSTOC _ 2 PLACE DECIMAL ANGLES ARE AS FOLLOWS: ANGLES CONTINUELS ANGLES CONTENTION # 1 - Mar-14 SMA RIGHT ANGLES CONTENTION # 1 - Mar-14 SMA RIGHT ANGLES CONTENTION # 1 - Mar-14	SMA RIGHT ANGLE CRIMP PLUG			135103-03-M0.25			
- 135103-03-00.50 19.69 [0.500] 135103-03-24.00 - 24.00 [0.610] - 135103-03-24.00 - 24.00 [0.610] - 135103-03-00.75 29.53 [0.750] 135103-03-340.00 - - 135103-03-340.00 - 36.00 [0.914] - 135103-03-48.00 - 135103-03-48.00 - 48.00 [1.219] - 48.00 [1.219] - VSW R :1 MAX X HI-POT : 500 VRMS - - - - INS. LOSS : dBMAX OTHER OTHER OTHER - - - -				-			
135103-03-24.00 - 24.00 [0.610] - 135103-03-M0.75 29.53 [0.750] 135103-03-36.00 - 36.00 [0.914] - 135103-03-36.00 - 36.00 [0.914] - 135103-03-36.00 - 48.00 [1.219] DESIGN REQUIREMENTS:			135103-03-18.00	- 425402 02 M0 50			
- 135103-03-M0.75 29.53 [0.750] 135103-03-36.00 - 36.00 [0.914] - 135103-03-48.00 - 48.00 [1.219] - 135103-03-48.00 - 48.00 [1.219] - 135103-03-48.00 - 48.00 [1.219] - - - - 6.00 [1.219] - - - - - - - - - - - - - - - - - - - - - - -<				135103-03-M0.50			
^{135103-03-36.00} - ^{36.00} [0.914] - ^{135103-03-M1.00} ^{39.37} [1.000] [1.001] [1.01] [1.001] [1.01]				- 135103_03_M0_75			-
UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: MATERIAL UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: MATERIAL 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLESS 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLESS 4.015 (0,127 mm) ± 1° SEE NOTES SEE NOTES			135103-03-36.00	-			-
DESIGN REQUIREMENTS: X FREQUENCY : DC TO 12.4 GHz X CONTINUITY VSW R :1 MAX X HI-POT : 500 VRMS INS. LOSS : dBMAX OTHER UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: MATERIAL UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: MATERIAL 2 PLACE DECIMAL ±, 015 (0,381 mm) ±, 005 (0,127 mm) ± 1 MATERIAL SEE NOTES			-	135103-03-M1.00			_
X FREQUENCY : DC TO 12.4 GHz X CONTINUITY VSW R :1 MAX X HI-POT : 500 VRMS INS. LOSS : dBMAX OTHER OTHER UNLESS OTHERWISE SPEcified, TOLERANCES ARE AS FOLLOWS: MATERIAL L DRAWN DATE TITLE SMA RIGHT ANGLE			135103-03-48.00				_
UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° SEE NOTES CUSTO MATERIAL DRAWN DATE TITLE MOHAN 11-Mar-14 SMA RIGHT ANGL	FREQUENCY : DC TO 12.4 GHZ						
UNLESS OTHERWISE SPECIFIED, TOLERANCES ARE AS FOLLOWS: 2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ±1° SEE NOTES	VSWR :1 MAX X HI-POT : 50	DO VRMS					
2 PLACE DECIMAL 3 PLACE DECIMAL ANGLES ±.015 (0,381 mm) ±.005 (0,127 mm) ±1° SEE NOTES MOHAN 11-Mar-14 SMA RIGHT ANGL	INS. LOSS : dBMAX						
±.015 (0,381 mm) ±.005 (0,127 mm) ± 1° SEE NOTES		MATERIAL					
	±.015 (0,381 mm) ±.005 (0,127 mm) ± 1°	SEE NOTES				- 14	
IOTICE - These drawings, specifications, or other data (1) are, and remain the LNGINEER DATE IU SMA LRIMP P	NOTICE - These drawings, specifications, or other data (1) are, and remain the property of Amphenol Corp. (2) must be returned upon request; and (3) are					-14	
onfidential and not to be disclosed to any person other than those to whom they REFERENCE RU-JIO/U DUUDLL		REFERENCE				14	
other data by Amphenol Corp., or to any other person to anyone for any purpose is	other data by Amphenol Corp., or to any other person to anyone for any purpose is					-14	VARIUUS LENGIH
rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to	not to be regarded by implication or otherwise in any manner licensing, granting rights or permitting such holder or any other person to manufacture, use or sell any product, process or design, patented or otherwise, that may in any way be related to or disclosed by said drawings, specifications, or other data.						



В

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol:

<u>135103-03-06.00</u> <u>135103-03-12.00</u> <u>135103-03-36.00</u> <u>135103-03-24.00</u> <u>135103-03-M0.25</u> <u>135103-03-M0.50</u> 135103-03-M0.75 135103-03-M1.00