NOTES:		THIRD ANGLE PRC			ISIONS
			REV	DESCRIPTION	DATE ECO APPR
 MATERIALS AND FINISHES: INNER CONDUCTOR - BERYLLIUM COPPER OUTER CONDUCTOR - BRASS, WHITE BRONZE PLATING NUT - BRASS, WHITE BRONZE PLATING INSULATOR - PTFE, NATURAL ELECTRICAL: A. IMPEDANCE: 50 OHM B. FREQUENCY RANGE: DC - 6 GHz C. VSWR: ≤1.05 (DC -36GHz) D. INSERTION LOSS: ≤0.05 (3GHz) E. DWS: 2500V F. INTERMODULATION: ≤-166 dBc (2 X 43 dBm) MECHANICAL: A. DURABILITY: 500 CYCLES MIN. B. TEMPERATURE RANGE: -40° C TO +85° C PACKAGING: A. OUANTITY: SINGLE PACK B. MARKING: BAG TO BE MARKED "AMPHENOL RF, AD-4310PNJ-1, AND DATE CODE" 				RELEASE TO MFG.	6/15/16 01061 KCE
UNLESS OTHERWISE SPECIFIED, DIMENSIONS ARE IN METRIC AND TOLERANCES ARE: <pre></pre>	MATERIAL	K. ELMES 03 ENGINEER D/ K. ELMES 03	ATE 3-May-16 ATE 3-May-16 4.3/10 PLU	FOMER OL All other sheets af IG TO N JACK	TTLINE DRAWING FOR INTERNAL USE ONLY Amphenol RF www.amphenolrf.com
other data by Amphenol Corp., or to any other person to anyone for any purpose is not to be regarded by implication or otherwise in any manner licensing, granting rights to permitting such holder or any other person to manufacture, use or sell any product process or design potential or otherwise that any for any be related to	REFERENCE EAR# 7112 CONFIGURATION LEVEL: In Work	K. CAPOZZI 6.	ATE /15/16 SCALE: 1.0:1.0 S	HEET 2 OF 2	DRAWING NO.AD-43I0PNJ-I ITEM NO.AD-43I0PNJ-I
or disclosed by said drawings, specifications, or other data.	FINISH	CAD FILE	dwg size B	I KEV L	PART NO.AD-43I0PNJ-I
		1		, v	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: AD-4310PNJ-1