

|  |  | REVISIONS   |                 |
|--|--|---|-----------------|
|  |  | REV ECO DESCRIPTION DATE BY APPR  | R               |
|  |  | A1 - RELEASE NUMBER 27/JUL/2021 LOUIE TOMM  | /IY             |
| 9.53   | 4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.765-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4.755-<br>4. | L L L L L L L L L L L L L L L L L L L   |                 |
| KEY-A CONFIGURATION  | KEY-B CONFIGURATION  | KEY-C CONFIGURATION   |                 |
| PART NUMBERCOLOR OF HOUSINGAT16-15SA-K003BLACKAT16-15SA-EK02GRAY | PART NUMBER COLOR OF HOUSING<br>AT16-15SB-K003 BLACK   | PART NUMBERCOLOR OF HOUSINGAT16-15SC-K003BLACKAT16-15SC-EK02GRAY  | AI 10-133A-AAAA |
|  |  | SEE PIN CHART   |                 |
|  |  | PART NUMBER DESCRIPTION T   | EM              |
|  |  | UNLESS OTHERWISE SPECIFICATIONS: SIGNATURES DATERIALS LIST   UNLESS OTHERWISE SPECIFICATIONS: SIGNATURES DATERIALS SIGNATURES   UNLESS OTHERWISE SPECIFICATIONS: SIGNATURES DATERIALS SIGNATURES   UNLESS OTHERWISE SPECIFICATIONS: SIGNATURES DATERIALS SIGNATURES DATERIALS   STORE reference APPROVAL DUE N ZUMUZOT ASUBSIDIARY of Amphenol Corporation   STORE reference APPROVAL TOMPYXE ZUMUZOT ASUBSIDIARY of Amphenol Corporation   MATERIAL SPECIFICATIONS: TOMPYXE ZUMUZOT DUSTORER: TOMPYXE SUBJORD   PROCESS SPECIFICATIONS: THERMAN OF SUBPLET FOR<br>SPECIFICATIONS APPENDIX OF AUPPLED AND<br>OF REPORTATIONS APPLED AND<br>OF R | 1               |

|   |  |   | REVISIONS   |                    |            |          |
|---|--|---|---|--------------------|------------|----------|
|   | REV  | ECO   | DESCRIPTION   | DATE               | BY         | APPR     |
|   | A1   | -   | RELEASE NUMBER  | 27/JUL/2021        | LOUIE      | TOMMY    |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  | 9.53  |   |                    |            |          |
|   |  |   |   |                    |            |          |
| ¢.  | ¢.   |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  | hì  |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   | -15SE  | H1  |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   | <u>    </u> }  | }   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  | ╘───  |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
| KEY-D CONFIGURATION                         | KEY-E CONFIGURATI  | N   |   |                    |            |          |
| PART NUMBER COLOR OF HOUSING                |  | F HOUSING   |   |                    |            |          |
|   | AT16-15SE-K003 BLAG  |   |   |                    |            |          |
| AT16-15SD-K003 BLACK<br>AT16-15SD-EK02 GRAY | AT16-155E-EK02 GRA   |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  |   |   |                    |            |          |
|   |  | E P/N CHART   |   |                    |            |          |
|   |  | T NUMBER  | DES   | CRIPTION           |            | ITEM     |
|   | QUANTITY   | MA  | TERIALS LIS   |                    |            |          |
|   | UNLESS OTHERWISE SPECIF<br>1) All dimensions are in metric(m   |   | ES DATE SINF SV   | stems Corpo        | ration     |          |
|   | 2) Tolerances are as follows:<br>1 PL DEC ±0.30   Fractions ±<br>2 PL DEC ±0.15   Angles ±1*<br>3 PL DEC ±0.08 |   |   | sidiary of Ampheno |            |          |
|   | 3 PL DEC ±0.08 August 1<br>3) Note reference =   | ENGINEER:   | 44724   | Morley Drive       | 5, 00, p01 | 10001    |
|   | MATERIAL SPECIFICATIONS:   |   | E 29/JUL/2021   | Township, MI 48036 |            |          |
|   |  | CUSTOMER:   |   | ON PLUG, SOCKE     | T,AT SE    | RIES     |
|   | PROCESS SPECIFICATIONS:  | THIS DRAWING IS SUPPL<br>INFORMATION ONLY. DES<br>SPECIFICATIONS AND PE<br>SHOWN HEREON ARE TH<br>THE AMPHENOL CORPOR | IED FOR<br>SIGN FEATURES,<br>RFORMANCE DATA SIZE FSCM NO. DW    | IG NO:             |            | REVISION |
|   |  |   |   |                    |            |          |
|   |  | SHOWN HEREON ARE TH<br>THE AMPHENOL CORPOR<br>OF REPRODUCTION ARE<br>DIMENSIONS ARE SUBJE<br>MANUFACTURING VARIA      | E PROPERTY OF<br>RATION. NO RIGHTS<br>IMPLIED. ALL<br>TTO NOTAL | AT16-15SX->        | XXX        | A1       |

## AT Series<sup>™</sup> - Contact Size 16 Options

| Machined Contacts, Sockets & Pins |  |    |       |          |  |
|-----------------------------------|--|----|-------|----------|--|
| Part Number                       | Part Number Description                |    | AWG   | Туре     |  |
| AT60-215-1631                     | Male Contact - Pin, Gold-plated        | 16 | 14    | Machined |  |
| AT62-209-1631                     | Female Contact - Socket, Gold-plated   | 16 | 14    | Machined |  |
| AT60-215-16141                    | Male Contact - Pin, Nickel-plated      | 16 | 14    | Machined |  |
| AT62-209-16141                    | Female Contact - Socket, Nickel-plated | 16 | 14    | Machined |  |
| AT60-202-1631                     | Male Contact - Pin, Gold-plated        | 16 | 16-20 | Machined |  |
| AT62-201-1631                     | Female Contact - Socket, Gold-plated   | 16 | 16-20 | Machined |  |
| AT60-202-16141                    | Male Contact - Pin, Nickel-plated      | 16 | 16-20 | Machined |  |
| AT62-201-16141                    | Female Contact - Socket, Nickel-plated | 16 | 16-20 | Machined |  |
| AT60-202-1631-22                  | Male Contact - Pin, Gold-plated        | 16 | 22-24 | Machined |  |
| AT62-201-1631-22                  | Female Contact - Socket, Gold-plated   | 16 | 22-24 | Machined |  |
| AT60-202-16141-22                 | Male Contact - Pin, Nickel-plated      | 16 | 22-24 | Machined |  |
| AT62-201-16141-22                 | Female Contact - Socket, Nickel-plated | 16 | 22-24 | Machined |  |

|      | Tooling - Machined Contacts |  |  |  |  |
|------|-----------------------------|--|--|--|--|
| Part | Part Number                 | Description  |  |  |  |
| <    | CA-5D12                     | Universal Hand Crimp Tool, Size 12/16/20<br>(Machined contacts only) |  |  |  |
|      | CA-5E12                     | Pneumatic Crimp Tool, Size 12/16/20<br>(Machined contacts only)      |  |  |  |

|            | Contact Removal Tools |   |  |  |  |  |
|------------|-----------------------|---|--|--|--|--|
| Part       | Part Number           | Description   |  |  |  |  |
| 2 comments | ATRT-100              | Used for removal of contacts for A Series™ products |  |  |  |  |
|            | AT11-310-1605         | Contact Removal Tool, Plastic, Size 16              |  |  |  |  |
|            | A114017               | Sealing Plug, Size 16, White                        |  |  |  |  |

| Stamped & Formed Contacts, Sockets & Pins |  |      |       |                  |  |
|---|--|------|-------|------------------|--|
| Part Number                               | Description                            | Size | AWG   | Туре             |  |
| AT60-14-0144                              | Male Contact - Pin, Gold-plated        | 16   | 14-16 | Stamped & Formed |  |
| AT62-14-0144                              | Female Contact - Socket, Gold-plated   | 16   | 14-16 | Stamped & Formed |  |
| AT60-14-0122                              | Male Contact - Pin, Nickel-plated      | 16   | 14-16 | Stamped & Formed |  |
| AT62-14-0122                              | Female Contact - Socket, Nickel-plated | 16   | 14-16 | Stamped & Formed |  |
| AT60-16-0144                              | Male Contact - Pin, Gold-plated        | 16   | 16-18 | Stamped & Formed |  |
| AT62-16-0144                              | Female Contact - Socket, Gold-plated   | 16   | 16-18 | Stamped & Formed |  |
| AT60-16-0122                              | Male Contact - Pin, Nickel-plated      | 16   | 16-18 | Stamped & Formed |  |
| AT62-16-0122                              | Female Contact - Socket, Nickel-plated | 16   | 16-18 | Stamped & Formed |  |
| AT60-16-0644                              | Male Contact - Pin, Gold-plated        | 16   | 18-20 | Stamped & Formed |  |
| AT62-16-0644                              | Female Contact - Socket, Gold-plated   | 16   | 18-20 | Stamped & Formed |  |
| AT60-16-0622                              | Male Contact - Pin, Nickel-plated      | 16   | 18-20 | Stamped & Formed |  |
| AT62-16-0622                              | Female Contact - Socket, Nickel-plated | 16   | 18-20 | Stamped & Formed |  |
| AT60-16-0844                              | Male Contact - Pin, Gold-plated        | 16   | 20-22 | Stamped & Formed |  |
| AT62-16-0844                              | Female Contact - Socket, Gold-plated   | 16   | 20-22 | Stamped & Formed |  |
| AT60-16-0822                              | Male Contact - Pin, Nickel-plated      | 16   | 20-22 | Stamped & Formed |  |
| AT62-16-0822                              | Female Contact - Socket, Nickel-plated | 16   | 20-22 | Stamped & Formed |  |

|      | Tooling - Stamped & Formed Contacts |   |  |  |  |  |
|------|-------------------------------------|---|--|--|--|--|
| Part | Part Number                         | Description   |  |  |  |  |
|      | MFX-3950                            | Crimp Die - Size 16, 18-20AWG (S&F contacts only)       |  |  |  |  |
|      | MFX-3953                            | Crimp Die - Size 16, 16-18AWG (S&F contacts only)       |  |  |  |  |
|      | MFX-3975                            | Crimp Die - Size 16, 14-16AWG (S&F contacts only)       |  |  |  |  |
|      | MFX-3990                            | Crimp Die - Size 16, 20-22AWG (S&F contacts only)       |  |  |  |  |
|      | ATT-16-00                           | Hand Crimp Tool - Size 16, 14-16AWG (S&F contacts only) |  |  |  |  |
|      | ATT-16-01                           | Hand Crimp Tool - Size 16, 18-20AWG (S&F contacts only) |  |  |  |  |
|      | ATT-1612-03                         | Hand Crimp Tool - Size 16, 20-22AWG (S&F contacts only) |  |  |  |  |

Amphenol Sine Systems 44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

## **ATP Series™** - Contact Size 12 Options

| Machined Contacts, Sockets & Pins |  |      |       |          |  |
|-----------------------------------|--|------|-------|----------|--|
| Part Number                       | Description                            | Size | AWG   | Туре     |  |
| AT60-204-12141-10                 | Male Contact - Pin, Nickel-plated      | 12   | 10-12 | Machined |  |
| AT62-203-12141-10                 | Female Contact - Socket, Nickel-plated | 12   | 10-12 | Machined |  |
| AT60-220-1231                     | Male Contact - Pin, Gold-plated        | 12   | 12-14 | Machined |  |
| AT62-210-1231                     | Female Contact - Socket, Gold-plated   | 12   | 12-14 | Machined |  |
| AT60-204-12141                    | Male Contact - Pin, Nickel-plated      | 12   | 12-14 | Machined |  |
| AT62-203-12141                    | Female Contact - Socket, Nickel-plated | 12   | 12-14 | Machined |  |

|              | Stamped & Formed Contacts, Sockets & Pins |      |       |                  |  |  |
|--------------|---|------|-------|------------------|--|--|
| Part Number  | Description                               | Size | AWG   | Туре             |  |  |
| AT60-12-0244 | Male Contact - Pin, Gold-plated           | 12   | 10-12 | Stamped & Formed |  |  |
| AT62-12-0244 | Female Contact - Socket, Gold-plated      | 12   | 10-12 | Stamped & Formed |  |  |
| AT60-12-0222 | Male Contact - Pin, Nickel-plated         | 12   | 10-12 | Stamped & Formed |  |  |
| AT62-12-0222 | Female Contact - Socket, Nickel-plated    | 12   | 10-12 | Stamped & Formed |  |  |
| AT60-12-0144 | Male Contact - Pin, Gold-plated           | 12   | 12-14 | Stamped & Formed |  |  |
| AT62-12-0144 | Female Contact - Socket, Gold-plated      | 12   | 12-14 | Stamped & Formed |  |  |
| AT60-12-0166 | Male Contact - Pin, Nickel-plated         | 12   | 12-14 | Stamped & Forme  |  |  |
| AT62-12-0166 | Female Contact - Socket, Nickel-plated    | 12   | 12-14 | Stamped & Forme  |  |  |

| Smaller AWG for Diagnostic Applications • Gold-plated • Increased Mating Cycles • Cost-effective |   |      |     |          |
|--|---|------|-----|----------|
| Part Number  | Description   | Size | AWG | Туре     |
| 65-54749   | Male Contact - DiagnosticGrade™, Pin, Gold-plated         | 12   | 20  | Machined |
| AT62-210-1231-1820   | Female Contact - DiagnosticGrade™, Socket,<br>Gold-plated | 12   | 20  | Machined |

DiagnosticGrade™ Machined Contacts, Sockets & Pins

|        | Tooling - Machined Contacts |  |  |  |  |
|--------|-----------------------------|--|--|--|--|
| Part   | Part Number                 | Description  |  |  |  |
| $\leq$ | CA-5D12                     | Universal Hand Crimp Tool, Size 12/16/20<br>(Machined contacts only) |  |  |  |
| 38 F   | CA-5E12                     | Pneumatic Crimp Tool, Size 12/16/20<br>(Machined contacts only)      |  |  |  |

|           | Contact Removal Tools |   |  |  |  |
|-----------|-----------------------|---|--|--|--|
| Part      | Part Number           | Description   |  |  |  |
| - and and | ATRT-100              | Used for removal of contacts for A Series™ products |  |  |  |
|           | AT11-337-1205         | Contact Removal Tool, Plastic, Size 12              |  |  |  |
|           | A114017               | Sealing Plug, Size 12, White                        |  |  |  |

| Tooling - Stamped & Formed Contacts |             |   |
|-------------------------------------|-------------|---|
| Part                                | Part Number | Description   |
|                                     | MFX-3973    | Crimp Die - Size 12 (S&F contacts only)                       |
|                                     | MFX-3985    | Crimp Die - Size 12 (S&F contacts only) 10-12AWG -02XX Series |
|                                     | ATT-12-00   | Hand Crimp Tool - Size 12, 12AWG (S&F contacts only)          |

## Amphenol Sine Systems

44724 Morley Drive Clinton Township, MI 48036 USA www.amphenol-sine.com 09/2021

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Amphenol: AT16-15SB-K003