


THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1

REV	DESCRIPTION	DATE	BY
A	INITIAL RELEASE	10/28/22	YA



Dwg. Number	Customer P/N	Times P/N	Length(L) in 'inch'
IE-00419-01	-	IBPS047-KMKM-4.0IN	4 +0.20/-0
IE-00419-02	-	IBPS047-KMKM-6.0IN	6 +0.20/-0
IE-00419-03	-	IBPS047-KMKM-8.0IN	8 +0.20/-0
IE-00419-04	-	IBPS047-KMKM-10.0IN	10 +0.20/-0
IE-00419-05	-	IBPS047-KMKM-12.0IN	12 +0.24/-0

1.0 Scope

This drawing documents the construction and performance of PT- 047 cable assemblies manufactured by Times Microwave systems.

2.0 Cable Information

- 2.1 Cable to be PT-047
- 2.2 Jacket color to be Blue
- 2.3 Jacket material to be FEP
- 2.4 Nominal cable impedance to be 50 ohms
- 2.5 Cable diameter to be 0.062" [1.58mm] (Nominal).

3.0 Connector Information

- 3.1 Forward Connector
 - Type K (M) Straight Connector (SP107)
 - Connector Body – Stainless Steel, Gold Plated
 - Center Contact – Beryllium Copper, Gold Plated
- 3.2 After Connector
 - Type K (M) Straight Connector (SP107)
 - Connector Body – Stainless Steel, Gold Plated
 - Center Contact – Beryllium Copper, Gold Plated

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.

These drawings and specifications contain proprietary information which is the property of Times Microwave Systems.

Approvals

Drawn YA 10/28/22

Checked

Approved



TIMES MICROWAVE SYSTEMS

www.timesmicrowave.com

PT-047 CABLE ASSEMBLY
(Space Assemblies)

Size A CAGE CODE 68999 Drawing No.: IE-00419-XX

Scale: NA

Rev. (A)

Sheet: 1 of 2

THE REVISION STATUS OF ALL SHEETS OF THIS DRAWING IS THE SAME AS SHEET 1

REV	DESCRIPTION	DATE	BY
A	INITIAL RELEASE	10/28/22	YA

4.0 Electrical Performance

4.1 Frequency range: DC – 40GHz

4.2 Insertion loss & VSWR: As per below table,

Dwg. Number	Max. Insertion Loss in dB	Max. VSWR
	@ 40GHz	@ 40GHz
IE-00419-01	1.45	1.40
IE-00419-02	1.94	1.40
IE-00419-03	2.43	1.40
IE-00419-04	2.92	1.40
IE-00419-05	3.43	1.40

5.0 Mechanical Performance

5.1 Overall Length to be specified length.

5.2 Minimum Bend radius is 0.25" [6.5mm].

6.0 Environmental Performance

6.1 Installation Temperature Range (-65°C to +150°C)

6.2 Storage Temperature Range (-65°C to +150°C)

6.3 Operating Temperature Range (-65°C to +150°C)

7.0 NOTES

7.1 All Dimensions are in INCH.

7.2 Assemblies built in Class 100,000 clean room.

7.3 Low outgassing materials per ASTM E595.

7.4 Unless Otherwise Specified: Tolerance will be,

Linear Dimension	Tolerance
<20 INCH	±0.4 INCH
20-79 INCH	±0.6 INCH
>79 INCH	±0.8 INCH

****Tolerances are not accumulative.**

Unless otherwise specified, dimensions are in INCH. Tolerances are applicable when specified.

These drawings and specifications contain proprietary information which is the property of Times Microwave Systems.

Approvals

Drawn YA 10/28/22

Checked

Approved



TIMES MICROWAVE SYSTEMS

www.timesmicrowave.com

PT-047 CABLE ASSEMBLY
(Space Assemblies)

Size
A

CAGE CODE
68999

Drawing No.:
IE-00419-XX

Scale: NA

Rev. (A)

Sheet: 2 of 2

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[IBPS047-KMKM-10.0IN](#) [IBPS047-KMKM-12.0IN](#) [IBPS047-KMKM-4.0IN](#) [IBPS047-KMKM-6.0IN](#) [IBPS047-KMKM-8.0IN](#)