

NOTES:

1) LABEL REQUIREMENT:

LABELS ARE M23053/5 ,WHITE. ACCEPTABLE SUBSTITUTION IS DAT-38-292 OR TRANSVINYL (DAT-63-292-2.5).

2) ASSEMBLY REQUIREMENT:

USE ND353 EPOXY FOR TERMINATION.

REVISION HISTORY - ALL SHEETS ARE AT THE SAME REVISION

REV	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	2019/04/17	



3	C24712	FLIGHTLINX 50/125 OM3 SIMPLEX	3.78 FEET
2	961-251-2C1	SIMPLEX LC, MM, BEIGE HOUSING, 2MM MINI BOOT	1
1	M29N0226Y	TERMINUS ASSY, PC, NO KEY, WITH CRIMP SLEEVE, 126um	1
ITEM NO.	PART NO.	DESCRIPTION	QTY/ LENGTH

		MATERIAL:	DFTR/Designer: C. Hoang 2019/04/12	Amphenol FSI	
			Check By: S. McEwan 2019/04/15		
			Manufacturing: S. McEwan 2019/04/15	TITLE: NGCON TERMINI TO LC ASSEMBLY, MM, 50/125um	
			Market Manager/PLM: Q. Abraham 2019/04/16		
			Configuration Management: L. Brown 2019/04/17	SIZE A	
		DRILLED HOLE DIAMETER TOLERANCE Ø.000 TO Ø.125 $\begin{smallmatrix} +.001 \\ -.001 \end{smallmatrix}$ Ø.126 TO Ø.250 $\begin{smallmatrix} +.001 \\ -.001 \end{smallmatrix}$ Ø.251 TO Ø.500 $\begin{smallmatrix} +.002 \\ -.002 \end{smallmatrix}$ Ø.501 TO Ø.750 $\begin{smallmatrix} +.003 \\ -.003 \end{smallmatrix}$	CAGE CODE 0YPM2		DWG NO 18041108QA-D2
		DO NOT SCALE THIS DRAWING UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE IN INCHES. TOLERANCES ON 3 PL = ±.010 2 PL = ±.020 ANGLES = ±3° INTERPRET DIM AND TOL PER ASME 14.5M-1994			
	NEXT ASSY	USED ON	SCALE: NONE		REV -
	APPLICATION				
			SHEET 1 OF 1		

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[18041108QA-D2](#)