

4

3

2

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

10-729922-000

10-729922-000

10-729922-000

10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000

REV. A

SHEET 1 OF 1

DOCUMENT NO. 10-729922-000


REV. A


SHEET 1 OF 1


DOCUMENT NO. 10-729922-000


GENERAL TOLERANCE

DIM. RANGE	0.5 ~ 3	> 3 ~ 6	> 6 ~ 30	> 30 ~ 120	> 120 ~ 400
TOLERANCE	±0.1	±0.1	±0.2	±0.3	±0.5









CUSTOMER DRAWING

NOTES:

1. THE REFERENCED PRODUCT IS IN COMPLIANCE WITH THE MAXIMUN CONCENTRATION VALUES(MCVS) SET FORTH IN THE 2009/125/EC AMENDMENT TO 2011/65/EC RoHS DIRECTIVE.

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION AND SUCH INFORMATION MAY NOT BE DISCLOSED TO OTHERS FOR ANY PURPOSE OR USED FOR MANUFACTURING PURPOSES WITHOUT WRITTEN PERMISSION FROM THE AMPHENOL CORP.

N/A

NEXT ASSEMBLY

METRIC DOCUMENT

PRO/ENGINEER INFORMATION

Pro/e Model Used: 10-729922-000.ASSEM

Drawing Name: 10-729922-000-CUS-A

UNLESS OTHERWISE SPECIFIED

SPECIFICATIONS

POS

QTY

PART NUMBER

DESCRIPTION

NOTE

LINEAR DIMENSIONS ARE IN: MILLIMETERS

TOLERANCES: ANGLES= ±2° DEFAULT LINEAR TOLERANCES SEE TABLE

DIM. & TOL. PER ASME Y14.5M-1994; DRW PER MIL-DTL-31000; OTHER AMPHENOL STANDARDS: 9-9318

LEGENDS: △=FLAG NOTE CALL OUT REFERENCE ONLY

MATERIAL SPEC.

N/A

PROCESS SPEC.

N/A

APPROVALS

DATE

THIRD ANGLE PROJECTION

PREPARED BY

ENGINEER IN CHARGE

DESIGN MANAGER

DESIGN ACTIVITY GROUP

CHRIS LI

CHRIS LI

RAN XIAO

C&I

13-Nov-13

AMPHENOL INDUSTRIAL OPERATIONS

Amphenol Technology(Zhuhai)Co.,Ltd

No.63, Xingnan Road, Sanzao Town, Jinwan, Zhuhai, PRC

3.6MM WTB PIN&LOCKING CLIP ASS

SIZE

CAGE CODE

DOCUMENT NO.

REV.

C

77820

10-729922-000

A

SCALE: 4.0

REF.

SHEET 1 OF 1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[10-729922-000](#)