

1	2	3	4	5	6	7	8
C5	White	4		REV. B C	ECN NO. LE3-720039 DATE 2007/01/24	SIGN Simon	DESCRIPTION Add Copper Foil
C4	Purple	4				Ruru	Change Logo & SR
C3	Blue	1					
C2	Green	1					
C1	RED	1					
24	White						
23	Blue	2					
22	Drain						
21							
20							
19	Drain						
18	Green	2					
17	White						
16	Green	4					
15	Orange						
14	Yellow	3					
13							
12							
11	Drain						
10	Red	2					
9	White						
8	Red	4					
7	Brown	4					
6	Black	4					
5							
4							
3	Drain						
2	Brown	2	Type 4 1C				
1	White		Type 3 1P				
Conn.	Wire Color	Wire Type	Type 2 1P+D+AL+MY				
Pin Out			Type 1 Coax				
UNIT:mm			TITLE DIS 18+5 M Pin M Conn 180	ITEM NO.	DRAWN BY Ruru	DATE 2017/06/30	
TOLERANCE		SCALE Free		SHEET 1 OF 1	DWG NO. DIS-23AMMM-SL7AXX	CHECKED BY Rita	DATE 2017/06/30
±0.5 mm		REV. C	SIZE A4	QC :Inspection Item	CUSTOMER ALTW	APPROVED BY Max	DATE 2017/06/30
1	2	3	4	5	6	7	8 FMWI0702-01-01A2

Coax Spiral

Cable DIS-23AMMM-SL7000 Conn.

@Q(L(mm))

Φ8.5

ALTW
CONFIDENTIAL
2017.06.30
R&D DEPT.

NOTE:
 * Waterproof Rate : IP67
 * @Q Important Dimension To Check.
 * Housing : Black,ABS
 * Pin : Copper Alloy,Gold Plated
 * Gasket : Black,EPDM
 * SCREW : Steel,Nickel Plated
 * Cable : UL20276*3Coax(S)+(1P*28#+D+Al+Mylar)
 $*4C+(1P+6C)*28#+Al+B$, Black, OD=8.5mm
 * Cable Length Tolerance: 1M~5M±5%mm,
 * Wire Color : Coax 受 FOAMED PE 製程所影響, 實際 INSULATION 顏色較淡
 * DVI CONN. 的金屬殼與銅箔及 Braid 需做導通測試且能導通

Pin 8
Pin 1
Pin 17
Pin 24
Conn.
ALTW
DCC. DEPT.
CONFIDENTIAL
2017.07.06
ISSUED

52.6
50.9
DIS-23AMMM-SL7AXX
XX:01~05Meters
01:01Meter
02:02Meters
:
:
05:05Meters
Cable Length (L):01~05Meters

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Amphenol:](#)

[DIS-23AMMM-SL7A03](#) [DIS-23AMMM-SL7A04](#)